

Printing date 30.10.2024 Version number 5 Revision: 30.10.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 100 PMMA Series Resists in Chlorobenzene
- · Article number: M640002, M640003, M640004, M640005, M640006, M640007, M640008
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Product category PC30 Photo-chemicals
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Telephone: (617) 965-5511 Fax: (617) 965-5818

Importer:

A-Gas Electronic Materials

Unit 3, IO Centre

Swift Valley

Rugby, Warwickshire

CV21 1TW, UK

*Tel:* +44-0-1788-537535

Fax: +44-0-1788-535835

Website: www.agasem.com

Email: customerservice.em@agas.com

Kayaku Advanced Materials, Inc.

200 Flanders Road

Westborough, MA 01581

Tel: (617) 965-5511

Fax: (617) 965-5818

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuam.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511

Chemtrec USA Emergency: 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

(Contd. on page 2)



Printing date 30.10.2024 Revision: 30.10.2024 Version number 5

Trade name: 100 PMMA Series Resists in Chlorobenzene

(Contd. of page 1)



GHS08 health hazard

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



### GHS07

Acute Tox. 4 H302 Harmful if swallowed. H332 Harmful if inhaled. Acute Tox. 4 Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

#### · 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms









GHS02

GHS07

GHS08 GHS09

· Signal word Danger

## · Hazard-determining components of labelling:

Chlorobenzene

#### · Hazard statements

H226 Flammable liquid and vapour. H302+H332 Harmful if swallowed or if inhaled.

Causes skin irritation. H315

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

### · Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P280

IF SWALLOWED: Immediately call a POISON CENTER/doctor. P301+P310

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position P304+P341

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 3)



Printing date 30.10.2024 Version number 5 Revision: 30.10.2024

Trade name: 100 PMMA Series Resists in Chlorobenzene

(Contd. of page 2)

1-20%

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

## SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 108-90-7	Chlorobenzene	80-100%	
EINECS: 203-628-5	Flam. Liq. 3, H226; STOT RE 1, H372; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H336		
· Additional Components:			

Additional information: For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

9010-88-2 Poly(methyl methacrylate-co-ethyl acrylate)

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

(Contd. on page 4)



Printing date 30.10.2024 Version number 5 Revision: 30.10.2024

Trade name: 100 PMMA Series Resists in Chlorobenzene

(Contd. of page 3)

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

*In case of fire, the following can be released:* 

Hydrogen chloride (HCl)

Phosgene gas

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

## SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

*Use explosion-proof apparatus / fittings and spark-proof tools.* 

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

(Contd. on page 5)



Printing date 30.10.2024 Version number 5 Revision: 30.10.2024

Trade name: 100 PMMA Series Resists in Chlorobenzene

(Contd. of page 4)

· 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.

### · Ingredients with limit values that require monitoring at the workplace:

#### 108-90-7 Chlorobenzene

WEL Short-term value: 3 ppm Long-term value: 1 ppm Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Long-sleeved work clothes

## SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Colour: Clear

(Contd. on page 6)



Printing date 30.10.2024 Version number 5 Revision: 30.10.2024

Trade name: 100 PMMA Series Resists in Chlorobenzene

	(Contd. of page		
· Odour:	Mild		
· Odour threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. ve: 184 °C		
· Flash point:	28 °C		
· Flammability	Not applicable.		
· Auto-ignition temperature:	590 °C		
· Decomposition temperature:	Not determined.		
· Ignition temperature:	Product is not selfigniting.		
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.		
· Explosion limits: Lower: Upper:	1.3 Vol % 11.0 Vol %		
· Vapour pressure at 20 °C:	12 hPa		
· Density: · Relative density	Not determined Not determined. See Table 1 Other Information		
· Vapour density · Evaporation rate	Not determined. Not determined.		
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.		
Partition coefficient: n-octanol/water:	Not determined.		
· Viscosity:     Dynamic:     Kinematic:	Not determined. Not determined.		
· 9.2 Other information	Name         Number         Sp. Grav. VOC(%by wt.) VOC (g/L)           100C2         M640002         1.108         98         1085           100C3         M640003         1.109         97         1075           100C4         M640004         1.110         96         1065           100C5         M640005         1.111         95         1055           100C6         M640006         1.112         94         1045           100C7         M640007         1.113         93         1035           100C8         M640008         1.114         92         1025		

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 7)



Printing date 30.10.2024 Version number 5 Revision: 30.10.2024

Trade name: 100 PMMA Series Resists in Chlorobenzene

(Contd. of page 6)

· 10.4 Conditions to avoid

Contact with incompatible materials.

Heat, flames and sparks. Extremes of temperature and direct sunlight.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Hydrogen chloride (HCl)

Possible traces of Phosgene

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if swallowed or if inhaled.

· LD/LC50	· LD/LC50 values relevant for classification:		
108-90-7	108-90-7 Chlorobenzene		
Oral	LD50	1110 mg/kg (Rat)	
Dermal	LD50	>7940 mg/kg (rabbit)	
Inhalative	LC50	13.9 mg/L (Rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

· 12.1 Toxicity

	1211 10111011		
	· Aquatic toxicity: 108-90-7 Chlorobenzene		
Ī			
		4.30-16.00 mg/l (daphnia magna)	
	EC50/96 hr   12.5 mg/l (algae)		
LC100/48 h   0.03-28 mg/l (golden orfe)		0.03-28 mg/l (golden orfe)	
	LC50/76 h	4.5-7.4 mg/l (Lepomis macrochirus (Bluegill))	

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)



Printing date 30.10.2024 Version number 5 Revision: 30.10.2024

Trade name: 100 PMMA Series Resists in Chlorobenzene

(Contd. of page 7)

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name ADR, IATA IMDG	RESIN SOLUTION RESIN SOLUTION (CHLOROBENZENE), MARIN POLLUTANT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3 Prammavie riquius. 3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substance. Chlorobenzene
Marine pollutant:	Yes
	Warning: Flammable liquids.



Printing date 30.10.2024 Version number 5 Revision: 30.10.2024

Trade name: 100 PMMA Series Resists in Chlorobenzene

		(Contd. of page 8)
· EMS Number:	F-E,S-D	
· Segregation groups	Liquid halogenated hydrocarbons	
· 14.7 Transport in bulk according to A	Annex II of	
Marpol and the IBC Code	Not applicable.	
Transport/Additional information:		
· ADR		
Limited quantities (LQ)	5L	
Transport category 3		
Tunnel restriction code	D/E	
· UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, III	

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Poisons Act

· Regi	ılated	explosives	precursors
--------	--------	------------	------------

None of the ingredients is listed.

### · Regulated poisons

None of the ingredients is listed.

## · Reportable explosives precursors

None of the ingredients is listed.

#### · Reportable poisons

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)



Printing date 30.10.2024 Version number 5 Revision: 30.10.2024

#### Trade name: 100 PMMA Series Resists in Chlorobenzene

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids — Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

\* \* Data compared to the previous version altered.

GB ·