

Printing date 31.10.2024

Version number 5

Revision: 31.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: 200 PMMA Series Resists in Chlorobenzene

- · Article number:
- M740002, M740003, M740004, M740005, M740006, M740007, M740008, M740009, M740010, M740012
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- **Product category** PC30 Photo-chemicals
- · Application of the substance / the mixture Photoresist remover
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Kayaku Advanced Materials, Inc.
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818
- Further information obtainable from: Product Safety Email: productsafety@kayakuam.com
- 1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

GHS02 flame

-

Flam. Liq. 3 H226 Flammable liquid and vapour.

GHS08

GHS08 health hazard

STOT RE 1

H372 Causes damage to organs through prolonged or repeated exposure.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Acute Tox. 4	H302 Harmful if swallowed.
Acute Tox. 4	H332 Harmful if inhaled.
Skin Irrit. 2	H315 Causes skin irritation.

(Contd. on page 2)

GB



Revision: 31.10.2024

Safety data sheet according to UK REACH Printing date 31.10.2024 Version number 5 Trade name: 200 PMMA Series Resists in Chlorobenzene (Contd. of page 1) STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms GHS02 GHS07 GHS08 GHS09 · Signal word Danger · Hazard-determining components of labelling: Chlorobenzene · Hazard statements H226 Flammable liquid and vapour. H302+H332 Harmful if swallowed or if inhaled. Causes skin irritation. H315 H336 May cause drowsiness or dizziness. H372 Causes damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. · Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P302+P352 IF ON SKIN: Wash with plenty of soap and water. P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide. P403+P235 Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international P501 regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB



Printing date 31.10.2024

Version number 5

Revision: 31.10.2024

Trade name: 200 PMMA Series Resists in Chlorobenzene

	(Contd. of page 2)
· Dangerous components:	
CAS: 108-90-7 Chlorobenzene	80-100%
EINECS: 203-628-5 Flam. Liq. 3, H226; STOT RE 1, H372; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H336	
· Additional Components:	
9010-88-2 Poly(methyl methacrylate-co-ethyl acrylate)	1-20%

9010-88-2 Poly(methyl methacrylate-co-ethyl acrylate)

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. · After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• *After swallowing:* Do not induce vomiting; call for medical help immediately.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

• 5.1 Extinguishing media

- · Suitable extinguishing agents:
- Alcohol resistant foam
- Fire-extinguishing powder

ABC powder

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. *Ensure adequate ventilation* Keep away from ignition sources.
- · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

GB



Printing date 31.10.2024

Version number 5

Revision: 31.10.2024

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 3)

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Use only in well ventilated areas. Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Use explosion-proof apparatus / fittings and spark-proof tools.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• **Requirements to be met by storerooms and containers:** No special requirements.

• Information about storage in one common storage facility: Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions).

• Further information about storage conditions: Store in cool, dry conditions in well sealed containers. Protect from heat and direct sunlight. Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

108-90-7 Chlorobenzene

WEL Short-term value: 3 ppm Long-term value: 1 ppm Sk

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from food and beverages.

Wash hands before breaks and at the end of work.

• Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)



Printing date 31.10.2024

Version number 5

Revision: 31.10.2024

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 4)

GB

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Long-sleeved work clothes

9.1 Information on basic physical and ch	nemical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	Clear
Odour:	Mild
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	184 °C
Flash point:	28 °C
Flammability	Not applicable.
Auto-ignition temperature:	590 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits:	
Lower:	1.3 Vol %
Upper:	11.0 Vol %
Vapour pressure at 20 °C:	12 hPa
Density:	See Other information
Relative density	Not determined.
Vapour density	Not determined.



Printing date 31.10.2024

Version number 5

Revision: 31.10.2024

Trade name: 200 PMMA Series Resists in Chlorobenzene

		(Contd. of page :	
· Evaporation rate	Not determined.		
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.		
· Partition coefficient: n-octanol/water:	Not determined.		
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.		
• 9.2 Other information	Name Number Sp.Grav. VOC(%by wt.) VOC (g/L) 200C2 M740002 1.108 98 1085 200C3 M740003 1.109 97 1075 200C4 M740004 1.110 96 1065 200C5 M740005 1.111 95 1055 200C6 M740006 1.112 94 1045 200C7 M740007 1.113 93 1035 200C8 M740008 1.114 92 1025 200C9 M740009 1.115 91 1015 200C10 M740010 1.117 90 1005 200C12 M740012 1.118 88 985		

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid
- Heat, flames and sparks. Extremes of temperature and direct sunlight.
- Contact with incompatible materials.
- · 10.5 Incompatible materials:
- Strong Oxidizing Agents, Strong Bases, Strong Acids, Strong Reducing Agents, Iron, Hydrazine
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity
- Harmful if swallowed or if inhaled.
- · LD/LC50 values relevant for classification:
- 108-90-7 Chlorobenzene
- Oral LD50 2290 mg/kg (Rat)
- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 7)

⁻ GB ·



Revision: 31.10.2024

Printing date 31.10.2024

Version number 5

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 6)

· Additional toxicological information:

• CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA

UN1866

· 14.2 UN proper shipping name · ADR

1866 RESIN SOLUTION

(Contd. on page 8)

GB -



Revision: 31.10.2024

Printing date 31.10.2024

Version number 5

Trade name: 200 PMMA Series Resists in Chlorobenzene

	(Contd. of page
IMDG	RESIN SOLUTION (CHLOROBENZENE), MARINA POLLUTANT
IATA	RESIN SOLUTION
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances Chlorobenzene
Marine pollutant:	Yes
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E,S-D
Segregation groups	Liquid halogenated hydrocarbons
14.7 Transport in bulk according to Annex II of	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
UN "Model Regulation":	UN1866, RESIN SOLUTION, ENVIRONMENTALL HAZARDOUS, 3, III

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

(Contd. on page 9)

⁻ GB



Printing date 31.10.2024

Version number 5

Revision: 31.10.2024

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 8)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour. H302 Harmful if swallowed. H315 Causes skin irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H372 Causes damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. · Department issuing SDS: Product safety department · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com) · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 * * Data compared to the previous version altered.