

Printing date 01/28/2022 Reviewed on 01/28/2022

1 Identification

- · Product identifier
- Trade name: 200 PMMA Series Resists in Chlorobenzene
- · Product number:

M740002, M740003, M740004, M740005, M740006, M740007, M740008, M740009, M740010, M740012

- · Application of the substance / the mixture Photoresist remover
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials, Inc.

200 Flanders Road

Westborough, MA 01581 Tel: (617) 965-5511

Tel: (617) 965-5511 Fax: (617) 965-5818

· Information department:

Product Safety

Email: productsafety@kayakuAM.com

· Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300

Chemtrec International Emergency: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

 (Contd. on page 2)



Printing date 01/28/2022 Reviewed on 01/28/2022

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 1)

· Hazard pictograms









GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Chlorobenzene

· Hazard statements

H226 Flammable liquid and vapor. H302+H332 Harmful if swallowed or if inhaled.

Causes skin irritation. H315

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 *If on skin: Wash with plenty of soap and water.*

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 *If eye irritation persists: Get medical advice/attention.*

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)



Printing date 01/28/2022 Reviewed on 01/28/2022

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 2)

· vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

Γ	· Dangerou	s components:	
		Chlorobenzene ♠ Flam. Liq. 3, H226; ♦ STOT RE 1, H372; ♦ Aquatic Chronic 2, H411; ♦ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H336	80-100%
ſ	· Additiona	l Components:	
	9010-88-2	Poly(methyl methacrylate-co-ethyl acrylate)	1-20%

4 First-aid measures

- · Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Wear SCBA.



Printing date 01/28/2022 Reviewed on 01/28/2022

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 3)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Use only in well ventilated areas.

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Keep container well-sealed in cool, dry location.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)



Printing date 01/28/2022 Reviewed on 01/28/2022

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 4)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Wash hands before breaks and at the end of work.

· Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material Contact glove manufacture for break-through time.
- · Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Informa	tion	
· Appearance:		
Form:		Fluid

Information on basic physical and chemical properties

Color: Clear
Odor: Mild

• Odor threshold: Not determined.
• pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:184 °C (363.2 °F)

Flash point: 28 °C (82.4 °F)
 Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 590 °C (1,094 °F)

Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 1.3 Vol % Upper: 11.0 Vol %

(Contd. on page 6)



Printing date 01/28/2022 Reviewed on 01/28/2022

Trade name: 200 PMMA Series Resists in Chlorobenzene

				(Contd. of page
· Vapor pressure at 20 °C (68 °F):	12 hPa (9 mm Hg)			
· Density:	See other information			
· Relative density	Not determined.			
· Vapor density	Not determined.			
· Evaporation rate	1.6-2.3 (BuAc=1)			
· Solubility in / Miscibility with				
Water:	Water miscible No			
· Partition coefficient (n-octanol/wate	r): Not determined.			
· Viscosity:				
Dynamic:	Not determined.			
Kinematic:	Not determined.			
· Other information	Name Number Sp.Grav. Vol	.(%by w	t.) VOC (g/L)	
·	200C2 M740002 1.108	98	1085	
	200C3 M740003 1.109	97	1075	
	200C4 M740004 1.110	96	1065	
	200C5 M740005 1.111	95	1055	
	200C6 M740006 1.112	94	1045	
	200C7 M740007 1.113	93	1035	
	200C8 M740008 1.114	92	1025	
	200C9 M740009 1.115	91	1015	
	200C10 M740010 1.117	90	1005	
	200C12 M740012 1.118	88	985	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

· Incompatible materials:

Strong Oxidizing Agents, Strong Bases, Strong Acids, Strong Reducing Agents, Iron, Hydrazine

· Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

108-90-7 Chlorobenzene

Oral LD50 2290 mg/kg (Rat)

- Primary irritant effect:
- on the skin: No irritant effect.

(Contd. on page 7)



Printing date 01/28/2022 Reviewed on 01/28/2022

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 6)

- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.

Disposal must be made in accordance with Federal, State, and Local regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.



Printing date 01/28/2022 Reviewed on 01/28/2022

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 7)

UN-Number	
DOT, ADR, IMDG, IATA	UN1866
UN proper shipping name	
DOT, ADR	Resin solution
IMDG	RESIN SOLUTION (CHLOROBENZENE), MARIN POLLUTANT
IATA	RESIN SOLUTION
Transport hazard class(es)	
DOT	
7.4.00.000	
Class	3 Flammable liquids
Label	3
Class	3 Flammable liquids
Class Label	3 Flammable liquids 3
Label Packing group	-
Label	-
Label Packing group	III Product contains environmentally hazardous substance
Label Packing group DOT, ADR, IMDG, IATA	JIII
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Marine pollutant:	III Product contains environmentally hazardous substance Chlorobenzene
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards:	III Product contains environmentally hazardous substance. Chlorobenzene Yes Warning: Flammable liquids
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user	III Product contains environmentally hazardous substance Chlorobenzene Yes Warning: Flammable liquids
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Hazard identification number (Kemler code)	III Product contains environmentally hazardous substance. Chlorobenzene Yes Warning: Flammable liquids : 30
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Hazard identification number (Kemler code) EMS Number: Segregation groups Transport in bulk according to Annex II of	III Product contains environmentally hazardous substance. Chlorobenzene Yes Warning: Flammable liquids: 30 F-E,S-D Liquid halogenated hydrocarbons
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Hazard identification number (Kemler code) EMS Number: Segregation groups	III Product contains environmentally hazardous substance. Chlorobenzene Yes Warning: Flammable liquids : 30 F-E,S-D

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

(Contd. on page 9)



Printing date 01/28/2022 Reviewed on 01/28/2022

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 8)

· Section 313 (Specific toxic chemical listings):

108-90-7 Chlorobenzene

- TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.
- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

108-90-7 Chlorobenzene

D

· TLV (Threshold Limit Value)

108-90-7 Chlorobenzene

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

108-90-7 Chlorobenzene

New Jersey State Right To Know List

108-90-7 Chlorobenzene

· Pennsylvania Hazardous Substances List

108-90-7 Chlorobenzene

- · California SCAQMD Rule 443.1 VOC's: No information available.
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS07

GHS08

GHS09

- · Signal word Danger
- · Hazard-determining components of labeling:

Chlorobenzene

· Hazard statements

H226 Flammable liquid and vapor.

H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.



Printing date 01/28/2022 Reviewed on 01/28/2022

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 9)

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

- Date of preparation / last revision 01/28/2022 / 4
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

 ${\it IATA: International Air Transport Association}$

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

 $PEL: Permissible\ Exposure\ Limit$

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

(Contd. on page 11)



Printing date 01/28/2022 Reviewed on 01/28/2022

Trade name: 200 PMMA Series Resists in Chlorobenzene

(Contd. of page 10)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.