

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2022

Version number 3

Revision: 01.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· **Trade name:** 2200 PMMA Series Resists in Anisole

· **Article number:** 2200A1.5, 2200A2, 2200A3, 2200A4, 2200A5, 2200A6, 2200A7, 2200A8, 2200A9, 2200A10

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· **Sector of Use** SU16 Manufacture of computer, electronic and optical products, electrical equipment

· **Product category** PC30 Photo-chemicals

· **Application of the substance / the mixture** Photoresist

· 1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

Manufacturer:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Telephone: (617) 965-5511

Fax: (617) 965-5818

Importer:

A-Gas Electronic Materials

Unit 3, IO Centre

Swift Valley

Rugby, Warwickshire

CV21 1TW, UK

Tel: +44-0-1788-537535

Fax: +44-0-1788-535835

Website: www.agasem.com

Email: customerservice.em@agas.com

· **Further information obtainable from:**

Product Safety

Email: productsafety@kayakuAM.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511

Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**



Flam. Liq. 3 H226 Flammable liquid and vapour.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2022

Version number 3

Revision: 01.02.2022

Trade name: 2200 PMMA Series Resists in Anisole

(Contd. of page 1)

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Warning

Hazard-determining components of labelling:

Anisole

Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2022

Version number 3

Revision: 01.02.2022

Trade name: 2200 PMMA Series Resists in Anisole

(Contd. of page 2)

· Dangerous components:

CAS: 100-66-3 EINECS: 202-876-1	Anisole ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	80-100%
------------------------------------	---	---------

· Additional Components:

CAS: 9011-14-7 EC number: 618-466-4	Poly(methyl methacrylate)	1-20%
--	---------------------------	-------

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media
· Suitable extinguishing agents:

Alcohol resistant foam
Fire-extinguishing powder
Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet
Water

· 5.2 Special hazards arising from the substance or mixture No further relevant information available.

· 5.3 Advice for firefighters
· Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.02.2022

Version number 3

Revision: 01.02.2022

Trade name: 2200 PMMA Series Resists in Anisole

(Contd. of page 3)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**· 7.1 Precautions for safe handling**

Use only in well ventilated areas.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Use only under yellow light

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· 7.2 Conditions for safe storage, including any incompatibilities**· Storage:****· Requirements to be met by storerooms and containers:**

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products.

· Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

· Further information about storage conditions:

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

Store in cool, dry conditions in well sealed containers.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from exposure to the light.

· 7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****· 8.1 Control parameters****· Additional information about design of technical facilities:** No further data; see item 7.**· Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists valid during the making were used as basis.**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

· Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2022

Version number 3

Revision: 01.02.2022

Trade name: 2200 PMMA Series Resists in Anisole

(Contd. of page 4)

· Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves Nitrile rubber, NBR

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:


Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties
· General Information
· Appearance:

Form:	Liquid
Colour:	Clear to light yellow
· Odour:	Strong
· Odour threshold:	Not determined.

· pH-value:	Not determined.
--------------------	-----------------

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	184 °C

· Flash point:	43 °C
-----------------------	-------

· Flammability (solid, gas):	Not applicable.
-------------------------------------	-----------------

· Ignition temperature:	475 °C
--------------------------------	--------

· Decomposition temperature:	Not determined.
-------------------------------------	-----------------

· Auto-ignition temperature:	Product is not selfigniting.
-------------------------------------	------------------------------

· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
--------------------------------	---

· Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapour pressure at 20 °C:	0.4 hPa
------------------------------------	---------

· Density:	Not determined
· Relative density	See Table 1 Other Information
· Vapour density	Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2022

Version number 3

Revision: 01.02.2022

Trade name: 2200 PMMA Series Resists in Anisole

(Contd. of page 5)

· Evaporation rate	Not determined.																																																							
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.																																																							
· Partition coefficient: n-octanol/water:	Not determined.																																																							
· Viscosity:																																																								
Dynamic:	Not determined.																																																							
Kinematic:	Not determined.																																																							
· 9.2 Other information	<table><tr><td>Name</td><td>Number</td><td>Sp.Grav.</td><td>Vol.(%by wt.)</td><td>VOC (g/L)</td></tr><tr><td>2200A1.5</td><td>M830501</td><td>1.000</td><td>98.5</td><td>985</td></tr><tr><td>2200A2</td><td>M830002</td><td>1.000</td><td>98</td><td>980</td></tr><tr><td>2200A3</td><td>M830003</td><td>1.003</td><td>97</td><td>970</td></tr><tr><td>2200A4</td><td>M830004</td><td>1.004</td><td>96</td><td>960</td></tr><tr><td>2200A5</td><td>M830005</td><td>1.005</td><td>95</td><td>955</td></tr><tr><td>2200A6</td><td>M830006</td><td>1.006</td><td>94</td><td>945</td></tr><tr><td>2200A7</td><td>M830007</td><td>1.007</td><td>93</td><td>935</td></tr><tr><td>2200A8</td><td>M830008</td><td>1.009</td><td>92</td><td>930</td></tr><tr><td>2200A9</td><td>M830009</td><td>1.011</td><td>91</td><td>920</td></tr><tr><td>2200A10</td><td>M830010</td><td>1.012</td><td>90</td><td>910</td></tr></table>	Name	Number	Sp.Grav.	Vol.(%by wt.)	VOC (g/L)	2200A1.5	M830501	1.000	98.5	985	2200A2	M830002	1.000	98	980	2200A3	M830003	1.003	97	970	2200A4	M830004	1.004	96	960	2200A5	M830005	1.005	95	955	2200A6	M830006	1.006	94	945	2200A7	M830007	1.007	93	935	2200A8	M830008	1.009	92	930	2200A9	M830009	1.011	91	920	2200A10	M830010	1.012	90	910
Name	Number	Sp.Grav.	Vol.(%by wt.)	VOC (g/L)																																																				
2200A1.5	M830501	1.000	98.5	985																																																				
2200A2	M830002	1.000	98	980																																																				
2200A3	M830003	1.003	97	970																																																				
2200A4	M830004	1.004	96	960																																																				
2200A5	M830005	1.005	95	955																																																				
2200A6	M830006	1.006	94	945																																																				
2200A7	M830007	1.007	93	935																																																				
2200A8	M830008	1.009	92	930																																																				
2200A9	M830009	1.011	91	920																																																				
2200A10	M830010	1.012	90	910																																																				

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid**
 Contact with incompatible materials.
 Heat, flames and sparks. Extremes of temperature and direct sunlight.
- **10.5 Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **10.6 Hazardous decomposition products:**
 Carbon monoxide and carbon dioxide
 Phenol
 methyl methacrylate

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
 Harmful if inhaled.

 · **LD/LC50 values relevant for classification:**
100-66-3 Anisole

Oral	LD50	3700 mg/kg (Rat)
Dermal	LD50	>5000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
 Causes skin irritation.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2022

Version number 3

Revision: 01.02.2022

Trade name: 2200 PMMA Series Resists in Anisole

(Contd. of page 6)

- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

100-66-3 Anisole

EC50/24 h	40 mg/l (daphnia magna)
EC50/96 hr	162 mg/l (green algae)
LC50/48 hr	120 mg/L (Cyprinus carpio (common carp))

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1866

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 01.02.2022

Version number 3

Revision: 01.02.2022

Trade name: 2200 PMMA Series Resists in Anisole

(Contd. of page 7)

· 14.2 UN proper shipping name	1866 RESIN SOLUTION, mixture
· ADR	RESIN SOLUTION
· IMDG, IATA	
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E,S-D
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Transport category	3
· Tunnel restriction code	D/E
· UN "Model Regulation":	UN1866, RESIN SOLUTION, mixture, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
No further relevant information available.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.02.2022

Version number 3

Revision: 01.02.2022

Trade name: 2200 PMMA Series Resists in Anisole

(Contd. of page 8)

- **Department issuing SDS:** Product safety department
- **Contact:** Tom Cole, EHS Manager (tcole@kayakuAM.com)

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3