

Printing date 01.11.2024

Version number 6

Revision: 01.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: 495 PMMA Series Resists in Chlorobenzene

· Article number:

M140001, M140002, M140003, M140004, M140005, M140006, M140007, M140507, M140008, M140009, M140010, M140011, M140012

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- Product category PC30 Photo-chemicals
- Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818
- Further information obtainable from: Product Safety Email: productsafety@kayakuam.com

• 1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

GHS08 health hazard

H372 Causes damage to organs through prolonged or repeated exposure.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT RE 1

Acute Tox. 4H302 Harmful if swallowed.Acute Tox. 4H332 Harmful if inhaled.

(Contd. on page 2)



Printing date 01.11.2024

Version number 6

Revision: 01.11.2024

Skin Irrit. 2	(Contd. of pag H315 Causes skin irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.
· 2.2 Label ele	
	cording to Regulation (EC) No 1272/2008
-	is classified and labelled according to the GB CLP regulation.
• Hazard picto	ograms
<u> </u>	
	\vee \vee \vee
GHS02 C	GHS07 GHS08 GHS09
· Signal word	Danger
· Hazard-dete	rmining components of labelling:
Chlorobenze	ne
• Hazard state	ments
H226	Flammable liquid and vapour.
H302+H332	Harmful if swallowed or if inhaled.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
· Precautiona	ry statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses
	present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
<i>P337+P313</i>	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use alcohol resistant foam to extinguish.
P370+P378	In case of fire: Use fire-extinguishing powder to extinguish.
P370+P378	In case of fire: Use carbon dioxide to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internation regulations.
· 2.3 Other ha	
· Results of P	BT and vPvB assessment

(Contd. on page 3)



Printing date 01.11.2024

Safety data sheet according to UK REACH

Version number 6

Revision: 01.11.2024

Trade name: 495 PMMA Series Resists in Chlorobenzene

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	nts:	
	Chlorobenzene	85-100%
	 Flam. Liq. 3, H226; STOT RE 1, H372; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H336 	
· Additional Compone	nts:	
CAS: 9011-14-7	Poly(methyl methacrylate)	1-15%
EC number: 618-466-	-4	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. • After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eve contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Alcohol resistant foam Fire-extinguishing powder
- Carbon dioxide
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail. In case of fire, the following can be released:

Hydrogen chloride (HCl)

Phosgene gas

(Contd. on page 4)

GB



Printing date 01.11.2024

Version number 6

Revision: 01.11.2024

Trade name: 495 PMMA Series Resists in Chlorobenzene

(Contd. of page 3)

· 5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Keep away from ignition sources. Ensure adequate ventilation
 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow product to reach sewage system or any water course.
 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
 6.4 Reference to other sections See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- *Information about storage in one common storage facility:* Do not store together with oxidising and acidic materials.
- Do not store together with alkalis (caustic solutions).
- Further information about storage conditions:
 Store in cool, dry conditions in well sealed containers.
 Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
 Protect from heat and direct sunlight.
 Store receptacle in a well ventilated area.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 5)

GB -




Printing date 01.11.2024

Version number 6

Revision: 01.11.2024

Trade name: 495 PMMA Series Resists in Chlorobenzene



9.1 Information on basic physical and chemical properties General Information						
Appearance: Form:	Liquid					
Form: Colour:	Clear					
Odour:	Mild					
Odour threshold:	Not determined.					
pH-value:	Not determined.					
Change in condition						
Melting point/freezing point:	Undetermined.					



Revision: 01.11.2024

Printing date 01.11.2024

Version number 6

Trade name: 495 PMMA Series Resists in Chlorobenzene

Initial boiling point and boiling range	(Contd. of page : 132 °C		
Flash point:	28 °C (クローズドカップ)		
Flammability	Not applicable.		
Auto-ignition temperature:	590 °C		
Decomposition temperature:	Not determined.		
Ignition temperature:	Product is not selfigniting.		
Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.		
Explosion limits: Lower: Upper:	1.3 Vol % 11.0 Vol %		
Vapour pressure at 20 °C:	12 hPa		
Density: Relative density Vapour density Evaporation rate	Not determined See Table 1 Other Information Not determined. Not determined.		
Solubility in / Miscibility with water:	Not miscible or difficult to mix.		
Partition coefficient: n-octanol/water:	Not determined.		
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.		
9.2 Other information	NameNumberSp.Grav.VOC(%by wt.)VOC (g/L)495C1M1400011.105991095495C2M1400021.107981085495C3M1400031.109971075495C4M1400041.110961065495C5M1400051.110951055495C6M1400061.111941045495C7M1400071.113931035495C7.5M1400071.11392.51030495C8M1400081.114921025495C9M1400091.115911015495C10M1400101.116901005495C11M1400111.11789995495C12M1400121.11888985		

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

• 10.2 Chemical stability Stable

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 7)

⁻ GB



Printing date 01.11.2024

Safety data sheet according to UK REACH

Version number 6

Revision: 01.11.2024

Trade name: 495 PMMA Series Resists in Chlorobenzene

(Contd. of page 6)

• 10.4 Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.

• 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases

• 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide Hydrogen chloride (HCl) Possible traces of Phosgene

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity

Harmful if swallowed or if inhaled.

· LD/LC50 values relevant for classification:

108-90-7 Chlorobenzene

OralLD501110 mg/kg (Rat)DermalLD50>7940 mg/kg (rabbit)InhalativeLC5013.9 mg/L (Rat)

· Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· Additional toxicological information:

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure
- Causes damage to organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

• Aquatic toxicity:

108-90-7 Chlorobenzene

EC50/24 h 4.30-16.00 mg/l (daphnia magna)

EC50/96 hr 12.5 mg/l (algae)

LC100/48 h 0.03-28 mg/l (golden orfe)

LC50/76 h 4.5-7.4 mg/l (Lepomis macrochirus (Bluegill))

• 12.2 Persistence and degradability Expected to biodegrade

• 12.3 Bioaccumulative potential Not expected to bioaccumulate.

• 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

GB -



Printing date 01.11.2024

Version number 6

Revision: 01.11.2024

Trade name: 495 PMMA Series Resists in Chlorobenzene

(Contd. of page 7)

- Ecotoxical effects:
- Remark: Toxic for fish
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- *Recommendation:* Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name	
ADR, IATA	RESIN SOLUTION
IMDG	RESIN SOLUTION (CHLOROBENZENE), MARIN. POLLUTANT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
3	
Class	
	3 Flammable liquids.
Label	3 Flammable liquids. 3
Label 14.4 Packing group	3
Label 14.4 Packing group	-
Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards:	3 III
Label 14.4 Packing group ADR, IMDG, IATA	3 III Product contains environmentally hazardous substances
Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards:	3 III Product contains environmentally hazardous substances Chlorobenzene



Revision: 01.11.2024

Printing date 01.11.2024

Version number 6

Trade name: 495 PMMA Series Resists in Chlorobenzene

		(Contd. of page 8)
EMS Number:	F-E,S-D	
Segregation groups	Liquid halogenated hydrocarbons	
14.7 Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	5L	
Transport category	3	
Tunnel restriction code	D/E	
UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, III	

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture • Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

• Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 10)



Revision: 01.11.2024

Printing date 01.11.2024

Version number 6

Trade name: 495 PMMA Series Resists in Chlorobenzene

(Contd. of page 9) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 GB