ADVANCED MATERIALS


Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2022

Version number 7

Revision: 14.01.2022



• 1.1 Product identifier

• Trade name: 50 PMMA Series Resists in Chlorobenzene

- Article number:
- M540002, M540003, M540004, M540005, M540006, M540007, M540008, M540009, M540010, M540012
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818
- Further information obtainable from: Product Safety Email: productsafety@kayakuAM.com · 1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)
- Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

GHS02 flame

H226 Flammable liquid and vapour.

GHS08 health hazard

STOT RE 1

Flam. Liq. 3

H372 Causes damage to organs through prolonged or repeated exposure.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Acute Tox. 4	H302 Harmful if swallowed.
Acute Tox. 4	H332 Harmful if inhaled.
Skin Irrit. 2	H315 Causes skin irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.

(Contd. on page 2)



Revision: 14.01.2022

Printing date 14.01.2022

Version number 7

Trade name: 50 PMMA Series Resists in Chlorobenzene		
	(Contd. of page 1)	
· 2.2 Label e		
	according to Regulation (EC) No 1272/2008 t is classified and labelled according to the CLP regulation.	
· Hazard pic		
<u> (8</u>)		
	\vee \vee \vee	
GHS02	GHS07 GHS08 GHS09	
· Signal word	d Danger	
• Hazard-det	ermining components of labelling:	
Chlorobenz		
• Hazard stat	tements	
H226	Flammable liquid and vapour.	
H302+H33	2 Harmful if swallowed or if inhaled.	
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	
· Precaution	ary statements	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No	
	smoking.	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P273	Avoid release to the environment.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
P301+P310	<i>IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</i>	
P302+P352		
P304+P34	<i>I IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position</i>	
	comfortable for breathing.	
P305+P35	1+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if	
	present and easy to do. Continue rinsing.	
P333+P313		
P337+P313	<i>3 If eye irritation persists: Get medical advice/attention.</i>	
P370+P378	8 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.	
P403+P233		
P501	Dispose of contents/container in accordance with local/regional/national/international	
	regulations.	
· 2.3 Other h	-	
	PBT and vPvB assessment	
• PBT: Not a		
• vPvB: Not a	applicable.	

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

EU -



Printing date 14.01.2022

Version number 7

Revision: 14.01.2022

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 2)			
· Dangerous components:			
	Chlorobenzene	75-100%	
	Poly(methyl methacrylate-co-methacrylic acid) � Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-15%	
Additional information, For	the wording of the listed har and physics refer to section 16		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- Alcohol resistant foam
- Fire-extinguishing powder
- ABC powder
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

EU



Printing date 14.01.2022

Version number 7

Revision: 14.01.2022

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 3)

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Use explosion-proof apparatus / fittings and spark-proof tools.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and containers: No special requirements.

- Information about storage in one common storage facility: Do not store together with alkalis (caustic solutions). Do not store together with oxidising and acidic materials.
 Further information about storage conditions:
- Store in cool, dry conditions in well sealed containers. Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

108-90-7 Chlorobenzene

IOELV Short-term value: 70 mg/m³, 15 ppm

Long-term value: 23 mg/m³, 5 ppm

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from food and beverages.
- Wash hands before breaks and at the end of work.

• Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

^{· 8.1} Control parameters

EU



Printing date 14.01.2022

Version number 7

Revision: 14.01.2022

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 4)

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves Nitrile rubber, NBR
- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

SECTION 9: Physical and che	emical properties
9.1 Information on basic physical an	id chemical properties
General Information	
Appearance:	
Form:	Liquid
Colour:	Clear
Odour:	Mild
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling ra	nge: 132 °C
Flash point:	28 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	590 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits:	
Lower:	1.3 Vol %
Upper:	11.0 Vol %
Vapour pressure at 20 °C:	12 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.

— EU -



Printing date 14.01.2022

Version number 7

Revision: 14.01.2022

Trade name: 50 PMMA Series Resists in Chlorobenzene

		(Contd. of page
Evaporation rate	Not determined.	
Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
9.2 Other information	Name Number Sp. Grav. Vol.(%by wt.) VOC (g/L) 50C2 M540002 1.108 98 1085 50C3 M540003 1.109 97 1075 50C4 M540004 1.110 96 1065 50C5 M540005 1.111 95 1055 50C6 M540006 1.112 94 1045 50C7 M540007 1.113 93 1035 50C8 M540008 1.114 92 1025 50C9 M540009 1.115 91 1015 50C10 M540010 1.116 90 1005 50C12 M540012 1.117 88 985	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Stable under normal use conditions Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.
- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:
- Carbon monoxide and carbon dioxide
- Hydrogen chloride (HCl)
- Possible traces of Phosgene

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

Harmful if swallowed or if inhaled.

· LD/LC50 values relevant for classification:

108-90-7 Chlorobenzene

Oral LD50 2290 mg/kg (Rat)

(Contd. on page 7)

EU -

ADVANCED MATERIALS

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 14.01.2022

Printing date 14.01.2022

Version number 7

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 6)

- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure
- Causes damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

108-90-7 Chlorobenzene

EC50/24 h 4.30-16.00 mg/l (daphnia magna)

LC100/48 h 0.03-28 mg/l (golden orfe)

LC50/76 h 4.5-7.4 mg/l (Lepomis macrochirus (Bluegill))

EC50/96 hr 12.5 mg/l (algae)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.

• **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

(Contd. on page 8)



Printing date 14.01.2022

Version number 7

Revision: 14.01.2022

(Contd. of page 7)

Trade name: 50 PMMA Series Resists in Chlorobenzene

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name	
ADR, IMDG, IATA	RESIN SOLUTION
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
3	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDĞ, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	<i>30</i>
EMS Number:	F-E, <u>S-E</u>
Segregation groups	Liquid halogenated hydrocarbons
14.7 Transport in bulk according to Annex II o	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
· Limited quantities (LQ)	5L
· Transport category	3
Tunnel restriction code	D/E
· UN ''Model Regulation'':	UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

• Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

(Contd. on page 9)

EU

Safety data sheet

Revision: 14.01.2022

Trade name: 50 PMMA Series Resists in Chlorobenzene

- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

Abbreviations and acronvms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2


Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2





Printing date 14.01.2022

ADVANCED MATERIALS

(Contd. of page 8)