

Printing date 14.01.2022 Version number 7 Revision: 14.01.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 50 PMMA Series Resists in Chlorobenzene
- · Article number:

M540002, M540003, M540004, M540005, M540006, M540007, M540008, M540009, M540010, M540012

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Product category PC30 Photo-chemicals
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Telephone: (617) 965-5511

Fax: (617) 965-5818

#### Importer:

A-Gas Electronic Materials

Unit 3, IO Centre

Swift Valley

Rugby, Warwickshire

CV21 1TW, UK

Tel: +44-0-1788-537535 Fax: +44-0-1788-535835 Website: www.agasem.com

Email: customerservice.em@agas.com

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuAM.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency : 703-527-3887 (24 hr)

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

(Contd. on page 2)



Printing date 14.01.2022 Revision: 14.01.2022 Version number 7

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 1)



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

#### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02

GHS07

GHS08 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Chlorobenzene

#### · Hazard statements

H226 Flammable liquid and vapour. H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

*Toxic to aquatic life with long lasting effects.* H411

### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray. P261

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 *IF ON SKIN: Wash with plenty of soap and water.* 

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position P304+P341

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

*If eye irritation persists: Get medical advice/attention.* P337+P313

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

(Contd. on page 3)



Printing date 14.01.2022 Version number 7 Revision: 14.01.2022

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 2)

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB**: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions

70-100%
1-30%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

*Immediately remove any clothing soiled by the product.* 

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)



Printing date 14.01.2022 Version number 7 Revision: 14.01.2022

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 3)

- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

*Use explosion-proof apparatus / fittings and spark-proof tools.* 

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5)



Printing date 14.01.2022 Version number 7 Revision: 14.01.2022

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 4)

Ingredients with limit values that require monitoring at the workplace:

#### 108-90-7 Chlorobenzene

WEL Short-term value: 3 ppm Long-term value: 1 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Colour: Clear
Odour: Mild

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 132 °C

· Flash point: 28 °C

(Contd. on page 6)



Printing date 14.01.2022 Version number 7 Revision: 14.01.2022

Trade name: 50 PMMA Series Resists in Chlorobenzene

	(Contd. of page
Flammability (solid, gas):	Not applicable.
Ignition temperature:	590 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapoumixtures are possible.
Explosion limits: Lower: Upper:	1.3 Vol % 11.0 Vol %
Vapour pressure at 20 °C:	12 hPa
Density: Relative density Vapour density Evaporation rate	Not determined. Not determined. Not determined. Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
9.2 Other information	Name         Number         Sp. Grav. Vol.(%by wt.)         VOC (g/L)           50C2         M540002         1.108         98         1085           50C3         M540003         1.109         97         1075           50C4         M540004         1.110         96         1065           50C5         M540005         1.111         95         1055           50C6         M540006         1.112         94         1045           50C7         M540007         1.113         93         1035           50C8         M540008         1.114         92         1025           50C9         M540009         1.115         91         1015           50C10         M540010         1.116         90         1005

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable under normal use conditions
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

(Contd. on page 7)



Printing date 14.01.2022 Version number 7 Revision: 14.01.2022

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 6)

Hydrogen chloride (HCl) Possible traces of Phosgene

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if swallowed or if inhaled.

### · LD/LC50 values relevant for classification:

#### 108-90-7 Chlorobenzene

Oral LD50 2290 mg/kg (Rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure
- Causes damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

· 12.1 Toxicity

### · Aquatic toxicity:

#### 108-90-7 Chlorobenzene

EC50/24 h 4.30-16.00 mg/l (daphnia magna)

LC100/48 h | 0.03-28 mg/l (golden orfe)

LC50/76 h 4.5-7.4 mg/l (Lepomis macrochirus (Bluegill))

EC50/96 hr | 12.5 mg/l (algae)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

*Toxic for aquatic organisms* 

(Contd. on page 8)



Printing date 14.01.2022 Version number 7 Revision: 14.01.2022

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 7)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

# SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name	
ADR	1866 RESIN SOLUTION
IMDG, IATA	RESIN SOLUTION
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	<i>F-E,S-E</i>
Segregation groups	Liquid halogenated hydrocarbons
14.7 Transport in bulk according to Annex II o	of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E



Printing date 14.01.2022 Version number 7 Revision: 14.01.2022

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 8)

· UN ''Model Regulation'':

UN1866, RESIN SOLUTION, 3, III

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2