ADVANCED MATERIALS

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.11.2024

Version number 4 (replaces version 3)

Revision: 01.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

### · 1.1 Product identifier

· Trade name: 950 PMMA Series Resists in Chlorobenzene

· Article number:

950C1, 950C2, 950C3, 950C4, 950C4.5, 950C5, 950C6, 950C6.5, 950C7, 950C7.5, 950C8, 950C9, 950C10, 950C11, 950C12, 950C15

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- Product category PC30 Photo-chemicals
- Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818
- Further information obtainable from: Product Safety Email: productsafety@kayakuam.com

*Annu: productsdycry@nayannam.com* • 1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency : 703-527-3887 (24 hr)

# **SECTION 2: Hazards identification**

• 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

GHS08 health hazard

H372 Causes damage to organs through prolonged or repeated exposure.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT RE 1

Acute Tox. 4H302 Harmful if swallowed.Acute Tox. 4H332 Harmful if inhaled.

(Contd. on page 2)

IAL5 Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.11.2024

**Y**\KU°

ADVANCED MATERIALS

Version number 4 (replaces version 3)

Revision: 01.11.2024

Skin Irrit. 2	(Contd. of pag H315 Causes skin irritation.
SKIN IFFIL 2 STOT SE 3	
STOT SE 3	H336 May cause drowsiness or dizziness.
	ding to Regulation (EC) No 1272/2008 lassified and labelled according to the CLP regulation.
<u> {@</u> }{!	
GHS02 GHS	507 GHS08 GHS09
Signal word Da	nger
	ning components of labelling:
Chlorobenzene Hazard stateme	nte
	ns ammable liquid and vapour.
	immable liquid and vapour. Irmful if swallowed or if inhaled.
	uses skin irritation.
	uses skin irritation. Iy cause drowsiness or dizziness.
	uses damage to organs through prolonged or repeated exposure.
	xic to aquatic life with long lasting effects.
Precautionary s	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a posit
	comfortable for breathing.
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carl dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internation
2204 1	regulations.
2.3 Other hazar	
	and vPvB assessment
<b>PBT:</b> Not applie	
vPvB: Not appli	cubie.
	of endocrine-disrupting properties

(Contd. on page 3)

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.11.2024

Version number 4 (replaces version 3)

Revision: 01.11.2024

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 2)

#### **SECTION 3:** Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 108-90-7	Chlorobenzene	85-100%		
EINECS: 203-628-5	🚸 Flam. Liq. 3, H226; 🚸 STOT RE 1, H372; 🚯 Aquatic Chronic 2,			
Index number: 602-033-00-1	H411; ( Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315;			
	STOT SĚ 3, H336			
· Additional Components:				
CAS: 9011-14-7 Poly	(methyl methacrylate)	1-15%		
EC number: 618-466-4				
Additional information: For the wording of the listed hazard phrases refer to section 16.				

## **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. • After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eve contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

### **SECTION 5:** Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Alcohol resistant foam Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail. In case of fire, the following can be released:

Hydrogen chloride (HCl)

Phosgene gas

(Contd. on page 4)

EU -

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.11.2024

Version number 4 (replaces version 3)

Revision: 01.11.2024

Trade name: 950 PMMA Series Resists in Chlorobenzene

· 5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

### **SECTION 6:** Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Use explosion-proof apparatus / fittings and spark-proof tools. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

• Further information about storage conditions: Store in cool, dry conditions in well sealed containers. Protect from heat and direct sunlight. Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

· 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)

(Contd. of page 3)



ADVANCED MATERIALS according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.11.2024

*Version number 4 (replaces version 3)* 

Revision: 01.11.2024

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 4)

#### **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-90-7 Chlorobenzene

*IOELV* Short-term value: 70 mg/m<sup>3</sup>, 15 ppm

Long-term value: 23 mg/m<sup>3</sup>, 5 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures: Keep away from food and beverages.

Wash hands before breaks and at the end of work.

• Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. · Material of gloves Nitrile rubber, NBR

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Long-sleeved work clothes

#### **SECTION 9:** Physical and chemical properties • 9.1 Information on basic physical and chemical properties 11 C

· General Information	
· Physical state	Liquid
· Colour:	Clear to light yellow
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point	
and boiling range	132 °C
· Flammability	Not applicable.

(Contd. on page 6)

EU-



IAL5Safety data sheetaccording to Regulation (EC) No 1907/2006, Article 31 ADVANCED MATERIALS

Printing date 01.11.2024

ҜѦ҄҅ѴѦҜҴ҅

Version number 4 (replaces version 3)

Revision: 01.11.2024

Trade name: 950 PMMA Series Resists in Chlorobenzene

		(Contd. of pag
Lower and upper explosion limit		
Lower:	1.3 Vol %	
Upper:	11.0 Vol %	
Flash point:	28 °C	
Auto-ignition temperature:	590 °C	
Decomposition temperature:	Not determined.	
pH	Not determined.	
Viscosity:		
Kinematic viscosity	Not determined.	
Dynamic:	Not determined.	
Solubility		
water:	Not miscible or difficult to mix.	
Partition coefficient n-octanol/water		
(log value)	Not determined.	
Vapour pressure at 20 °C:	12 hPa	
Density and/or relative density		
Density:	Not determined	
Relative density	See Table 1 Other Information	
Vapour density	Not determined.	
9.2 Other information	Name Number Sp.Grav. VOC(%by	$v(t) VOC(\alpha/L)$
9.2 Other information	950C1 M240001 1.106 99	1095
	950C1 M240001 1.100 99 950C2 M240002 1.107 98	1095
	950C2 M240002 1.107 98 950C3 M240003 1.108 97	1085
	950C4 M240004 1.109 96	1065
	950C4.5 M240504 1.109 95.5	1060
	950C5 M240005 1.110 95	1055
	950C6 M240006 1.111 94	1045
	950C6.5 M240506 1.112 93.5 950C7 M240007 1.113 93	1040
		1035
	950C7.5 M240507 1.113 92.5	1030
	950C8 M240008 1.114 92	1025
	950C9 M240009 1.115 91	1015
	950C10 M240010 1.115 90	1005
	950C11 M240011 1.116 89	<i>995</i>
	950C12 M240012 1.117 88	985 050
	950C15 M240015 1.120 85	950
Appearance:	Eluid	
Form:	Fluid	
Important information on protection of health and environment, and on safety		
Ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, j mixtures are possible.	formation of explosive air/vapo
Solvent content:		
Organic solvents:	0.0 %	
Solids content:	6.0 %	
Change in condition	-	
Evaporation rate	Not determined.	

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.11.2024

*Version number 4 (replaces version 3)* 

Revision: 01.11.2024

Trade name: 950 PMMA Series Resists in Chlorobenzene

		(Contd. of page 6)
Information with regard to physical		
hazard classes		
Explosives	Not applicable.	
Flammable gases	Not applicable.	
Aerosols	Not applicable.	
Oxidising gases	Not applicable.	
Gases under pressure	Not applicable.	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Not applicable.	
Self-reactive substances and mixtures	Not applicable.	
Pyrophoric liquids	Not applicable.	
Pyrophoric solids	Not applicable.	
Self-heating substances and mixtures	Not applicable.	
Substances and mixtures, which emit		
flammable gases in contact with water	Not applicable.	
Oxidising liquids	Not applicable.	
Oxidising solids	Not applicable.	
Organic peroxides	Not applicable.	
Corrosive to metals	Not applicable.	
Desensitised explosives	Not applicable.	

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid
- Heat, flames and sparks. Extremes of temperature and direct sunlight.
- Contact with incompatible materials.
- 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- 10.6 Hazardous decomposition products:
- Carbon monoxide and carbon dioxide
- Hydrogen chloride (HCl)
- Possible traces of Phosgene

# SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity
- Harmful if swallowed or if inhaled.

•	LD/LC50	values r	elevant f	for cla	assificatio	n:

108-90-7 Chlorobenzene		
		1110 mg/kg (Rat)
Dermal	LD50	>7940 mg/kg (rabbit)
Inhalative	LC50	13.9 mg/L (Rat)

(Contd. on page 8)



EU

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.11.2024

ADVANCED MATERIALS

Version number 4 (replaces version 3)

Revision: 01.11.2024

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 7) • Primary irritant effect: · Skin corrosion/irritation May cause skin irritation • Serious eye damage/irritation Based on available data, the classification criteria are not met. • **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met. · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. • *Reproductive toxicity* Based on available data, the classification criteria are not met. · STOT-single exposure May cause drowsiness or dizziness. · STOT-repeated exposure Causes damage to organs through prolonged or repeated exposure. · Aspiration hazard Based on available data, the classification criteria are not met. • *Experience with humans:* No further relevant information available. · 11.2 Information on other hazards · Endocrine disrupting properties 108-90-7 Chlorobenzene List II

# SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:				
108-90-7 Chlorobenzene				
EC50/24 h 4.30-16.00 mg/l (daphnia magna)				
EC50/96 hr 12.5 mg/l (algae)				
LC100/48 h 0.03-28 mg/l (golden orfe)				
LC50/76 h 4.5-7.4 mg/l (Lepomis macrochirus (Bluegill))				
12.2 Persistence and degradability Expected to biodegrade				
· 12.3 Bioaccumulative potential Not expected to bioaccumulate.				
· 12.4 Mobility in soil No further relevant information available.				
· 12.5 Results of PBT and vPvB assessment				
· <b>PBT:</b> Not applicable.				
· <b>vPvB:</b> Not applicable.				
• 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.				
· 12.7 Other adverse effects				
· Remark: Toxic for fish				
· Additional ecological information:				
General notes:				
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water				
Do not allow product to reach ground water, water course or sewage system.				
Danger to drinking water if even small quantities leak into the ground.				
Also poisonous for fish and plankton in water bodies.				
Toxic for aquatic organisms				

### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.11.2024

ΚΫΛΫΚΙ

ADVANCED MATERIALS

Version number 4 (replaces version 3)

Revision: 01.11.2024

(Contd. of page 8)

Trade name: 950 PMMA Series Resists in Chlorobenzene

Disposal must be made in accordance with International, National, and regional regulations.

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.* 

14.1 UN number or ID number ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name ADR, IATA IMDG	RESIN SOLUTION RESIN SOLUTION (CHLOROBENZENE), MARIN POLLUTANT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substance. Chlorobenzene
Marine pollutant:	Yes
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Segregation groups	Warning: Flammable liquids. 30 F-E,S-D Liquid halogenated hydrocarbons
14.7 Maritime transport in bulk according to IM instruments	<i>Not applicable.</i>
Transport/Additional information:	
ADR Limited quantities (LQ) Transport category Tunnel restriction code	5L 3 D/E
UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, III

# **SECTION 15: Regulatory information**

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 10)

<sup>–</sup> EU –

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.11.2024

Version number 4 (replaces version 3)

Revision: 01.11.2024

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 9)

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

• Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

• Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

*H411 Toxic to aquatic life with long lasting effects.* 

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

- · Version number of previous version: 3
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

- EINECS: European Inventory of Existing Commercial Chemica ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent

(Contd. on page 11)

<sup>—</sup> EI

according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.11.2024

Version number 4 (replaces version 3)

Revision: 01.11.2024

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 10)

FL

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

