

Printing date 01.02.2022 Version number 4 Revision: 01.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 950 PMMA Series Resists in Chlorobenzene
- · Article number:

950C1, 950C2, 950C3, 950C4, 950C4.5, 950C5, 950C6, 950C6.5, 950C7, 950C7.5, 950C8, 950C9, 950C10, 950C11, 950C12, 950C15

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · **Product category** PC30 Photo-chemicals
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581 Telephone: (617) 965-5511

Fax: (617) 965-5818

Importer:

A-Gas Electronic Materials

Unit 3, IO Centre

Swift Valley

Rugby, Warwickshire

CV21 1TW, UK

Tel: +44-0-1788-537535 Fax: +44-0-1788-535835 Website: www.agasem.com

Email: customerservice.em@agas.com

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuAM.com · 1.4 Emergency telephone number:

Kayaku Advanced Materials: 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

(Contd. on page 2)



Printing date 01.02.2022 Version number 4 Revision: 01.02.2022

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 1)



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02

GHS07

GHS08 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Chlorobenzene

· Hazard statements

H226 Flammable liquid and vapour. H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

(Contd. on page 3)



Printing date 01.02.2022 Version number 4 Revision: 01.02.2022

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 2)

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	Chlorobenzene	85-100%
	Flam. Liq. 3, H226; 🗞 STOT RE 1, H372; 🥎 Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H336	
· Additional Componen	ts:	
CAS: 9011-14-7	Poly(methyl methacrylate)	1-15%
EC number: 618-466-		

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

(Contd. on page 4)



Printing date 01.02.2022 Version number 4 Revision: 01.02.2022

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 3)

· For safety reasons unsuitable extinguishing agents: Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

In case of fire, the following can be released:

Hydrogen chloride (HCl)

Phosgene gas

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Use explosion-proof apparatus / fittings and spark-proof tools.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

(Contd. on page 5)



Printing date 01.02.2022 Version number 4 Revision: 01.02.2022

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 4)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

108-90-7 Chlorobenzene

WEL Short-term value: 3 ppm Long-term value: 1 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Wash hands before breaks and at the end of work.

Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: Clear to light yellow
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 6)



Printing date 01.02.2022 Version number 4 Revision: 01.02.2022

Trade name: 950 PMMA Series Resists in Chlorobenzene

	(Contd. of page
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : 132°C
Flash point:	28 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	590 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.3 Vol %
Upper:	11.0 Vol %
Vapour pressure at 20 °C:	12 hPa
Density:	Not determined
Relative density	See Table 1 Other Information
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	0.0 %
Solids content:	6.0 %



Printing date 01.02.2022 Version number 4 Revision: 01.02.2022

Trade name: 950 PMMA Series Resists in Chlorobenzene

				(Contd. of page 6
9.2 Other information	Name Number Sp.Grav.	Vol.(%by wt	.) VOC (g/L)	
•	950C1 M240001 1.106	99	1095	
	950C2 M240002 1.107	98	1085	
	950C3 M240003 1.108	97	1075	
	950C4 M240004 1.109	96	1065	
	950C4.5 M240504 1.109	95.5	1060	
	950C5 M240005 1.110	95	1055	
	950C6 M240006 1.111	94	1045	
	950C6.5 M240506 1.112	93.5	1040	
	950C7 M240007 1.113	93	1035	
	950C7.5 M240507 1.113	92.5	1030	
	950C8 M240008 1.114	92	1025	
	950C9 M240009 1.115	91	1015	
	950C10 M240010 1.115	90	1005	
	950C11 M240011 1.116	89	995	
	950C12 M240012 1.117	88	985	
	950C15 M240015 1.120	85	950	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Hydrogen chloride (HCl)

Possible traces of Phosgene

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if swallowed or if inhaled.

	· LD/LC50 1	· LD/LC50 values relevant for classification:	
	108-90-7 C	108-90-7 Chlorobenzene	
ſ			1110 mg/kg (Rat)
1	Dermal	LD50	>7940 mg/kg (rabbit)
	Inhalative	LC50	13.9 mg/L (Rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 01.02.2022 Version number 4 Revision: 01.02.2022

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 7)

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Experience with humans: No further relevant information available.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

_	-		
	· Aquatic toxicity:		
	108-90-7 Chlorobenzene		
	EC50/24 h	4.30-16.00 mg/l (daphnia magna)	
	EC50/96 hr	12.5 mg/l (algae)	
	LC100/48 h	0.03-28 mg/l (golden orfe)	
	LC50/76 h	4.5-7.4 mg/l (Lepomis macrochirus (Bluegill))	
	EC50/96 hr LC100/48 h	12.5 mg/l (algae) 0.03-28 mg/l (golden orfe)	

- · 12.2 Persistence and degradability Expected to biodegrade
- · 12.3 Bioaccumulative potential Not expected to bioaccumulate.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)



Printing date 01.02.2022 Version number 4 Revision: 01.02.2022

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 8)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name ADR, IATA IMDG	RESIN SOLUTION RESIN SOLUTION (CHLOROBENZENE), MARIA POLLUTANT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substance Chlorobenzene
Marine pollutant:	Yes
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Segregation groups	Warning: Flammable liquids. 30 F-E,S-D Liquid halogenated hydrocarbons
14.7 Transport in bulk according to Annex II o	of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 10)



Printing date 01.02.2022 Version number 4 Revision: 01.02.2022

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 9)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

GB ·