

Printing date 09/29/2021

1 Identification

· Product identifier

• Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

- · Product number: G040100
- · Application of the substance / the mixture Solvents
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Kayaku Advanced Materials, Inc.
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818
- Information department: Product Safety Email: productsafety@kayakuAM.com • Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 Chemtrec International Emergency : 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapor.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger · Hazard statements H225 Highly flammable liquid and vapor. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P210 P261 Avoid breathing dust/fume/gas/mist/vapors/spray P280 Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 If swallowed: Immediately call a poison center/doctor. P302+P352 If on skin: Wash with plenty of soap and water. P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eves: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Reviewed on 09/29/2021

(Contd. on page 2)

US



Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

P337+P313	<i>(Contd. of page 1) If eye irritation persists: Get medical advice/attention.</i>
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon
1 570 1 570	dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international
1001	regulations.
· Classification s	0
· NFPA ratings (
	lealth = 0
	Tire = 3
	Peactivity = 0
· HMIS-ratings ((scale 0 - 4)
HEALTH 1	Health = 1
FIRE 3	Fire = 3
REACTIVITY 0	Reactivity = 0
• Other hazards	
•	and vPvB assessment
• PBT: Not appli	
• vPvB: Not appl	
3 Composition	/information on ingredients
· Chomical char	acterization: Mixtures
• Description: So	-
-	
• Dangerous con	iponenis:

107-98-2 1-methoxy-2-propanol 🐼 Flam. Liq. 3, H226; 🗘 STOT SE 3, H336 0.5-2%	646-06-0 1,3-dioxolane	🚸 Flam. Liq. 2, H225	98-99.5%
	107-98-2 1-methoxy-2-propanol	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	0.5-2%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- \cdot After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

• Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- Extinguishing media
- \cdot Suitable extinguishing agents:
- Alcohol resistant foam
- *Fire-extinguishing powder*
- Carbon dioxide
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- *In case of fire, the following can be released:*
- Formaldehyde
- Advice for firefighters
- **Protective equipment:** Wear SCBA.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Ensure adequate ventilation
 Keep away from ignition sources
 Use respiratory protective device against the effects of fumes/dust/aerosol.
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up:
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust) Ensure adequate ventilation.
- Dispose contaminated material as waste according to Section 13.
- **Reference to other sections** See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Keep away from heat and direct sunlight. Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges.
- Conditions for safe storage, including any incompatibilities • Storage:
- Requirements to be met by storerooms and containers:

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products. Store in a cool location.

(Contd. on page 4)

US •



Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

(Contd. of page 3)

- Information about storage in one common storage facility:
- Do not store together with oxidizing and acidic materials. Do not store together with alkalis (caustic solutions).
- Further information about storage conditions: Keep container well-sealed in cool, dry location. Protect from heat and direct sunlight.
- Store receptacle in a well ventilated area.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

646-06-0 1,3-dioxolane

TLV 61 mg/m³, 20 ppm

107-98-2 1-methoxy-2-propanol

REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm

TLV Short-term value: (553) NIC-369 mg/m³, (150) NIC-100 ppm Long-term value: (369) NIC-184 mg/m³, (100) NIC-50 ppm NIC-A4

· Additional information: The lists that were valid during the creation were used as basis.

• Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from food and beverages.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.
- · Respiratory equipment:
- In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. **Protection of hands:**
- Selection of glove material on consideration of the penetration times, rates of diffusion and degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- Material of gloves
- Butyl rubber, BR
- Nitrile rubber, NBR
- Penetration time of glove material Contact glove manufacture for break-through time.

(Contd. on page 5)

US



Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

(Contd. of page 4)

• Eye protection: Tightly sealed goggles

Information on basic physical and c	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear to light yellow
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-26.4 °C (-15.5 °F)
Boiling point/Boiling range:	75 °C (167 °F)
Flash point:	-6 °C (21.2 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	274 °C (525.2 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo
	mixtures are possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	133 hPa (99.8 mm Hg)
Density at 20 °C (68 °F):	1.0355 g/cm ³ (8.64125 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. of page 5)



Safety Data Sheet acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

• Other information

No further relevant information available.

10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Polymerization.
- Possible formation of peroxide.
- · Conditions to avoid
- Contact with incompatible materials.
- Heat, flames and sparks. Extremes of temperature and direct sunlight.
- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- Hazardous decomposition products:

Formaldehyde

Carbon monoxide and carbon dioxide

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

646-06-0 1,3-dioxolane

	/	
Oral	LD50	3000 mg/kg (Rat)
	LD50	8480 mg/kg (rabbit)
Inhalative	LC50	68.4 mg/L (Rat)

107-98-2 1-methoxy-2-propanol

	-	
Oral	LD50	5660 mg/kg (Rat)
Dermal	LD50	13000 mg/kg (rabbit)
Inhalative	LC50/4 h	54.6 mg/l (Rat)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Strong irritant with the danger of severe eye injury.

· Sensitization: No sensitizing effects known.

• *Experience with humans:* No further relevant information available.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program)

None of the ingredients are listed.

(Contd. on page 7)

– US

(Contd. of page 6)



Safety Data Sheet acc. to OSHA HCS

Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

• Aquatic toxicity:

	Aquan ioxicay.		
	646-06-0 1,3-dioxolane		
	14 day NOEC	>1000 mg/l (algae)	
	LC50/48 hr	12000 mg/L (Sheepshead minnow)	
	107-98-2 1-methoxy-2-propanol		
	EC50/96 hr	23300 mg/l (daphnia magna)	
		>1000 mg/l (green algae)	
	LC50/96 h	20800 mg/l (Pimephales promelas)	
Persistence and degradability The single components are biodegradable			
Behavior in environmental systems:			
· Bioaccumulative potential			
Due to the distribution coefficient n-octanol/water a worth-mentioning accumulation in organisms is not expected.			
· Mobility in soil			
	Components Promilence check menow other strict discipation in soil expected. Keeperly hot ways 1 and 50		

Component: Propylene glycol monomethyl ether, rapid dissipation in soil expected. Koc value between 1 and 50 indicating very high soil mobility.

• Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Disposal must be made in accordance with Federal, State, and Local regulations.

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

· Recommended cleansing agent: Water, if necessary with cleansing agents.

(Contd. on page 8)



Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

(Contd. of page 7)

Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN1166
· UN proper shipping name · DOT, ADR · IMDG, IATA	Dioxolane DIOXOLANE
· Transport hazard class(es)	
·DOT	
· Class · Label	3 Flammable liquids 3
· ADR, IMDG, IATA	
· Class	3 Flammable liquids
·Label	3
· Packing group · DOT, ADR, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Hazard identification number (Kemler code) · EMS Number:	Warning: Flammable liquids): 33 F-E,S-D
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN ''Model Regulation'':	UNI 166, Dioxolane, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

• Section 355 (extremely hazardous substances):

None of the ingredients are listed.

• Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.

(Contd. on page 9)

⁷⁾ ∙US —



Printing date 09/29/2021

· Proposition 65

Reviewed on 09/29/2021

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

(Contd. of page 8)

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value)

None of the ingredients are listed.

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

107-98-2 1-methoxy-2-propanol

· New Jersey State Right To Know List

646-06-0 1,3-dioxolane

107-98-2 1-methoxy-2-propanol

· Pennsylvania Hazardous Substances List

646-06-0 1,3-dioxolane

107-98-2 1-methoxy-2-propanol

· California SCAQMD Rule 443.1 VOC's: No information available.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Da	nger
• Hazard stateme	nts
H225 Highly fla	mmable liquid and vapor.
· Precautionary s	tatements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for
	breathing.
	(Contd on page 10)

(Contd. on page 10)

[—]us



Printing date 09/29/2021

Reviewed on 09/29/2021

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

	(Contd. of page 9)
P305+P351+P3	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Charmin al a afata	and enter A Chamical Safety Agagement has not been agained out

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Date of preparation / last revision 09/29/2021 / 4

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

- HMIS: Hazardous Materials Identification System (USA)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

US -