

Printing date 28.01.2025 Version number 11 Revision: 28.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: EBR PG

· Article number: G042075

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · **Product category** PC21 Laboratory chemicals
- · Application of the substance / the mixture Solvents
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials, Inc.

200 Flanders Road

Westborough, MA 01581

Tel: (617) 965-5511 Fax: (617) 965-5818

The appointed Only Representative* for the United Kingdom (UK):

H2 COMPLIANCE UK Ltd,

Mazars Tower Bridge House,

St Katharine's Way.

St Katharine's & Wapping,

London,

United Kingdom

E1W 1DD

Tel: +353-21-4868120

Email: info@h2compliance.com

*Only Representative for 1,3-dioxolane (EINICS 211-463-5, CAS 646-06-0) only. Other substances are being supported under UK- REACH by Only Representatives of Non-UK suppliers and others may be exempt from registration.

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuam.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Dam. 1 H318 Causes serious eye damage.



Revision: 28.01.2025 Version number 11 *Printing date 28.01.2025*

Trade name: EBR PG

(Contd. of page 1)



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

GHS05

- · Signal word Danger
- · Hazard-determining components of labelling:

1.3-dioxolane

1-methoxy-2-propanol

· Hazard statements

H225 Highly flammable liquid and vapour.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position P304+P341

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 *If skin irritation or rash occurs: Get medical advice/attention.*

If eye irritation persists: Get medical advice/attention. P337+P313

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

None of the ingredients are included in the list established in accordance with Article 59(1) for having endocrine disrupting properties.

None of the ingredients are substances identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (or Commission Regulation (EU) 2018/605.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)



Printing date 28.01.2025 Version number 11 Revision: 28.01.2025

Trade name: EBR PG

(Contd. of page 2)

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Solvent mixture

· Dangerous components:				
CAS: 646-06-0 EINECS: 211-463-5	1,3-dioxolane	♠ Flam. Liq. 2, H225; ♦ Eye Dam. 1, H318	50-80%	
CAS: 107-98-2 EINECS: 203-539-1		♠ Flam. Liq. 3, H226; ♠ STOT SE 3, H336	5-30%	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Formaldehyde

Can form explosive gas-air mixtures.

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

(Contd. on page 4)



Printing date 28.01.2025 Version number 11 Revision: 28.01.2025

Trade name: EBR PG

(Contd. of page 3)

· 5.3 Advice for firefighters

· **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect from heat.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and containers:

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products. Store in a cool location.

· Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

· Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) Positive radiation resist edge bead remover

CD.



Printing date 28.01.2025 Version number 11 Revision: 28.01.2025

Trade name: EBR PG

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin. Do not inhale gases / fumes / aerosols.

- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Colour: Clear to light yellow
Odour: Characteristic
Odour threshold: Not determined.

(Contd. on page 6)



Printing date 28.01.2025 Version number 11 Revision: 28.01.2025

Trade name: EBR PG

	(Contd. of page
pH-value:	Not determined.
Change in condition Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	2: 75 °C
Flash point:	<7.5 °C
Flammability	Not applicable.
Auto-ignition temperature:	270 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapor
	mixtures are possible.
Explosion limits:	
Lower:	2.1 Vol %
Upper:	20.5 Vol %
	Not determined.
Vapour pressure at 20 °C:	133 hPa
Density at 20 °C:	1.0355 g/cm^3
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Polymerisation.

Possible formation of peroxide.

· 10.4 Conditions to avoid

Contact with incompatible materials.

Heat, flames and sparks. Extremes of temperature and direct sunlight.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Formaldehyde

(Contd. on page 7)



Printing date 28.01.2025 Version number 11 Revision: 28.01.2025

Trade name: EBR PG

Carbon monoxide and carbon dioxide

(Contd. of page 6)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:			
646-06-0 1	646-06-0 1,3-dioxolane			
Oral	LD50	3000 mg/kg (Rat)		
Dermal	LD50	8480 mg/kg (rabbit)		
Inhalative	LC50	68.4 mg/L (Rat)		
107-98-2 1	107-98-2 1-methoxy-2-propanol			
Oral	LD50	5660 mg/kg (Rat)		
Dermal	LD50	13000 mg/kg (rabbit)		
Inhalative	LC50/4 h	54.6 mg/l (Rat)		

- · Primary irritant effect:
- · Skin corrosion/irritation Not a known skin irritant
- · Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation No information
- · Experience with humans: No further relevant information available.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity No information
- · Carcinogenicity No information
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure No information
- · Aspiration hazard No information

SECTION 12: Ecological information

· 12.1 Toxicity

· Aqua	· Aquatic toxicity:		
	06-0 1,3-dioxolo		
Oral	14 day NOEC	>1000 mg/l (algae)	
	EC50	7650 mg/kg (daphnia magna)	
	LC50 48 hr	12000 mg/L (Sheepshead minnow)	
107-9	107-98-2 1-methoxy-2-propanol		
	EC50 96 hr	23300 (daphnia magna)	
		>1000 (green algae)	
	LC50/96 h	20800 mg/l (Pimephales promelas)	

· 12.2 Persistence and degradability The single components are biodegradable

(Contd. on page 8)



Printing date 28.01.2025 Version number 11 Revision: 28.01.2025

Trade name: EBR PG

(Contd. of page 7)

· 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water a worth-mentioning accumulation in organisms is not expected.

· 12.4 Mobility in soil

Component: Propylene glycol monomethyl ether, rapid dissipation in soil expected. Koc value between 1 and 50 indicating very high soil mobility.

- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport inju	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1166
· 14.2 UN proper shipping name	
$\cdot ADR$	1166 DIOXOLANE
· IMDG, IATA	DIOXOLANE
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	

3/	

· Class

· Label	3	•
· 14.4 Packing group · ADR, IMDG, IATA	II	
· 14.5 Environmental hazards:		

3 Flammable liquids.

· 14.	5 Env	ironmenta	ul	hazards:
-------	-------	-----------	----	----------

· Marine pollutant: No

· 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code):

(Contd. on page 9)



Printing date 28.01.2025 Version number 11 Revision: 28.01.2025

Trade name: EBR PG

		(Contd. of page 8
· EMS Number:	F-E,S-D	
· 14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.	
Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	IL	
· Transport category	2	
· Tunnel restriction code	D/E	
· UN "Model Regulation":	UN1166, DIOXOLANE, 3, II	

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3