

Printing date 16.10.2024

Version number 6

Revision: 16.10.2024

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### · 1.1 Product identifier

• Trade name: LOR B Series Resists

• Article number:

*G316702, G316703, G316704, G316707, G316708, G316709, G316710, G316711, G316712, G316715, G316716, G316719* 

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- Product category PC30 Photo-chemicals
- Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Manufacturer: Kayaku Advanced Materials 200 Flanders Road Westborough, MA 01581 Telephone: (617) 965-5511 Fax: (617) 965-5818

Importer: A-Gas Electronic Materials Unit 3, IO Centre Swift Valley Rugby, Warwickshire CV21 1TW, UK Tel: +44-0-1788-537535 Fax: +44-0-1788-535835 Website: www.agasem.com Email: customerservice.em@agas.com

Further information obtainable from: Product Safety
Email: productsafety@kayakuam.com
1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

(Contd. on page 2)

GB •



Revision: 16.10.2024

Printing date 16.10.2024

Version number 6

Trade name: LOR B Series Resists

Eve Irrit 2 H <sup>2</sup>	(Contd. of pag B19 Causes serious eye irritation.
2.2 Label eleme	
	nis ding to Regulation (EC) No 1272/2008
	lassified and labelled according to the GB CLP regulation.
Hazard pictogra	
	ints
<i>&lt; *% &gt;&lt;</i> 1	
GHS02 GHS	07
011502 0116	
Signal word Wa	
Hazard stateme	
	le liquid and vapour.
H315 Causes sk	
	rious eye irritation.
Precautionary s	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a posi comfortable for breathing.
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lense.
	present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	<i>If eye irritation persists: Get medical advice/attention.</i>
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Car
	dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internation
	regulations.
2.3 Other hazar	ds
None of the ingr disrupting prope	redients are included in the list established in accordance with Article 59(1) for having endoc erties.
	redients are substances identified as having endocrine disrupting properties in accordance v
	out in Commission Delegated Regulation (EU) 2017/2100 (or Commission Regulation (I
2018/605.	our in commission Delegated Regulation (DO) 2017/2100 (or commission Regulation (
	and vPvB assessment
<b>PBT:</b> Not applie	
· · · · · · · · · · · · · · · · ·	cable.

### SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

<sup>-</sup> GB -



Revision: 16.10.2024

Printing date 16.10.2024

Version number 6

Trade name: LOR B Series Resists

		(Contd. of page 2)
· Dangerous compone	ents:	
CAS: 120-92-3	Cyclopentanone	65-85%
EINECS: 204-435-9	🚸 Flam. Liq. 3, H226; 🚸 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 102322-80-5	Polyaliphatic imide copolymer	1-20%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 107-98-2	1-methoxy-2-propanol	10-15%
EINECS: 203-539-1	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
	Proprietary Dye B	0.25-2%
	𝚯 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
· Additional informati	ion: For the wording of the listed hazard phrases refer to section 16.	

### **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

### **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

- *Suitable extinguishing agents: Alcohol resistant foam*
- *Fire-extinguishing powder*

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.

### **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation
- Keep away from ignition sources.

• 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

GB –



Printing date 16.10.2024

Version number 6

Revision: 16.10.2024

Trade name: LOR B Series Resists

(Contd. of page 3)

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols. Keep away from heat and direct sunlight. Use only under yellow light

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and containers: Store in a cool location.

Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.

- Information about storage in one common storage facility: Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions).
- Further information about storage conditions: Store in cool, dry conditions in well sealed containers. Store receptacle in a well ventilated area. Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm Long-term value: 375 mg/m<sup>3</sup>, 100 ppm Sk

• *Additional information:* The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from food and beverages.

(Contd. on page 5)

GB -



Printing date 16.10.2024

Version number 6

Revision: 16.10.2024

(Contd. of page 4)

Trade name: LOR B Series Resists

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

In case of low exposure use cartridge r respiratory protective device. <b>Protection of hands:</b>	respirator. In case of intensive or longer exposure use self-containe
Protective gloves	
Material of gloves Nitrile rubber, NBR Penetration time of glove material	e and resistant to the product/ the substance/ the preparation. found out by the manufacturer of the protective gloves and has to b
Tightly sealed goggles	
9.1 Information on basic physical and ch	iemiem propernies
General Information Appearance: Form: Colour: Odour: Odour threshold:	Liquid Yellow-brown Sweetish Not determined.
Appearance: Form: Colour: Odour:	Yellow-brown Sweetish
Appearance: Form: Colour: Odour: Odour threshold:	Yellow-brown Sweetish Not determined. Not determined. Undetermined.
Appearance: Form: Colour: Odour: Odour threshold: pH-value: Change in condition Melting point/freezing point:	Yellow-brown Sweetish Not determined. Not determined. Undetermined.
Appearance: Form: Colour: Odour: Odour threshold: pH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Yellow-brown Sweetish Not determined. Not determined. Undetermined. 120 °C
Appearance: Form: Colour: Odour: Odour threshold: pH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range: Flash point:	Yellow-brown Sweetish Not determined. Not determined. Undetermined. 120 °C 30 °C
Appearance: Form: Colour: Odour: Odour threshold: pH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range: Flash point: Flammability	Yellow-brown Sweetish Not determined. Not determined. 120 °C 30 °C Not applicable.
Appearance: Form: Colour: Odour: Odour threshold: pH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range: Flash point: Flammability Auto-ignition temperature:	Yellow-brown Sweetish Not determined. Not determined. 120 °C 30 °C Not applicable. 270 °C
Appearance: Form: Colour: Odour: Odour threshold: pH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range: Flash point: Flammability Auto-ignition temperature: Decomposition temperature:	Yellow-brown Sweetish Not determined. Not determined. 120 °C 30 °C Not applicable. 270 °C Not determined.
Appearance: Form: Colour: Odour: Odour threshold: pH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range: Flash point: Flammability Auto-ignition temperature: Decomposition temperature: Ignition temperature:	Yellow-brown Sweetish Not determined. Not determined. 120 °C 30 °C Not applicable. 270 °C Not determined. Product is not selfigniting. Product is not selfigniting.



Printing date 16.10.2024

Version number 6

Revision: 16.10.2024

Trade name: LOR B Series Resists

					(Contd. of page
Upper:	Not detern	ined.			
Vapour pressure at 20 °C:	12 hPa				
Density:	See Other	information	1		
· Vapour density	Not detern	ined.			
Evaporation rate	Not detern	ined.			
Solubility in / Miscibility with					
water:	Not miscib	Not miscible or difficult to mix.			
Partition coefficient: n-octanol/water:	Not determined.				
Viscosity:					
Dynamic:	Not detern	ined.			
Kinematic:	Not determined.				
9.2 Other information	Name	Number	Sp. Grav.	VOC(%by wt.)	VOC(g/L)
	LOR 0.7B	G316702	0.947	98	925
	LOR 1B	G316703	0.952	96	915
	LOR 2B	G316704	0.955	95	910
	LOR 3B	G316707	0.961	<i>93</i>	900
	LOR 5B	G316708	0.966	92	890
	LOR 6B	G316709	0.967	91	885
	LOR 7B	G316710	0.969	91	880
	LOR 10B	G316711	0.974	89	870
	LOR 15B	G316712	0.978	88	860
	LOR 20B	G316715	0.985	86	850
	LOR 30B	G316716	0.987	85	840
	LOR 50B	G316719	0.998	82	815

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid
- Heat, flames and sparks. Extremes of temperature and direct sunlight.
- Contact with incompatible materials.
- 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- 10.6 Hazardous decomposition products:
- Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB —



Printing date 16.10.2024

Version number 6

Revision: 16.10.2024

Trade name: LOR B Series Resists

			(Contd. of page 6)
$\cdot$ LD/LC50 $\cdot$	values rele	want for classification:	
120-92-3 (	Syclopenta	none	
Oral	LD50	1180 mg/kg (Rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>19.5 mg/l (Rat)	
107-98-21	-methoxy-	2-propanol	
Oral	LD50	5660 mg/kg (Rat)	
Dermal	LD50	13000 mg/kg (rabbit)	
Inhalative	LC50/4 h	54.6 mg/l (Rat)	
102322-80	-5 Polyali <sub>I</sub>	phatic imide copolymer	
Oral	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)	
Dermal	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)	
· Respirator	osion/irritat in irritation ie damage/i rious eye irr y or skin so	tion 1. irritation	

· Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

• STOT-single exposure Based on available data, the classification criteria are not met.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic tox 120-92-3 C	vclopentanone
	100 mg/l (daphnia magna)
EC50/72 h	>100 mg/l (scenedesmus subspicatus)
LC50/96 h	>100 mg/l (fish)
107-98-2 1-	methoxy-2-propanol
EC50/96 hr	23300 mg/l (daphnia magna)
	>1000 mg/l (green algae)
LC50/96 h	20800 mg/l (Pimephales promelas)
· 12.3 Bioacc	ence and degradability No further relevant information available. umulative potential No further relevant information available. ty in soil No further relevant information available.

(Contd. on page 8)

<sup>-</sup> GB



Printing date 16.10.2024

## Safety data sheet according to UK REACH

Version number 6

Revision: 16.10.2024

Trade name: LOR B Series Resists

(Contd. of page 7)

#### • Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

• 12.5 Results of PBT and vPvB assessment

• *PBT*: Not applicable.

• **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

• 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

### SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1866	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1866 RESIN SOLUTION RESIN SOLUTION	
· 14.3 Transport hazard class(es)		
· ADR, IMDG, IATA		
· Class · Label	3 Flammable liquids. 3	
· 14.4 Packing group · ADR, IMDG, IATA	III	
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No	
<ul> <li>14.6 Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> <li>EMS Number:</li> </ul>	Warning: Flammable liquids. 33 F-E, <u>S-E</u>	
• 14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	of Not applicable.	
· Transport/Additional information:		
· ADR · Limited quantities (LQ)	5L	
	(0	Contd. on page 9)



Printing date 16.10.2024

Version number 6

Revision: 16.10.2024

Trade name: LOR B Series Resists

		(Contd. of page 8)
· Transport category	3	
• Tunnel restriction code	D/E	
· UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, III	

### SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

#### Reportable poisons

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

#### · Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

*PBT: Persistent, Bioaccumulative and Toxic* 

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 10)



Version number 6

Revision: 16.10.2024

Printing date 16.10.2024

Trade name: LOR B Series Resists

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 (Contd. of page 9)

GB