

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version number 4

Revision: 12.10.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: LOR B Series Resists

• Article number:

G316702, G316703, G316704, G316707, G316708, G316709, G316710, G316711, G316712, G316715, G316716, G316719

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- Product category PC30 Photo-chemicals
- Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Manufacturer: Kayaku Advanced Materials 200 Flanders Road Westborough, MA 01581 Telephone: (617) 965-5511 Fax: (617) 965-5818

Importer: A-Gas Electronic Materials Unit 3, IO Centre Swift Valley Rugby, Warwickshire CV21 1TW, UK Tel: +44-0-1788-537535 Fax: +44-0-1788-535835 Website: www.agasem.com Email: customerservice.em@agas.com

Further information obtainable from: Product Safety
Email: productsafety@kayakuAM.com
1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

(Contd. on page 2)

GB •



Printing date 12.10.2021

Version number 4

Revision: 12.10.2021

Trade name: LOR B Series Resists

Englumit 2 112	(Contd. of page
2.2 Lahel eleme	19 Causes serious eye irritation.
	nis ding to Regulation (EC) No 1272/2008
The product is c	lassified and labelled according to the CLP regulation.
Hazard pictogra	
<u> </u>	
GHS02 GHS	07
Signal word Wa	
Hazard statemen	
	e liquid and vapour.
H315 Causes sk	
	rious eye irritation.
Precautionary s	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. N smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,
	present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbo dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internation regulations.
2.3 Other hazar	8

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compon	ents:	
CAS: 120-92-3	Cyclopentanone	65-90%
EINECS: 204-435-9	🐼 Flam. Liq. 3, H226; 🕔 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 107-98-2	1-methoxy-2-propanol	10-15%
EINECS: 203-539-1	� Flam. Liq. 3, H226; � STOT SE 3, H336	
		(Contd. on page 3)

GB



Printing date 12.10.2021

Version number 4

Revision: 12.10.2021

Trade name: LOR B Series Resists

		(Contd.	of page 2)
• Additional Co	omponents:		
102322-80-5	Polyaliphatic imide copolymer Skin Irrit. 2, H315; Eye Irrit. 2, H319		1-20%
	🕐 Skin Irrit. 2, H315; Eye Irrit. 2, H319		
	Proprietary Dye B		0.1-2%
	𝐼 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319		
· Additional in	formation: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents:
- Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

- 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation
 Keep away from ignition sources.
 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

GB ____

Version number 4

Revision: 12.10.2021

Trade name: LOR B Series Resists

(Contd. of page 3)

Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols. Keep away from heat and direct sunlight. Use only under yellow light

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges.

• 7.2 Conditions for safe storage, including any incompatibilities • Storage:

Requirements to be met by storerooms and containers: Store in a cool location. Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.
Information about storage in one common storage facility: Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions).
Further information about storage conditions: Store in cool, dry conditions in well sealed containers.

Store receptacle in a well ventilated area. Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

• General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 5)



Printing date 12.10.2021

⁻ GB -



Printing date 12.10.2021

Version number 4

Revision: 12.10.2021

(Contd. of page 4)

Trade name: LOR B Series Resists

Avoid contact with the eyes and skin.

• Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:

and a

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

• *Material of gloves* Nitrile rubber, NBR

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and ch	nemical properties
General Information	
Appearance:	Timid
Form: Colour:	Liquid Yellow-brown
Odour:	Sweetish
Odour: Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	120 °C
Flash point:	30 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	270 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits:	
Lower:	2.3 Vol %
Upper:	Not determined.
Vapour pressure at 20 °C:	12 hPa

- GB



Printing date 12.10.2021

Version number 4

Revision: 12.10.2021

Trade name: LOR B Series Resists

					(Contd. of page
Density:	Not determ	ined			
Relative density	See Table	l Other Infe	ormation		
Vapour density	Not determ	ined.			
Evaporation rate	Not determ	ined.			
Solubility in / Miscibility with					
water:	Not miscib	le or difficı	ılt to mix.		
Partition coefficient: n-octanol/water:	Not determ	ined.			
Viscosity:					
Dynamic:	Not determ	ined.			
Kinematic:	Not determ	ined.			
9.2 Other information	Name	Number	Sp. Grav.	Vol.(%by w	t.) VOC(g/L)
	LOR 0.7B	G316702	0.965	98	940
	LOR 1B	G316703	0.967	96	930
	LOR 2B	G316704	0.973	95	930
	LOR 3B	G316707	0.980	93	920
	LOR 5B	G316708	0.982	92	910
	LOR 6B	G316709	0.984	91	900
	LOR 7B	G316710	0.988	91	900
	LOR 10B	G316711	0.990	89	880
	LOR 15B	G316712	0.992	88	870
	LOR 20B	G316715	1.002	86	860
	LOR 30B	G316716	1.004	85	850
	LOR 50B	G316719	1.007	82	830

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid
- *Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.*
- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide Nitrogen oxides (NOx)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

 \cdot Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

120-92-3 Cyclopentanone

Oral LD50 1180 mg/kg (Rat)

(Contd. on page 7)

GB



Printing date 12.10.2021

Version number 4

Revision: 12.10.2021

Trade name: LOR B Series Resists

		(Contd. of page 6)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>19.5 mg/l (Rat)
107-98-21	-methoxy-	2-propanol
Oral	LD50	5660 mg/kg (Rat)
Dermal	LD50	13000 mg/kg (rabbit)
Inhalative	LC50/4 h	54.6 mg/l (Rat)
102322-80	-5 Polyalip	ohatic imide copolymer
Oral	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)
Dermal	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)
Experience Additional CMR effect Germ cell Carcinoge Reproduct STOT-sing STOT-rep	sion/irritation n irritation e damage/f vious eye ir y or skin s e with hum toxicologi cts (carcino mutagenic nicity Base ive toxicity gle exposut eated expo	tion irritation

SECTION 12: Ecological information

•	12.	1 T	oxicity	
		'		

• Aquatic toxicity:

120-92-3 Cyclopentanone

EC50/48 h	100 mg/l (daphnia i	magna)
-----------	---------------------	--------

EC50/72 h >100 mg/l (scenedesmus subspicatus)

LC50/96 h >100 mg/l (fish)

107-98-2 1-methoxy-2-propanol

EC50/96 hr 23300 mg/l (daphnia magna)

>1000 mg/l (green algae)

LC50/96 h 20800 mg/l (Pimephales promelas)

· 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

Additional ecological information:

• General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. • 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

(Contd. on page 8)

GB

Version number 4

Revision: 12.10.2021

(Contd. of page 7)

Trade name: LOR B Series Resists

ADVANCED MATERIALS

· vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
ADR, IMDG, IATA	UN1866	
14.2 UN proper shipping name ADR IMDG, IATA	1866 RESIN SOLUTION RESIN SOLUTION	
14.3 Transport hazard class(es)		
ADR, IMDG, IATA		
Class Label	3 Flammable liquids. 3	
14.4 Packing group ADR, IMDG, IATA	111	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number:	Warning: Flammable liquids. 33 F-E, <u>S-E</u>	
14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	of Not applicable.	
Transport/Additional information:		
ADR Limited quantities (LQ) Transport category Tunnel restriction code	5L 3 D/E	
UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, III	

(Contd. on page 9)

Printing date 12.10.2021

ADVANCED MATERIALS

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version number 4

Revision: 12.10.2021

Trade name: LOR B Series Resists

(Contd. of page 8)

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

• Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3