

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/16/2024

Reviewed on 10/16/2024

1 Identification

- **Product identifier**
- **Trade name:** LOR B Series Resists
- **Product number:**
G316702, G316703, G316704, G316707, G316708, G316709, G316710, G316711, G316712, G316715, G316716, G316719
- **Application of the substance / the mixture** Photoresist
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Kayaku Advanced Materials, Inc.
200 Flanders Road
Westborough, MA 01581
Tel: (617) 965-5511
Fax: (617) 965-5818
- **Information department:**
Product Safety
Email: productsafety@kayakuam.com
- **Emergency telephone number:**
Kayaku Advanced Materials : 617-965-5511
Chemtrec USA Emergency : 800-424-9300
Chemtrec International Emergency : 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**
Cyclopentanone
- **Hazard statements**
H226 Flammable liquid and vapor.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/16/2024

Reviewed on 10/16/2024

Trade name: LOR B Series Resists

(Contd. of page 1)

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:
NFPA ratings (scale 0 - 4)


Health = 2

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)


Health = 2

Fire = 3

Reactivity = 0

Other hazards
Results of PBT and vPvB assessment

 • **PBT:** Not applicable.

 • **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

 • **Description:** Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

120-92-3	Cyclopentanone ⚠ Flammable Liquids 3, H226; ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319	65-85%
102322-80-5	Polyaliphatic imide copolymer ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319	1-20%
107-98-2	1-methoxy-2-propanol ⚠ Flammable Liquids 3, H226; ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	10-15%

(Contd. on page 3)

Safety Data Sheet


acc. to OSHA HCS

Printing date 10/16/2024

Reviewed on 10/16/2024

Trade name: LOR B Series Resists

(Contd. of page 2)

	Proprietary Dye B  Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Eye Irritation 2A, H319	0.25-2%
--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.
- **After swallowing:**
Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Alcohol resistant foam
Fire-extinguishing powder
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.
- **Advice for firefighters**
- **Protective equipment:** Wear SCBA.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/16/2024

Reviewed on 10/16/2024

Trade name: LOR B Series Resists

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
120-92-3	Cyclopentanone	0.87 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
· PAC-2:		
120-92-3	Cyclopentanone	9.5 ppm
107-98-2	1-methoxy-2-propanol	160 ppm
· PAC-3:		
120-92-3	Cyclopentanone	57 ppm
107-98-2	1-methoxy-2-propanol	660 ppm

7 Handling and storage

· Handling:
· Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Keep away from heat and direct sunlight.

Use only under yellow light

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities
· Storage:
· Requirements to be met by storerooms and containers:

Store in a cool location.

Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.

· Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Keep container well-sealed in cool, dry location.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.
· Control parameters
· Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/16/2024

Reviewed on 10/16/2024

Trade name: LOR B Series Resists

(Contd. of page 4)

At this time, the other constituents have no known exposure limits.

107-98-2 1-methoxy-2-propanol

REL	Short-term value: 540 mg/m ³ , 150 ppm Long-term value: 360 mg/m ³ , 100 ppm
TLV	Short-term value: 553 mg/m ³ , 150 ppm Long-term value: 369 mg/m ³ , 100 ppm

 · **Additional information:** The lists that were valid during the creation were used as basis.

 · **Exposure controls**

 · **Personal protective equipment:**

 · **General protective and hygienic measures:**

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

 · **Respiratory equipment:**

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

 · **Protection of hands:**


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

 · **Material of gloves** Nitrile rubber, NBR

 · **Penetration time of glove material** Contact glove manufacture for break-through time.

 · **Eye protection:**


Tightly sealed goggles

9 Physical and chemical properties

 · **Information on basic physical and chemical properties**

 · **General Information**

 · **Appearance:**

Form: Liquid

Color: Yellow-brown

 · **Odor:** Sweet

 · **Odor threshold:** Not determined.

 · **pH-value:** Not determined.

 · **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 120 °C (248 °F)

 · **Flash point:** 30 °C (86 °F)

 · **Flammability:** Not applicable.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/16/2024

Reviewed on 10/16/2024

Trade name: LOR B Series Resists

(Contd. of page 5)

· Auto igniting:	270 °C (518 °F)																																																																	
· Decomposition temperature:	Not determined.																																																																	
· Ignition temperature:	Product is not selfigniting.																																																																	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.																																																																	
· Explosion limits:																																																																		
Lower:	2.3 Vol %																																																																	
Upper:	Not determined.																																																																	
· Vapor pressure at 20 °C (68 °F):	12 hPa (9 mm Hg)																																																																	
· Density:	See Other information																																																																	
· Vapor density	Not determined.																																																																	
· Evaporation rate	Not determined.																																																																	
· Solubility in / Miscibility with Water:	Water miscible No																																																																	
· Partition coefficient (n-octanol/water):	Not determined.																																																																	
· Viscosity:																																																																		
Dynamic:	Not determined.																																																																	
Kinematic:	Not determined.																																																																	
· Other information	<table><tr><td>Name</td><td>Number</td><td>Sp. Grav.</td><td>VOC(%by wt.)</td><td>VOC(g/L)</td></tr><tr><td>LOR 0.7B</td><td>G316702</td><td>0.947</td><td>98</td><td>925</td></tr><tr><td>LOR 1B</td><td>G316703</td><td>0.952</td><td>96</td><td>915</td></tr><tr><td>LOR 2B</td><td>G316704</td><td>0.955</td><td>95</td><td>910</td></tr><tr><td>LOR 3B</td><td>G316707</td><td>0.961</td><td>93</td><td>900</td></tr><tr><td>LOR 5B</td><td>G316708</td><td>0.966</td><td>92</td><td>890</td></tr><tr><td>LOR 6B</td><td>G316709</td><td>0.967</td><td>91</td><td>885</td></tr><tr><td>LOR 7B</td><td>G316710</td><td>0.969</td><td>91</td><td>880</td></tr><tr><td>LOR 10B</td><td>G316711</td><td>0.974</td><td>89</td><td>870</td></tr><tr><td>LOR 15B</td><td>G316712</td><td>0.978</td><td>88</td><td>860</td></tr><tr><td>LOR 20B</td><td>G316715</td><td>0.985</td><td>86</td><td>850</td></tr><tr><td>LOR 30B</td><td>G316716</td><td>0.987</td><td>85</td><td>840</td></tr><tr><td>LOR 50B</td><td>G316719</td><td>0.998</td><td>82</td><td>815</td></tr></table>	Name	Number	Sp. Grav.	VOC(%by wt.)	VOC(g/L)	LOR 0.7B	G316702	0.947	98	925	LOR 1B	G316703	0.952	96	915	LOR 2B	G316704	0.955	95	910	LOR 3B	G316707	0.961	93	900	LOR 5B	G316708	0.966	92	890	LOR 6B	G316709	0.967	91	885	LOR 7B	G316710	0.969	91	880	LOR 10B	G316711	0.974	89	870	LOR 15B	G316712	0.978	88	860	LOR 20B	G316715	0.985	86	850	LOR 30B	G316716	0.987	85	840	LOR 50B	G316719	0.998	82	815
Name	Number	Sp. Grav.	VOC(%by wt.)	VOC(g/L)																																																														
LOR 0.7B	G316702	0.947	98	925																																																														
LOR 1B	G316703	0.952	96	915																																																														
LOR 2B	G316704	0.955	95	910																																																														
LOR 3B	G316707	0.961	93	900																																																														
LOR 5B	G316708	0.966	92	890																																																														
LOR 6B	G316709	0.967	91	885																																																														
LOR 7B	G316710	0.969	91	880																																																														
LOR 10B	G316711	0.974	89	870																																																														
LOR 15B	G316712	0.978	88	860																																																														
LOR 20B	G316715	0.985	86	850																																																														
LOR 30B	G316716	0.987	85	840																																																														
LOR 50B	G316719	0.998	82	815																																																														

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
Heat, flames and sparks. Extremes of temperature and direct sunlight.
Contact with incompatible materials.
- **Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/16/2024

Reviewed on 10/16/2024

Trade name: LOR B Series Resists

Nitrogen oxides (NOx)

(Contd. of page 6)

11 Toxicological information

 · **Information on toxicological effects**

 · **Acute toxicity:**

 · **LD/LC50 values that are relevant for classification:**

120-92-3 Cyclopentanone

Oral	LD50	1180 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>19.5 mg/l (Rat)

107-98-2 1-methoxy-2-propanol

Oral	LD50	5660 mg/kg (Rat)
Dermal	LD50	13000 mg/kg (rabbit)
Inhalative	LC50/4 h	54.6 mg/l (Rat)

102322-80-5 Polyaliphatic imide copolymer

Oral	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)
Dermal	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)

 · **Primary irritant effect:**

 · **on the skin:** Irritant to skin and mucous membranes.

 · **on the eye:** Irritating effect.

 · **Sensitization:** No sensitizing effects known.

 · **Experience with humans:** No further relevant information available.

 · **Additional toxicological information:**

 The product shows the following dangers according to internally approved calculation methods for preparations:
 Irritant

 · **Carcinogenic categories**

 · **IARC (International Agency for Research on Cancer)**

None of the ingredients are listed.

 · **NTP (National Toxicology Program)**

None of the ingredients are listed.

 · **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

12 Ecological information

 · **Toxicity**

 · **Aquatic toxicity:**

120-92-3 Cyclopentanone

EC50/48 h	100 mg/l (daphnia magna)
EC50/72 h	>100 mg/l (scenedesmus subspicatus)
LC50/96 h	>100 mg/l (fish)

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/16/2024

Reviewed on 10/16/2024

Trade name: LOR B Series Resists

(Contd. of page 7)

107-98-2 1-methoxy-2-propanol


EC50/96 hr	23300 mg/l (daphnia magna)
	>1000 mg/l (green algae)
LC50/96 h	20800 mg/l (Pimephales promelas)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.
 Disposal must be made in accordance with Federal, State, and Local regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made in accordance with Federal, State, and Local regulations.

14 Transport information

- | | |
|--------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA | UN1866 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT, IMDG, IATA · ADR | RESIN SOLUTION
1866 RESIN SOLUTION |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | |
|  | |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids
3 |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/16/2024

Reviewed on 10/16/2024

Trade name: LOR B Series Resists

(Contd. of page 8)

 · **ADR, IMDG, IATA**


· Class	3 Flammable liquids
· Label	3

· Packing group	III
· DOT, ADR, IMDG, IATA	III

· Environmental hazards:	
· Marine pollutant:	No

· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, S-E

· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
-----------------------------------------------------------------------------------	-----------------

· UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, III
---------------------------------	--------------------------------

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):** All ingredients are listed or comply with TSCA regulations.

· **Hazardous Air Pollutants**

None of the ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients are listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/16/2024

Reviewed on 10/16/2024

Trade name: LOR B Series Resists

(Contd. of page 9)

· TLV (Threshold Limit Value)	
None of the ingredients are listed.	
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients are listed.	
· Massachusetts State Right To Know List	
120-92-3	Cyclopentanone
107-98-2	1-methoxy-2-propanol
· New Jersey State Right To Know List	
120-92-3	Cyclopentanone
107-98-2	1-methoxy-2-propanol
· Pennsylvania Hazardous Substances List	
120-92-3	Cyclopentanone
107-98-2	1-methoxy-2-propanol

- **California SCAQMD Rule 443.1 VOC's:** See Section 9
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**
Cyclopentanone
- **Hazard statements**
H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
- **Precautionary statements**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P302+P352 If on skin: Wash with plenty of soap and water.
P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/16/2024

Reviewed on 10/16/2024

Trade name: LOR B Series Resists· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department
- **Contact:** Tom Cole, EHS Manager (tcole@kayakuam.com)

· **Revision History:**

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

- **Date of preparation / last revision** 10/16/2024 / 5

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Acute Toxicity - Oral 4: Acute toxicity – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3