GB

ADVANCED MATERIALS

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2022

Version number 6

Revision: 03.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

• Article number: M089025

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment

• Product category PC21 Laboratory chemicals

· Application of the substance / the mixture Solvents

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier: Manufacturer: Kayaku Advanced Materials
200 Flanders Road Westborough, MA 01581 Telephone: (617) 965-5511 Fax: (617) 965-5818

Importer: A-Gas Electronic Materials Unit 3, IO Centre Swift Valley Rugby, Warwickshire CV21 1TW, UK Tel: +44-0-1788-537535 Fax: +44-0-1788-535835 Website: www.agasem.com Email: customerservice.em@agas.com

• Further information obtainable from:

Product Safety Email: productsafety@kayakuAM.com • **1.4 Emergency telephone number:** Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
Classification according to Regulation (EC) No 1272/2008
flame
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. (Contd. on page 2)



rinting date 03.02.	2022	Version number 6	Revision: 03.02.2022
rade name: MIBK	/IPA 1:3 Positive Ro	adiation Resist Developer	
			(Contd. of page 1)
· 2.2 Label eleme			
	ding to Regulation (
• Hazard pictogra		d according to the CLP regulation.	
· Hazara piciogri	ums		
_ < ≝>< !	>		
GHS02 GHS	507		
· Signal word Da	nger		
-	ning components of	labelling:	
Isopropyl alcoh		0	
Methyl isobutyl	ketone		
· Hazard stateme			
	hly flammable liquid		
	ises serious eye irrit		
		rritation. May cause drowsiness or dizzine	ess.
• Precautionary s P210		n heat, hot surfaces, sparks, open flame	as and other ignition sources. No
1210	smoking.	n neui, noi surjuces, spurks, open jiume	es und other ignition sources. No
P261		dust/fume/gas/mist/vapours/spray.	
P280		gloves/protective clothing/eye protection/f	ace protection.
P301+P310		D: Immediately call a POISON CENTER	
P302+P352	IF ON SKIN: We	ash with plenty of soap and water.	
P304+P341		breathing is difficult, remove victim to fre	sh air and keep at rest in a position
DAGE =	comfortable for		
P305+P351+P3		nse cautiously with water for several m	unutes. Remove contact lenses, if
1000 ± 0010		v to do. Continue rinsing.	~
P333+P313 P337+P313		or rash occurs: Get medical advice/attenti persists: Get medical advice/attention.	<i>On</i> .
P370+P378		Jse to extinguish: Alcohol resistant foam, A	Fire-extinguishing nowder Carbon
1 5/0 1 5/0	dioxide.	σος το επιτησιιών. Ατέθησι resistant joum, i	ene chunguisning powder, curbon
P403+P235		entilated place. Keep cool.	
P501		tents/container in accordance with loco	ul/regional/national/international
· 2.3 Other hazar	0		
-	and vPvB assessmen	nt	
• PBT: Not applie			
• vPvB: Not appli			

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

 $\cdot \textit{Description: Mixture of substances listed below with nonhazardous additions.}$

(Contd. on page 3) GB-



Printing date 03.02.2022

Version number 6

Revision: 03.02.2022

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

	(Cont	td. of page 2)
· Dangerous compone	ents:	
CAS: 67-63-0	Isopropyl alcohol	70-80%
EINECS: 200-661-7	� Flam. Liq. 2, H225; � Eye Irrit. 2, H319; STOT SE 3, H336	-
CAS: 108-10-1	Methyl isobutyl ketone	20-30%
EINECS: 203-550-1		-

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing: Do not induce vomiting; call for medical help immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- Alcohol resistant foam
- Fire-extinguishing powder
- Carbon dioxide
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Water
- \cdot 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Keep away from ignition sources.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 6

Revision: 03.02.2022

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 3)

Ensure adequate ventilation • 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Store in cool, dry place in tightly closed receptacles. Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Use explosion-proof apparatus / fittings and spark-proof tools.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and containers:** Store in a cool location.

· Information about storage in one common storage facility: Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions).

- Further information about storage conditions:
- Store in cool, dry conditions in well sealed containers.
- Store receptacle in a well ventilated area.

Store under lock and key and with access restricted to technical experts or their assistants only.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

67-63-0 Isopropyl alcohol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

108-10-1 Methyl isobutyl ketone

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sk, BMGV

(Contd. on page 5)



Printing date 03.02.2022

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2022

Version number 6

Revision: 03.02.2022

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 4) · Ingredients with biological limit values: 108-10-1 Methyl isobutyl ketone BMGV 20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one • Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Personal protective equipment: · General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Do not inhale gases / fumes / aerosols. • Respiratory protection: In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device. · Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. · Material of gloves **PVA** gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. · Eye protection: Tightly sealed goggles

9.1 Information on basic physical and chemical properties General Information		
Appearance:		
Form:	Liquid	
Colour:	Colourless	
Odour:	Like alcohol	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling ra	nge: 82-116 °C	



Printing date 03.02.2022

Version number 6

Revision: 03.02.2022

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

	(Contd. of page 5)
· Flash point:	13 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	425 °C
· Decomposition temperature:	Not determined.
• Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	1.7 Vol % 12.0 Vol %
· Vapour pressure at 20 °C:	43 hPa
 Density: Relative density at 20 °C Vapour density Evaporation rate 	Not determined. 0.789 g/cm ³ Not determined. Not determined.
· Solubility in / Miscibility with water:	Partly miscible.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents:	100.0 %
• 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Possible formation of peroxide.
- 10.4 Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.
- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:
- Carbon monoxide and carbon dioxide
- Flammable gases/vapours

(Contd. on page 7)

GB

ADVANCED MATERIALS

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.02.2022

Version number 6

Revision: 03.02.2022

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 6)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

67-63-0 Isopropyl alcohol		
Oral	LD50	5045 mg/kg (Rat)
	LD50	12800 mg/kg (rabbit)
T 1 1 (·	1050/11	$20 \dots (1 (D \dots))$

Inhalative LC50/4 h 30 mg/l (Rat)

108-10-1 Methyl isobutyl ketone

Oral	LD50	2080 mg/kg (Rat)
	LD50	1600 mg/kg (rab)
Inhalative	LC50/4 h	100 mg/l (Rat)

· Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation

Causes serious eye irritation.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

• *Experience with humans:* No further relevant information available.

Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

• STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

67-63-0 Isoj	propyl alcohol	
EC50/48 h	7550-13300 mg/l (daphnia magna) (immobilization)	
EC50/72 h	>1000 mg/l (scenedesmus subspicatus) (Growth rate inhibition)	
LC50/96 h	9640-10400 mg/l (Pimephales promelas)	
108-10-1 M	ethyl isobutyl ketone	
EC50/96 hr	980 mg/l (scenedesmus subspicatus)	
	400 mg/l (Selenastrum capricornutum)	
LC50/24 h	5000 mg/l (daphnia magna)	
	460 mg/l (goldfish)	
LC50/96 h	505 mg/l (fathead minnow)	
	505-540 mg/l (Pimephales promelas)	
	600 mg/l (Salmo gairdneri)	
	1	(Contd. on page

ADVANCED MATERIALS

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 03.02.2022

Printing date 03.02.2022

Version number 6

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

(Contd. of page 7)

• 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available. • 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

UN1993
FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHO) METHYL ISOBUTYL KETONE)
3 Flammable liquids. 3
II
No
Warning: Flammable liquids.
33 F-E, <u>S-E</u>
of Not applicable.



Printing date 03.02.2022

Version number 6

Revision: 03.02.2022

Trade name: MIBK/IPA 1:3 Positive Radiation Resist Developer

• Transport/Additional information:	(Contd. of page a
· ADR	
· Limited quantities (LQ)	1L
Transport category	2
• Tunnel restriction code	D/E
· UN ''Model Regulation'':	UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANO) (ISOPROPYL ALCOHOL), METHYL ISOBUTYL KETONE), 3 II

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

• **Department issuing SDS:** Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

• Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity – Category 4 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3