

Printing date 10/12/2021 Reviewed on 10/12/2021

1 Identification

- · Product identifier
- · Trade name: PMGI SF Slow Series Resists
- · Product number:

G213102, G213103, G213104, G213105, G213106, G213107, G213108, G213109, G213111, G213113, G213115, G213119

- · Application of the substance / the mixture Photoresist
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials, Inc.

200 Flanders Road

Westborough, MA 01581

Tel: (617) 965-5511 Fax: (617) 965-5818

· Information department:

Product Safety

Email: productsafety@kayakuAM.com

Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300

Chemtrec International Emergency: 703-527-3887

2 Hazard(s) identification

Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Printing date 10/12/2021 Reviewed on 10/12/2021

Trade name: PMGI SF Slow Series Resists

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07

- · Signal word Warning
- Hazard-determining components of labeling:

Tetrahydrofurfuryl alcohol

· Hazard statements

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.



Printing date 10/12/2021 Reviewed on 10/12/2021

Trade name: PMGI SF Slow Series Resists

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous c	Dangerous components:	
120-92-3	Cyclopentanone	65-85%
	🍑 Flam. Liq. 3, H226; 🐠 Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
97-99-4	Tetrahydrofurfuryl alcohol	1-15%
102322-80-5	Polyaliphatic imide copolymer	1-25%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

· Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

(Contd. on page 4)



Printing date 10/12/2021 Reviewed on 10/12/2021

Trade name: PMGI SF Slow Series Resists

(Contd. of page 3)

· Advice for firefighters

· Protective equipment: Wear SCBA.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Keep receptacles tightly sealed.

Use only under yellow light

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers:

Store in a cool location.

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products.

· Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Keep container well-sealed in cool, dry location.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)



Printing date 10/12/2021 Reviewed on 10/12/2021

Trade name: PMGI SF Slow Series Resists

(Contd. of page 4)

· Control parameters

· Components with limit values that require monitoring at the workplace:

97-99-4 Tetrahydrofurfuryl alcohol

WEEL 0.5 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Do not inhale gases / fumes / aerosols.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

· Protection of hands:



Protective gloves

Contact golve manufacturerer for break-through time.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material Contact glove manufacture for break-through time.
- · Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: Clear to light yellow
Odor: Slightly sweet
Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 130 °C (266 °F)

Flash point: 30 °C (86 °F)

Flammability (solid, gaseous): Not applicable.

(Contd. on page 6)



Printing date 10/12/2021 Reviewed on 10/12/2021

Trade name: PMGI SF Slow Series Resists

	(Contd. of pag	
Ignition temperature:	280 °C (536 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.	
Explosion limits: Lower: Upper:	1.5 Vol % 9.7 Vol %	
Vapor pressure at 20 °C (68 °F):	0.3 hPa (0.2 mm Hg)	
Density: Relative density Vapor density Evaporation rate	Not determined. See Table 1 Other Information Not determined. Not determined.	
Solubility in / Miscibility with Water:	Partly miscible.	
Partition coefficient (n-octanol/wate	er): Not determined.	
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
Other information	Table 1. Product specific gravity and VOC data.	
	Name Number Sp. Grav. Vol.(%by wt.) VOC(g/L) SF2S G213102 0.968 98 950 SF3S G213103 0.970 97 945 SF4S G213104 0.973 96 935 SF5S G213105 0.975 95 930 SF6S G213106 0.980 94 920 SF7S G213107 0.981 93 915 SF8S G213108 0.984 92 905 SF9S G213109 0.985 91 900 SF11S G213111 0.992 89 880 SF13S G213113 0.998 87 860 SF15S G213115 1.003 85 850	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Contact with incompatible materials.

Heat, flames and sparks. Extremes of temperature and direct sunlight.

· Incompatible materials: Strong Oxidizing Agents, Strong Bases, Strong Acids, Amines

(Contd. on page 7)



Printing date 10/12/2021 Reviewed on 10/12/2021

Trade name: PMGI SF Slow Series Resists

(Contd. of page 6)

· Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:						
97-99-4 Te	97-99-4 Tetrahydrofurfuryl alcohol						
Oral	LD50	800 mg/kg (Guinea pig)					
		2300 mg/kg (mouse)					
		1600 mg/kg (Rat)					
Dermal	LD50	5000 mg/kg (Guinea pig)					
120-92-3 (120-92-3 Cyclopentanone						
Oral	LD50	1180 mg/kg (Rat)					
Dermal	LD50	>2000 mg/kg (rabbit)					
Inhalative	LC50/4 h	>19.5 mg/l (Rat)					
102322-80	102322-80-5 Polyaliphatic imide copolymer						
Oral	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)					
Dermal	LD50	>5000 mg/kg (Rat) (Data for compositionally similar material)					

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

None of the ingredients are listed.

· NTP (National Toxicology Program)

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:	
120-92-3 Cyclopentanone	
EC50/48 h	100 mg/l (daphnia magna)
EC50/72 h	>100 mg/l (scenedesmus subspicatus)
LC50/96 h	>100 mg/l (fish)

· Persistence and degradability No further relevant information available.

(Contd. on page 8)



Printing date 10/12/2021 Reviewed on 10/12/2021

Trade name: PMGI SF Slow Series Resists

(Contd. of page 7)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

UN-Number DOT, ADR, IMDG, IATA	UN1866	
UN proper shipping name DOT, IMDG, IATA ADR	RESIN SOLUTION 1866 RESIN SOLUTION	
Transport hazard class(es)		
DOT		
Class	3 Flammable liquids	
Label	3 Frammable liquids	
ADR, IMDG, IATA		
Class	3 Flammable liquids	
Label	3	
Packing group DOT, ADR, IMDG, IATA	III	



Printing date 10/12/2021 Reviewed on 10/12/2021

Trade name: PMGI SF Slow Series Resists

(Contd. of page 8)

· Environmental hazards:

· Marine pollutant:

· Special precautions for user Warning: Flammable liquids

· Hazard identification number (Kemler code): 33

• EMS Number: F-E,S-E

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN ''Model Regulation'': UN1866, RESIN SOLUTION, 3, III

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

No

- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- · TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.
- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

120-92-3 Cyclopentanone

97-99-4 Tetrahydrofurfuryl alcohol

· New Jersey State Right To Know List

120-92-3 Cyclopentanone

· Pennsylvania Hazardous Substances List

120-92-3 Cyclopentanone

(Contd. on page 10)



Printing date 10/12/2021 Reviewed on 10/12/2021

Trade name: PMGI SF Slow Series Resists

(Contd. of page 9)

97-99-4 Tetrahydrofurfuryl alcohol

- · California SCAQMD Rule 443.1 VOC's: See Table 1 Section 9
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02 GH

GHS07 GHS

- · Signal word Warning
- Hazard-determining components of labeling:

Tetrahydrofurfuryl alcohol

· Hazard statements

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Date of preparation / last revision 10/12/2021 / 3

(Contd. on page 11)



Printing date 10/12/2021 Reviewed on 10/12/2021

Trade name: PMGI SF Slow Series Resists

(Contd. of page 10)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Repr. 2: Reproductive toxicity – Category 2