

Printing date 12.10.2021 Version number 4 Revision: 12.10.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PMGI SFG Slow Series Resists
- · Article number:

G212120, G212150, G212160, G212170, G212101, G212102, G212103, G212106, G212109, G212115

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Product category PC30 Photo-chemicals
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Telephone: (617) 965-5511

Fax: (617) 965-5818

Importer:

A-Gas Electronic Materials

Unit 3, IO Centre

Swift Valley

Rugby, Warwickshire

CV21 1TW, UK

Tel: +44-0-1788-537535 Fax: +44-0-1788-535835

Website: www.agasem.com

 ${\it Email: customers ervice.em@agas.com}$

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuAM.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

(Contd. on page 2)



Printing date 12.10.2021 Version number 4 Revision: 12.10.2021

Trade name: PMGI SFG Slow Series Resists

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

moking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

| · Dangerous compo | ents: | |
|-------------------|---|--------|
| CAS: 120-92-3 | Cyclopentanone | 65-85% |
| EINECS: 204-435- | 🔗 🚫 Flam. Liq. 3, H226; 🕔 Skin Irrit. 2, H315; Eye Irrit. 2, H319 | |
| CAS: 107-98-2 | 1-methoxy-2-propanol | 1-15% |
| EINECS: 203-539- | 🚺 🍅 Flam. Liq. 3, H226; 🐠 STOT SE 3, H336 | |

| · Additional | Components: |
|--------------|-------------|
| | |

(Contd. on page 3)



Printing date 12.10.2021 Version number 4 Revision: 12.10.2021

Trade name: PMGI SFG Slow Series Resists

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

· 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

- 6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Printing date 12.10.2021 Revision: 12.10.2021 Version number 4

Trade name: PMGI SFG Slow Series Resists

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers: Store in a cool location.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

- · Further information about storage conditions: Store in cool, dry conditions in well sealed containers.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves Nitrile rubber, NBR

(Contd. on page 5)



Printing date 12.10.2021 Version number 4 Revision: 12.10.2021

Trade name: PMGI SFG Slow Series Resists

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

| CECTION | TO 7 | | | | • |
|------------|------------|--------|------------|---------|-----|
| SECTION 9: | Physical | and c | nomical | nraneri | 105 |
| DECITOR >. | I Itysicut | and ci | iciliticat | propert | |

| | 1 • 1 |
|---|---|
| 9.1 Information on basic physical and c | hemical properties |
| General Information Appearance: | |
| Form: | Liquid |
| Colour: | Clear to light yellow |
| Odour: | Slightly sweet |
| Odour threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range | : 120 °C |
| Flash point: | 30 °C |
| Flammability (solid, gas): | Not applicable. |
| Ignition temperature: | 270 °C |
| Decomposition temperature: | Not determined. |
| Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosive air/vapo mixtures are possible. |
| Explosion limits: | |
| Lower: | 2.3 Vol % |
| Upper: | Not determined. |
| Vapour pressure at 20 °C: | 12 hPa |
| Density: | Not determined |
| Relative density | Not determined. |
| | See Table 1 Other Information |
| · Vapour density | Not determined. |
| Evaporation rate | Not determined. |
| · Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |
| Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |

(Contd. on page 6)



Printing date 12.10.2021 Version number 4 Revision: 12.10.2021

Trade name: PMGI SFG Slow Series Resists

| (Contd. of page | e 5) |
|--|--|
| Not determined. | |
| Name Number Sp. Grav. Vol. (%by wt.) VOC (g/L) SFG 0.2S G212120 0.950 99.8 940 SFG 0.5S G212150 0.950 99.5 940 SFG 0.6S G212160 0.950 99.4 940 SFG 0.7S G212170 0.950 99.3 940 SFG 1S G212101 0.950 99 940 SFG 2S G212102 0.960 98 940 SFG 3S G212103 0.970 97 940 SFG 6S G212106 0.980 94 920 SFG 9S G212109 0.990 91 900 | |
| | Not determined. Name Number Sp. Grav. Vol.(%by wt.) VOC(g/L) SFG 0.2S G212120 0.950 99.8 940 SFG 0.5S G212150 0.950 99.5 940 SFG 0.6S G212160 0.950 99.4 940 SFG 0.7S G212170 0.950 99.3 940 SFG 1S G212101 0.950 99 940 SFG 2S G212102 0.960 98 940 SFG 3S G212103 0.970 97 940 SFG 6S G212106 0.980 94 920 |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 1 | values rele | vant for classification: |
|-------------|-------------|---|
| 120-92-3 (| Cyclopenta | none |
| Oral | LD50 | 1180 mg/kg (Rat) |
| Dermal | LD50 | >2000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >19.5 mg/l (Rat) |
| 107-98-2 1 | -methoxy- | 2-propanol |
| Oral | LD50 | 5660 mg/kg (Rat) |
| Dermal | LD50 | 13000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 54.6 mg/l (Rat) |
| 102322-80 | -5 Polyalip | phatic imide copolymer |
| Oral | LD50 | >5000 mg/kg (Rat) (Data for compositionally similar material) |
| Dermal | LD50 | >5000 mg/kg (Rat) (Data for compositionally similar material) |

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.



Printing date 12.10.2021 Version number 4 Revision: 12.10.2021

Trade name: PMGI SFG Slow Series Resists

(Contd. of page 6)

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

| · Aquatic tox | icity: |
|---------------|-------------------------------------|
| 120-92-3 Cy | yclopentanone |
| EC50/48 h | 100 mg/l (daphnia magna) |
| EC50/72 h | >100 mg/l (scenedesmus subspicatus) |
| LC50/96 h | >100 mg/l (fish) |
| 107-98-2 1- | methoxy-2-propanol |
| EC50/96 hr | 23300 mg/l (daphnia magna) |
| | >1000 mg/l (green algae) |
| LC50/96 h | 20800 mg/l (Pimephales promelas) |

- · 12.2 Persistence and degradability Moderately /partly biodegradable
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

GB



Printing date 12.10.2021 Version number 4 Revision: 12.10.2021

Trade name: PMGI SFG Slow Series Resists

(Contd. of page 7)

| 14.1 UN-Number | | |
|--|--------------------------------|--|
| ADR, IMDG, IATA | UN1866 | |
| 14.2 UN proper shipping name | | |
| ADR | 1866 RESIN SOLUTION | |
| IMDG, IATA | RESIN SOLUTION | |
| 14.3 Transport hazard class(es) | | |
| ADR, IMDG, IATA | | |
| | | |
| CI | 2.51 | |
| Class Label | 3 Flammable liquids. | |
| | 3 | |
| 14.4 Packing group | | |
| ADR, IMDG, IATA | III | |
| 14.5 Environmental hazards: | | |
| Marine pollutant: | No | |
| 14.6 Special precautions for user | Warning: Flammable liquids. | |
| Hazard identification number (Kemler code): | 33 | |
| EMS Number: | F-E, <u>S-E</u> | |
| 14.7 Transport in bulk according to Annex II o | pf | |
| Marpol and the IBC Code | Not applicable. | |
| Transport/Additional information: | | |
| ADR | | |
| Limited quantities (LQ) | 5L | |
| Transport category | 3 | |
| Tunnel restriction code | D/E | |
| UN ''Model Regulation'': | UN1866, RESIN SOLUTION, 3, III | |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

(Contd. on page 9)



Printing date 12.10.2021 Version number 4 Revision: 12.10.2021

Trade name: PMGI SFG Slow Series Resists

(Contd. of page 8)

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

_ CF