

Printing date 13.12.2024

Version number 4

Revision: 13.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: PN 1000 Developer

· Article number: Y056075

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment

· Product category PC21 Laboratory chemicals

· Application of the substance / the mixture Photoresist Developer

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier: Manufacturer: Kayaku Advanced Materials
200 Flanders Road Westborough, MA 01581 Telephone: (617) 965-5511 Fax: (617) 965-5818

Importer: A-Gas Electronic Materials Unit 3, IO Centre Swift Valley Rugby, Warwickshire CV21 1TW, UK Tel: +44-0-1788-537535 Fax: +44-0-1788-535835 Website: www.agasem.com Email: customerservice.em@agas.com

• Further information obtainable from:

Product Safety Email: productsafety@kayakuam.com • **1.4 Emergency telephone number:** Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.

(Contd. on page 2)

GB -



Revision: 13.12.2024

Printing date 13.12.2024

Version number 4

Trade	name:	PN	1000	Developer

	(Contd. of pag
\wedge	
GHS)7
$\mathbf{\vee}$	
	315 Causes skin irritation.
STOT SE 3 H.	335 May cause respiratory irritation.
2.2 Label eleme	nts
	ding to Regulation (EC) No 1272/2008
	lassified and labelled according to the GB CLP regulation.
Hazard pictogr	ims
< (%) < []	
\checkmark	
GHS02 GHS	605 GHS07
• Signal word Da	nger
· Hazard-determ	ining components of labelling:
Ethyl lactate	
· Hazard stateme	nts
H226 Flammab	le liquid and vapour.
H315 Causes sk	in irritation.
	rious eye damage.
	e respiratory irritation.
Precautionary	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
P261	smoking. Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protectio
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a posi-
	comfortable for breathing.
P305+P351+P.	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses
	present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Car dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internation
1 501	regulations.
2.3 Other hazar	
	and vPvB assessment
• PBT: Not applied	
	icable.

(Contd. on page 3)



Printing date 13.12.2024

Version number 4

Revision: 13.12.2024

Trade name: PN 1000 Developer

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 123-42-2	4-hydroxy-4-methylpentan-2-one	60-80%
EINECS: 204-626-7	🚸 Flam. Liq. 3, H226; 🚸 Eye Irrit. 2, H319	
CAS: 97-64-3	Ethyl lactate	10-25%
EINECS: 202-598-0	� Flam. Liq. 3, H226; � Eye Dam. 1, H318; � Skin Irrit. 2, H315; STOT SE 3, H335	
Additional informations For the wording of the listed hazand physics refer to section 16		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- *After skin contact: Generally the product does not irritate the skin.*
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing: If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- Alcohol resistant foam
- Fire-extinguishing powder

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources.

 6.2 Environmental precautions: Dilute with plenty of water.
 Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Revision: 13.12.2024

Printing date 13.12.2024

Version number 4

Trade name: PN 1000 Developer

(Contd. of page 3)

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.

Keep away from heat and direct sunlight.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Use explosion-proof apparatus / fittings and spark-proof tools.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• **Requirements to be met by storerooms and containers:** No special requirements.

• Information about storage in one common storage facility: Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions).

- *Further information about storage conditions:* Store in cool, dry conditions in well sealed containers. Protect from heat and direct sunlight. Store receptacle in a well ventilated area.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

123-42-2 4-hydroxy-4-methylpentan-2-one

WEL Short-term value: 362 mg/m³, 75 ppm Long-term value: 241 mg/m³, 50 ppm

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

• General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

(Contd. on page 5)



Printing date 13.12.2024

Version number 4

Revision: 13.12.2024

Trade name: PN 1000 Developer

(Contd. of page 4)

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

- *The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR*
- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and ch	nemical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	Clear to light yellow
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	150 °C
Flash point:	46 °C
Flammability	Not applicable.
Auto-ignition temperature:	400 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.0 Vol %
Upper:	17.0 Vol %
Vapour pressure at 20 °C:	1.1 hPa
Density at 20 °C:	0.9557 g/cm^3

GB -



Printing date 13.12.2024

Version number 4

Revision: 13.12.2024

Trade name: PN 1000 Developer

	(Contd. of page 5
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Fully miscible.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

- Contact with incompatible materials.
- 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases

· 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

123-42-2 4	123-42-2 4-hydroxy-4-methylpentan-2-one	
Oral	LD50	2520 mg/kg (Rat)
Dermal	LD50	13500 mg/kg (rab)
Inhalative	LC50/4 h	1500 mg/l (Rat)
97-64-3 E	thyl lactate	
Oral	LD50	8200 mg/kg (Rat)
Dermal	LD50	5000 mg/kg (rabbit)
Inhalative	Inhalative LC50 8 hr 5.4 mg/l (Rat)	
· Primary in	Primary irritant effect:	
· Skin corra	Skin corrosion/irritation	
Causas ski	Causas slam irritation	

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

• **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

• Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB



Revision: 13.12.2024

Printing date 13.12.2024

Version number 4

Trade name: PN 1000 Developer

(Contd. of page 6)

• Carcinogenicity Based on available data, the classification criteria are not met.

• *Reproductive toxicity Based on available data, the classification criteria are not met.*

• STOT-single exposure

May cause respiratory irritation.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

123-42-2 4-hydroxy-4-methylpentan-2-one

EC50/24 h 9000 mg/l (daphnia magna)

LC50/96 h 420 mg/l (Lepomis macrochirus (Bluegill))

97-64-3 Ethyl lactate

LC50/96 h 320 mg/l (zebra fish)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

• *PBT:* Not applicable.

· vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1993
· 14.2 UN proper shipping name	
· ADR, IMDĠ	FLAMMABLE LIQUID, N.O.S. (DIACETONE ALCOHO
	ETHYL LACTATE)
· IATA	Flammable liquid, n.o.s. (Diacetone alcohol, Ethyl lactate)



Revision: 13.12.2024

Printing date 13.12.2024

Version number 4

	(Contd. of page 7
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
·Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
· Stowage Category	A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	of Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
\cdot Excepted quantities ($\widetilde{E}Q$)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
Turner and a second	Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 D/E
· IMDG · Limited quantities (LQ)	5L
· Excepted quantities (EQ)	SL Code: El
Excepten quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (DIACETONE
	ALCOHOL, ETHYL LACTATE), 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

GB



Revision: 13.12.2024

Printing date 13.12.2024

Version number 4

Trade name: PN 1000 Developer

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation. · Department issuing SDS: Product safety department · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com) • Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3