ADVANCED MATERIALS

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.08.2021

Version number 8

Revision: 20.08.2021



· Trade name: SU-8 2000 Series Resists

• Article number:

Y111004, Y111007, Y111014, Y111022, Y111029, Y111045, Y111053, Y111058, Y111064, Y111069, Y111070, Y111072, Y111074, Y111075, Y111077

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- Product category PC30 Photo-chemicals
- Application of the substance / the mixture Photoresist
- \cdot 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818
- Further information obtainable from: Product Safety Email: productsafety@kayakuAM.com • 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 *Chemtrec USA Emergency* : 800-424-9300 (24 hr) *Chemtrec International Emergency* : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

GHS	102 flame
Flam. Liq. 3	H226 Flammable liquid and vapour.
GHS	09 environment
\checkmark	
1	
Aquatic Chroni	c 2 H411 Toxic to aquatic life with long lasting effects.
Aquatic Chroni	
GHS GHS	07
GHS Skin Irrit. 2	07 H315 Causes skin irritation.
GHS Skin Irrit. 2 Eye Irrit. 2	07 H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.
GHS Skin Irrit. 2 Eye Irrit. 2 Skin Sens. 1 2.2 Label elem Labelling acco	07 H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

EU



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.08.2021

Version number 8

Revision: 20.08.2021

Trade name: SU-8 2000 Series Resists

Hazard pictogra	(Contd. of page 1)
nazara piciogra	uns
	NY.
<u>< 🕲 > < !</u>	
∇ V	
GHS02 GHS	507 GHS09
Signal word Wa	urning
Hazard stateme	
H226 Flammab	le liquid and vapour.
H315 Causes sk	
H319 Causes se	rious eye irritation.
	e an allergic skin reaction.
	quatic life with long lasting effects.
Precautionary s	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a positio comfortable for breathing.
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, a
	present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
<i>P337+P313</i>	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbo
	dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
2.3 Other hazar	
Results of PBT PBT : Not appli	and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:	Enorm regin	3-75%
	Epoxy resin ③ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	5-7570
CAS: 120-92-3 EINECS: 204-435-9 Index number: 606-025-00-9 Reg.nr.: 01-2119495595-21-0000	Cyclopentanone Flam. Liq. 3, H226; () Skin Irrit. 2, H315; Eye Irrit. 2, H319	15-96%



Printing date 20.08.2021

Version number 8

Revision: 20.08.2021

Trade name: SU-8 2000 Series Resists

	(C)	ontd. of page 2)
CAS: 108-32-7 EINECS: 203-572-1 Index number: 607-194-00-1	Propylene carbonate Skin Irrit. 2, H315; Eye Irrit. 2, H319	0.1-5.0%
CAS: 89452-37-9	Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11)- hexafluoroantimonate (1-) (1:2) Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	0.05-2.5%
CAS: 71449-78-0	Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)- hexafluoroantimonate(1-) (1:1) Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	0.25-2.5%
• Additional information: For the	e wording of the listed hazard phrases refer to section 16.	LJ

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- Alcohol resistant foam Fire-extinguishing powder Carbon dioxide
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation Keep away from ignition sources.
 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

[—] EU —



Printing date 20.08.2021

Version number 8

Revision: 20.08.2021

Trade name: SU-8 2000 Series Resists

(Contd. of page 3) Do not allow to enter sewers/ surface or ground water. - 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. **SECTION 7: Handling and storage** · 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols. · Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges. · 7.2 Conditions for safe storage, including any incompatibilities · Storage: • Requirements to be met by storerooms and containers: Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles. Store in a cool location. · Information about storage in one common storage facility: Do not store together with alkalis (caustic solutions). Do not store together with oxidising and acidic materials. • Further information about storage conditions: Store in cool, dry conditions in well sealed containers. Protect from heat and direct sunlight. Store receptacle in a well ventilated area. · 7.3 Specific end use(s) No further relevant information available. **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

(Contd. on page 5)

⁻ EU



Printing date 20.08.2021

Version number 8

Revision: 20.08.2021

Trade name: SU-8 2000 Series Resists

(Contd. of page 4)

• **Respiratory protection:** In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

- *The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR*
- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and ch	nemical properties
General Information	
Appearance: Form:	Liquid
Colour:	Clear to light yellow
Odour:	Sweetish
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	130 °C
Flash point:	30 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	430 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density:	See Table 1 Other Information below

- EU



Printing date 20.08.2021

Version number 8

Revision: 20.08.2021

Trade name: SU-8 2000 Series Resists

					(Contd. of pag
Relative density	Not determine	ed.			
Vapour density	Not determine	ed.			
Evaporation rate	Not determine	ed.			
Solubility in / Miscibility with					
water:	Not miscible o	or difficult to	o mix.		
Partition coefficient: n-octanol/water:	Not determined.				
Viscosity:					
Dynamic:	Not determine	ed.			
Kinematic:	Not determine	ed.			
9.2 Other information	Name	Number	Sp. Grav.	Vol.(%by wt.)	VOC (g/L)
-	SU-8 2000.1	Y111004	1.00	94-98	960
	SU-8 2000.2	Y111007	1.00	90-95	930
	SU-8 2000.5	Y111014	1.07	85-90	920
	SU-8 2001	Y111022	1.100	80-85	860
	SU-8 2002	Y111029	1.123	70-75	800
	SU-8 2005	Y111045	1.164	50-55	640
	SU-8 2007	Y111053	1.175	45-50	550
	SU-8 2010	Y111058	1.187	40-45	500
	SU-8 2015	Y111064	1.200	35-40	430
	SU-8 2025	Y111069	1.219	30-35	380
	SU-8 2035	Y111070	1.227	20-30	370
	SU-8 2050	Y111072	1.233	20-30	345
	SU-8 2075	Y111074	1.236	20-30	320
	SU-8 2100	Y111075	1.237	20-30	310
	SU-8 2150	Y111077	1.238	20-30	285

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

- Contact with incompatible materials.
- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:
- Carbon monoxide

Corrosive gases/vapours

Danger of forming toxic pyrolysis products.

Antimony oxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

EU -



Printing date 20.08.2021

Version number 8

Revision: 20.08.2021

Trade name: SU-8 2000 Series Resists

			(Contd. of page 6
· LD/LC50	values rele	vant for classification:	
Epoxy resi	n		
Oral	LD50	>2000 mg/kg (Rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50	>5 mg/L (Rat)	
120-92-3 (Cyclopenta	none	
Oral	LD50	1820 mg/kg (Rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	19.5 mg/l (Rat)	
108-32-7 I	Propylene o	carbonate	
Oral	LD50	>29000 mg/kg (Rat)	
Dermal	LD50	>20,000 mg/kg (rabbit)	
Primary ir Skin corro Causes ski	sion/irritat n irritation	tion .	
Serious ey Causes ser	0		
Respirator May cause Additional	y or skin s an allergi toxicologi	ensitisation c skin reaction. cal information:	
CMR effect Germ cell Carcinoge Reproduct STOT-sing	ets (carcino mutagenic nicity Base ive toxicity gle exposui	<i>sygenity, mutagenicity and toxicity for reproduction)</i> <i>ity</i> Based on available data, the classification criteria are not met. and on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. <i>re</i> Based on available data, the classification criteria are not met. <i>sure</i> Based on available data, the classification criteria are not met.	

SECTION 12: Ecological information

· 12.1 Toxicity

Epoxy resin	$50 \le 1000 \text{ mg/l} (algae)$
	$\leq 1000 \text{ mg/l (fish)}$
	$\leq 1000 \text{ mg/l} (invertebrates)$
89452-37-9 Sul	fonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11)-hexafluoroantimonate (1-) (1:2)
LC50/24 h	4.4 mg/l (daphnia)
LC50/48 hr	0.68 mg/L (daphnia)
71449-78-0 Sul	fonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)
LC50/24 h	4.4 mg/l (daphnia)
LC50/48 hr	0.68 mg/L (daphnia)
12.2 Persistence	e and degradability No further relevant information available.
	ulative potential No further relevant information available.
	soil No further relevant information available.

(Contd. on page 8)

⁻ EU -

ADVANCED MATERIALS

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.08.2021

Version number 8

Revision: 20.08.2021

Trade name: SU-8 2000 Series Resists

(Contd. of page 7)

- Ecotoxical effects:
- *Remark: Toxic for fish* • *Additional ecological information:*
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

• Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

- 14.1 UN-Number - ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name ADR, IATA IMDG	RESIN SOLUTION RESIN SOLUTION (Sulfonium, diphenyl[4-(phenylthic phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1) Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11) hexafluoroantimonate (1-) (1:2)), MARINE POLLUTANT
· 14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
ADR, IMDG, IATA	3 Flammable liquids.
ADR, IMDG, IATA	3 Flammable liquids. 3
ADR, IMDG, IATA	1
ADR, IMDG, IATA	3



Printing date 20.08.2021

Version number 8

Revision: 20.08.2021

Trade name: SU-8 2000 Series Resists

	(Contd. of page
EMS Number:	F-E,S-D
Stowage Category	A
14.7 Transport in bulk according to Ar	nnex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: El
· · · · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: E1
· · ~	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN ''Model Regulation'':	UN1866, RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Directive 2012/18/EU

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- · Classification according to Regulation (EC) No 1272/2008
- Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

· Department issuing SDS: Product safety department

- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- Revision History:
- The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

(Contd. on page 10) EU ADVANCED MATERIALS

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.08.2021

Version number 8

Revision: 20.08.2021

Trade name: SU-8 2000 Series Resists

(Contd. of page 9) • Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2