

Printing date 10.02.2022 Version number 4 Revision: 10.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SU-8 R 2000 Series Resists
- · Article number: Y110029, Y110058, Y110069, Y110072, Y110077
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials, Inc.

200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuAM.com
• 1.4 Emergency telephone number:

· **1.4 Emergency telepnone number:** Kayaku Advanced Materials: 617-965-5511

Kayaku Advanced Materials <u>: 617-965-5511</u> Chemtrec USA Emergency <u>: 800-424-9300 (24 hr)</u>

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

· Signal word Warning

(Contd. on page 2)



Printing date 10.02.2022 Version number 4 Revision: 10.02.2022

Trade name: SU-8 R 2000 Series Resists

(Contd. of page 1)

· Hazard-determining components of labelling:

Epoxy resin

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H317 May cause an allergic skin reaction.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

moking.

Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	Epoxy resin	25-75%
	🗘 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 120-92-3	Cyclopentanone	23-78%
EINECS: 204-435-9	♦ Flam. Liq. 3, H226; ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	
Index number: 606-025-00-9		
Reg.nr.: 01-2119495595-21-0000		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Printing date 10.02.2022 Version number 4 Revision: 10.02.2022

Trade name: SU-8 R 2000 Series Resists

(Contd. of page 2)

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

· 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

(Contd. on page 4)



Printing date 10.02.2022 Version number 4 Revision: 10.02.2022

Trade name: SU-8 R 2000 Series Resists

(Contd. of page 3)

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers: Store in a cool location.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Do not store together with amines.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)




Printing date 10.02.2022 Version number 4 Revision: 10.02.2022

Trade name: SU-8 R 2000 Series Resists

(Contd. of page 4)

· Eye protection:



9.1 Information on basic physical and c	hemical properties
General Information	
Appearance:	Limid
Form: Colour:	Liquid Clear to light yellow
Odour:	Slightly sweet
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 130 °C
Flash point:	30 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	430 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density:	Not determined.
	Not determined
Relative density	See Table 1 Other Information
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	No. 1 de la constante de la co
water:	Not miscible or difficult to mix.
	Not determined.
Partition coefficient: n-octanol/water:	Not determined.



Printing date 10.02.2022 Version number 4 Revision: 10.02.2022

Trade name: SU-8 R 2000 Series Resists

					(Contd. of pag
Kinematic:	Not determine	ed.			
· 9.2 Other information	Name	Number	Sp. Grav.	Vol.(%by wt.)	VOC (g/L)
	SU-8 R 2002	Y110029	1.150	70-75	720
	SU-8 R 2010	Y110058	1.200	40-45	500
	SU-8 R 2025	Y110069	1.219	30-35	380
	SU-8 R 2050	Y110072	1.233	20-30	330
	SU-8 R 2150	Y110077	1.238	20-30	300

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- · 10.4 Conditions to avoid

Contact with incompatible materials.

Heat, flames and sparks. Extremes of temperature and direct sunlight.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification: Epoxy resin			
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative LC50 5 mg/L (Rat)		5 mg/L (Rat)	
120-92-3 (120-92-3 Cyclopentanone		
Oral	LD50	1180 mg/kg (Rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>19.5 mg/l (Rat)	

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 10.02.2022 Version number 4 Revision: 10.02.2022

Trade name: SU-8 R 2000 Series Resists

(Contd. of page 6)

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity	· Aquatic toxicity:		
Epoxy resin	Epoxy resin		
100 <lc ec="" ic<="" th=""><th> 50 \(\le 1000 \text{ mg/l (algae)} \)</th></lc>	50 \(\le 1000 \text{ mg/l (algae)} \)		
	$\leq 1000 \text{ mg/l (fish)}$		
	≤1000 mg/l (invertebrates)		
120-92-3 Cyclo	120-92-3 Cyclopentanone		
EC50/48 h	100 mg/l (daphnia magna)		
EC50/72 h	>100 mg/l (scenedesmus subspicatus)		
LC50/96 h	>100 mg/l (fish)		

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Tr	ansport information
1 / 1 IIN North on	

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1866
- · 14.2 UN proper shipping name
- · ADR 1866 RESIN SOLUTION

(Contd. on page 8)



Printing date 10.02.2022 Version number 4 Revision: 10.02.2022

Trade name: SU-8 R 2000 Series Resists

	(Contd. of pa
· IMDG, IATA	RESIN SOLUTION
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
· EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
· 14.7 Transport in bulk according to Annex II o	of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· <i>ADR</i>	
· Limited quantities (LQ)	5L
· Transport category	3
Tunnel restriction code	D/E
· UN ''Model Regulation'':	UN1866, RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Directive 2012/18/EU
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

(Contd. on page 9)



Printing date 10.02.2022 Version number 4 Revision: 10.02.2022

Trade name: SU-8 R 2000 Series Resists

(Contd. of page 8)

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

EU-