

Printing date 02/24/2021

1 Identification

· Product identifier

- · Trade name: SU-8 TF 6000 Series Resists
- **Product number:** Y143015, Y143027, Y143037, Y143051, Y143061 • **Application of the substance / the mixture** Photoresist
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Kayaku Advanced Materials, Inc.
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
- Fax: (617) 965-5818
- Information department: Product Safety Email: productsafety@kayakuAM.com • Emergency telephone number: Kayaku Advanced Materials : 617-965-5511
- Chemtrec USA Emergency : 800-424-9300 Chemtrec International Emergency : 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.

GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.

GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



Reviewed on 02/24/2021

(Contd. on page 2)

<u>--</u>US



Printing date 02/24/2021

Reviewed on 02/24/2021

	(Contd. of pag
• Signal word Da	inger
· Hazard-determ	ining components of labeling:
Proprietary Epo	oxy Resin
Cyclopentanone	
gamma-Butyrol	actone
• Hazard stateme	
	le liquid and vapor.
H332 Harmful i	
H315 Causes sk	
	prious eye damage.
	e an allergic skin reaction.
	e drowsiness or dizziness.
· Precautionary s	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable breathing.
P305+P351+P.	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if pres
D111 D111	and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 P370+P378	If eye irritation persists: Get medical advice/attention.
	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Car dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internatio regulations.
· Classification s	
· NFPA ratings ((scale 0 - 4)
H	Iealth = 3
\sim	Fire = 3
3 0 R	eactivity = 0
• HMIS-ratings (scale 0 - 4)
HEALTH *3	Health = *3
	Fire = 3
REACTIVITY 0	Reactivity = 0

• **vPvB:** Not applicable.

3 Composition/information on ingredients

• Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

⁻ US



Printing date 02/24/2021

Reviewed on 02/24/2021

Trade name: SU-8 TF 6000 Series Resists

	(Contd. of page .
· Dangerous components:	
120-92-3 Cyclopentanone	25-50%
🐼 Flam. Liq. 3, H226; 🗘 Skin Irrit. 2, H315; Eye Irrit. 2A, H3	19
108-65-6 1-Methoxy-2-propanol acetate	25-50%
🐼 Flam. Liq. 3, H226; 🗘 STOT SE 3, H336	
Epoxy resin	10-25%
🐼 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	
96-48-0 gamma-Butyrolactone	5-15%
📀 Eye Dam. 1, H318; 🚸 Acute Tox. 4, H302; STOT SE 3, H33	36
· Additional Components:	
Proprietary Photoacid Initiator	<1%
Aquatic Chronic 2, H411; 🕐 Acute Tox. 4, H302; Acute Tox. 4, H332	

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

· Extinguishing media

Suitable extinguishing agents: Alcohol resistant foam Fire-extinguishing powder Carbon dioxide

• For safety reasons unsuitable extinguishing agents: Water with full jet

Water

 \cdot Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

• Advice for firefighters

• **Protective equipment:** Wear SCBA.

(Contd. on page 4)



Printing date 02/24/2021

Reviewed on 02/24/2021

Trade name: SU-8 TF 6000 Series Resists

(Contd. of page 3)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources • Environmental precautions: Do not allow to enter sewers/ surface or ground water. Do not allow product to reach sewage system or any drains. Inform respective authorities in case of seepage into water course or sewage system. • Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- Precautions for safe handling
 Ensure good ventilation/exhaust at the workplace.
 Prevent formation of aerosols.
 Keep receptacles tightly sealed.
 Information about protection against explosions and fires:
- Keep ignition about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Use explosion-proof apparatus / fittings and spark-proof tools.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and containers: Store in a cool location.
- *Information about storage in one common storage facility:* Do not store together with oxidizing and acidic materials. Do not store together with amines.
- Further information about storage conditions: Keep container well-sealed in cool, dry location. Store receptacle in a well ventilated area. Protect from heat and direct sunlight.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

(Contd. on page 5)

⁻ ÚS



Printing date 02/24/2021

Reviewed on 02/24/2021

Trade name: SU-8 TF 6000 Series Resists

	(Contd. of page 4
At this time, the other constituents have no known exposure limits.	
108-65-6 1-Methoxy-2-propanol acetate	
WEEL Long-term value: 50 ppm	
Additional information: The lists that were valid during the creation were used as basis.	
Exposure controls	
Personal protective equipment:	
General protective and hygienic measures:	
Keep away from food and beverages.	
Immediately remove all soiled and contaminated clothing.	
Wash hands before breaks and at the end of work.	
Avoid contact with the eyes and skin.	
Respiratory equipment:	C CD (
In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, us	e SCBA.
Protection of hands:	
Protective gloves	
The glove material has to be impermeable and resistant to the product/ the substance/ the pre-	eparation.
Material of gloves Nitrile rubber, NBR	
Penetration time of glove material Contact glove manufacture for break-through time.	
Eye protection:	
Tightly sealed goggles	

Information on basic physical and	chemical properties	
· General Information		
Appearance:		
Form:	Liquid	
Color:	Clear to light yellow	
· Odor:	Sweet	
• Odor threshold:	Not determined.	
pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	130 °C (266 °F)	
Flash point:	30 °C (86 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	315 °C (599 °F)	
Decomposition temperature:	Not determined.	



Printing date 02/24/2021

Reviewed on 02/24/2021

Trade name: SU-8 TF 6000 Series Resists

	(Contd. of page :
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.3 Vol %
Upper:	10.8 Vol %
· Vapor pressure at 20 •C (68 •F):	11 hPa (8.3 mm Hg)
Density:	See other information
Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Partly miscible.
· Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Solids content:	10-70 %
• Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Exothermic polymerization.
- Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.
- · Incompatible materials: Strong Oxidizing Agents, Strong Bases, Strong Acids, Amines
- Hazardous decomposition products: Carbon monoxide and carbon dioxide Danger of toxic pyrolysis products. Corrosive gases/vapors

corrostre guses, rupors

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.

(Contd. on page 7)



Printing date 02/24/2021

Reviewed on 02/24/2021

Trade name: SU-8 TF 6000 Series Resists

(Contd. of page 6)

3

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

96-48-0 gamma-Butyrolactone

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

- Uncleaned packagings:
- Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

· UN-Number		
· DOT, ADR, IMDG, IATA	UN1866	
· UN proper shipping name		
$\cdot DOT, ADR$	Resin solution	
· IMDG, IATA	RESIN SOLUTION	



Printing date 02/24/2021

Reviewed on 02/24/2021

Trade name: SU-8 TF 6000 Series Resists

	(Contd. of page
· Transport hazard class(es)	
·DOT	
R AMAGER E LINGUS	
▼	
· Class	3 Flammable liquids
·Label	3
· ADR, IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
• Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
• Hazard identification number (Kemler code)	
• EMS Number:	<i>F-E,<u>S-E</u></i>
• Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN1866, Resin solution, 3, III
or now nogument	

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

• Section 355 (extremely hazardous substances):

None of the ingredients are listed.

• Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• **TSCA** (**Toxic Substances Control Act**): All ingredients are listed or comply with TSCA regulations. • **Proposition 65**

• Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

(Contd. on page 9)

US –

(Contd. of page 8)



Safety Data Sheet acc. to OSHA HCS

Printing date 02/24/2021

Reviewed on 02/24/2021

Trade name: SU-8 TF 6000 Series Resists

• Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

• TLV (Threshold Limit Value)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

120-92-3 Cyclopentanone

· New Jersey State Right To Know List

120-92-3 Cyclopentanone

· Pennsylvania Hazardous Substances List

120-92-3 Cyclopentanone

· California SCAQMD Rule 443.1 VOC's: No information available.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determ	ining components of labeling:
Proprietary Epo	oxy Resin
Cyclopentanone	
gamma-Butyrol	actone
· Hazard stateme	nts
H226 Flammab	le liquid and vapor.
H332 Harmful	if inhaled.
H315 Causes sh	
H318 Causes se	rious eye damage.
	e an allergic skin reaction.
	e drowsiness or dizziness.
· Precautionary	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for
	breathing.
P305+P351+P	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.

• US

0



Safety Data Sheet acc. to OSHA HCS

Printing date 02/24/2021

Reviewed on 02/24/2021

(a 1 a

Trade name: SU-8 TF 6000 Series Resists

	(Contd. of page 9)
P337+P313	<i>If eye irritation persists: Get medical advice/attention.</i>
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Date of preparation / last revision 02/24/2021 / 3

• Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3