

Printing date 25.02.2021 Version number 4 Revision: 25.02.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: XP PriElex® SU-8 1.0

· Article number: J143032

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials, Inc.

200 Flanders Road

Westborough, MA 01581

Tel: (617) 965-5511 Fax: (617) 965-5818

The person responsible in EU Member State:

ONLY REPRESENTATIVE

Lionel Marcélis, PhD

President

REACH NATION SRL

22 Rue Notre Dame au Bois

1440 Braine-le-Château

**BELGIUM** 

*Tel*: +32491880259

\*Only Representative for 2-methoxy-1-methylethyl acetate (CAS 108-65-6) only. Other substances are being supported under REACH by Only Representatives of Non-European suppliers and others may be exempt from registration.

Further information obtainable from:

Product Safety

Email: productsafety@kayakuAM.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)



Printing date 25.02.2021 Version number 4 Revision: 25.02.2021

Trade name: XP PriElex® SU-8 1.0

(Contd. of page 1)



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

#### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS08

GHS02 GHS05 GHS07

· Signal word Danger

#### · Hazard-determining components of labelling:

Proprietary Epoxy Resin gamma-Butyrolactone

1-Methoxy-2-propanol acetate

#### · Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

*P280* Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.

*P370+P378* In case of fire: Use for extinction: Carbon dioxide.

(Contd. on page 3)



Printing date 25.02.2021 Version number 4 Revision: 25.02.2021

Trade name: XP PriElex® SU-8 1.0

(Contd. of page 2)

*P403+P233* Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 120-92-3 EINECS: 204-435-9 Index number: 606-025-00-9	Cyclopentanone Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2, H319	40-60%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	<i>1-Methoxy-2-propanol acetate</i> (Registration No.: 01-2119475791-29-0050) ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	25-50%
	Proprietary Epoxy Resin Sens. 1, H317; Aquatic Chronic 4, H413	10-25%
CAS: 96-48-0 EINECS: 202-509-5	gamma-Butyrolactone ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; STOT SE 3, H336	5-15%
	Proprietary Photoacid Initiator  Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H332	<1%

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.



Printing date 25.02.2021 Version number 4 Revision: 25.02.2021

Trade name: XP PriElex® SU-8 1.0

(Contd. of page 3)

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow to enter sewers/surface or ground water.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Keep receptacles tightly sealed.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

*Use explosion-proof apparatus / fittings and spark-proof tools.* 

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: Store in a cool location.
- · Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

(Contd. on page 5)



Printing date 25.02.2021 Version number 4 Revision: 25.02.2021

Trade name: XP PriElex® SU-8 1.0

(Contd. of page 4)

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:

#### 108-65-6 1-Methoxy-2-propanol acetate

IOELV Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

- EU



Printing date 25.02.2021 Version number 4 Revision: 25.02.2021

Trade name: XP PriElex® SU-8 1.0

(Contd. of page 5)

0.1 Information on Louis at a 1	1
9.1 Information on basic physical and c General Information	nemical properties
Appearance:	
Form:	Liquid
Colour:	Light yellow
Colour.	Clear, colorless to pale yellow
Odour:	Sweetish
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	∷ 130 °C
Flash point:	30 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	315 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
	mixiures are possible.
Explosion limits:	
Lower:	1.3 Vol %
Upper:	10.8 Vol %
Vapour pressure at 20 °C:	11 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Partly miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	37.5 %
Solids content:	19.9 %
9.2 Other information	No further relevant information available.



Printing date 25.02.2021 Version number 4 Revision: 25.02.2021

Trade name: XP PriElex® SU-8 1.0

(Contd. of page 6)

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Bases, Strong Acids, Amines
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Danger of forming toxic pyrolysis products.

Corrosive gases/vapours

#### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:				
Proprietar	Proprietary Epoxy Resin				
Oral	NOEL 28 day repeated dose	250 mg/kg/day (Rat)			
120-92-3 (	Cyclopentanone				
Oral	LD50	1820 mg/kg (Rat)			
Dermal	LD50	>2000 mg/kg (rabbit)			
Inhalative	LC50/4 h	19.5 mg/l (Rat)			
96-48-0 ga	mma-Butyrolactone				
Oral	LD50	1540 mg/kg (Rat)			
Dermal	LD50	5000 mg/kg (gui)			
Inhalative	LC50/4 h	>5.1 mg/l (Rat)			
108-65-6 1	-Methoxy-2-propanol acetate	2			
Oral	LD50	8532 mg/kg (Rat)			
Dermal	LD50	>5000 mg/kg (Rat)			
Inhalative	LC50/6 h	4345 ppm (Rat)			

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 25.02.2021 Version number 4 Revision: 25.02.2021

Trade name: XP PriElex® SU-8 1.0

(Contd. of page 7)

- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

· 12.1 Toxicity

	Толиц	
· Aqu	atic toxicity	):
Prop	prietary Epo	oxy Resin
LC5	0/96 h	>0.31 mg/l (algae)
		>0.31 mg/l (Water flea)
NOE	EC/96 h	$\geq 0.99 \text{ mg/l (algae)}$
120-	-92-3 Cyclo	pentanone
EC5	50/48 h	3600 mg/l (Ceriodaphnia dubia (water flea))
		100 mg/l (daphnia magna)
EC5	50/72 h	>100 mg/l (scenedesmus subspicatus)
LC5	50/48 hr	2950 mg/L (golden orfe)
LC5	50/96 h	>100 mg/l (fish)
108-	-65-6 1-Met	thoxy-2-propanol acetate
ErC.	50 96 hour	>1000 mg/l (Pseudokirchneriella subcapitata (algea))
LC5	50	408-500 mg/l (daphnia magna)
		100-180 mg/l (rainbow trout (Oncorhynchus mykiss))
96-4	18-0 gamma	a-Butyrolactone
EC5	50/17 h	>10000 mg/l (bacterium)
EC5	50/48 h	>500 mg/l (daphnia magna)
EC5	50/72 h	360 mg/l (green algae)
LC5	50/96 h	>220 - <460 mg/l (golden orfe)
ErC. LC5  96-4  EC5  EC5	150 96 hour 160 <b>18-0 gamma</b> 50/17 h 50/48 h 50/72 h	>1000 mg/l (Pseudokirchneriella subcapitata (algea)) 408-500 mg/l (daphnia magna) 100-180 mg/l (rainbow trout (Oncorhynchus mykiss)) <b>1-Butyrolactone</b> >10000 mg/l (bacterium) >500 mg/l (daphnia magna) 360 mg/l (green algae)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.



Printing date 25.02.2021 Version number 4 Revision: 25.02.2021

Trade name: XP PriElex® SU-8 1.0

(Contd. of page 8)

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name ADR, IMDG, IATA	RESIN SOLUTION
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
14.7 Transport in bulk according to Annex II o	pf
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
 ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, III



Printing date 25.02.2021 Version number 4 Revision: 25.02.2021

Trade name: XP PriElex® SU-8 1.0

(Contd. of page 9)

#### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008 GHS label elements
- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 11)





Printing date 25.02.2021 Version number 4 Revision: 25.02.2021

Trade name: XP PriElex® SU-8 1.0

(Contd. of page 10)

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4