

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: 50 PMMA Series Resists in Chlorobenzene

· Article number:

M540002, M540003, M540004, M540005, M540006, M540007, M540008, M540009, M540010, M540012

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment

· Application of the substance / the mixture Photoresist

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Kayaku Advanced Materials
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818

· Further information obtainable from:

Product Safety
 Email: productsafety@kayakuAM.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511
 Chemtrec USA Emergency : 800-424-9300 (24 hr)
 Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 1)

 · **2.2 Label elements**

 · **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

 · **Hazard pictograms**


GHS02 GHS07 GHS08 GHS09

 · **Signal word** *Danger*

 · **Hazard-determining components of labelling:**

Chlorobenzene

 · **Hazard statements**

H226 Flammable liquid and vapour.

H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

 · **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.

P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

 · **2.3 Other hazards**

 · **Results of PBT and vPvB assessment**

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

 · **3.2 Chemical characterisation: Mixtures**

 · **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.08.2019

Version number 6

Revision: 12.08.2019

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 2)

· Dangerous components:

CAS: 108-90-7 EINECS: 203-628-5 Index number: 602-033-00-1	Chlorobenzene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H336	75-100%
CAS: 25086-15-1	Poly(methyl methacrylate-co-methacrylic acid) ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-15%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures
· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing: Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media
· Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

· For safety reasons unsuitable extinguishing agents: Water with full jet

· 5.2 Special hazards arising from the substance or mixture No further relevant information available.

· 5.3 Advice for firefighters
· Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 3)

- **6.3 Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Ensure adequate ventilation.
 Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 Ensure good ventilation/exhaust at the workplace.
 Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Use explosion-proof apparatus / fittings and spark-proof tools.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:**
 Do not store together with alkalis (caustic solutions).
 Do not store together with oxidising and acidic materials.
- **Further information about storage conditions:**
 Store in cool, dry conditions in well sealed containers.
 Protect from heat and direct sunlight.
 Store receptacle in a well ventilated area.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

 · **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

108-90-7 Chlorobenzene

IOELV	Short-term value: 70 mg/m ³ , 15 ppm
	Long-term value: 23 mg/m ³ , 5 ppm

- **Additional information:** The lists valid during the making were used as basis.

 · **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from food and beverages.
 Wash hands before breaks and at the end of work.

- **Respiratory protection:**

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 4)

 · **Protection of hands:**


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

 · **Material of gloves** Nitrile rubber, NBR

 · **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

 · **Eye protection:**


Tightly sealed goggles

SECTION 9: Physical and chemical properties

 · **9.1 Information on basic physical and chemical properties**

 · **General Information**

 · **Appearance:**

Form:	Fluid
Colour:	Clear
Odour:	Mild
Odour threshold:	Not determined.

 · **pH-value:** Not determined.

 · **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	132 °C

 · **Flash point:** 28 °C

 · **Flammability (solid, gas):** Not applicable.

 · **Ignition temperature:** 590 °C

 · **Decomposition temperature:** Not determined.

 · **Auto-ignition temperature:** Product is not selfigniting.

 · **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

 · **Explosion limits:**

Lower:	1.3 Vol %
Upper:	11.0 Vol %

 · **Vapour pressure at 20 °C:** 12 hPa

Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.08.2019

Version number 6

Revision: 12.08.2019

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 5)

· Evaporation rate	Not determined.																																																							
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.																																																							
· Partition coefficient: n-octanol/water:	Not determined.																																																							
· Viscosity:																																																								
Dynamic:	Not determined.																																																							
Kinematic:	Not determined.																																																							
· 9.2 Other information	<table><tr><th>Name</th><th>Number</th><th>Sp. Grav.</th><th>Vol.(%by wt.)</th><th>VOC (g/L)</th></tr><tr><td>50C2</td><td>M540002</td><td>1.108</td><td>98</td><td>1085</td></tr><tr><td>50C3</td><td>M540003</td><td>1.109</td><td>97</td><td>1075</td></tr><tr><td>50C4</td><td>M540004</td><td>1.110</td><td>96</td><td>1065</td></tr><tr><td>50C5</td><td>M540005</td><td>1.111</td><td>95</td><td>1055</td></tr><tr><td>50C6</td><td>M540006</td><td>1.112</td><td>94</td><td>1045</td></tr><tr><td>50C7</td><td>M540007</td><td>1.113</td><td>93</td><td>1035</td></tr><tr><td>50C8</td><td>M540008</td><td>1.114</td><td>92</td><td>1025</td></tr><tr><td>50C9</td><td>M540009</td><td>1.115</td><td>91</td><td>1015</td></tr><tr><td>50C10</td><td>M540010</td><td>1.116</td><td>90</td><td>1005</td></tr><tr><td>50C12</td><td>M540012</td><td>1.117</td><td>88</td><td>985</td></tr></table>	Name	Number	Sp. Grav.	Vol.(%by wt.)	VOC (g/L)	50C2	M540002	1.108	98	1085	50C3	M540003	1.109	97	1075	50C4	M540004	1.110	96	1065	50C5	M540005	1.111	95	1055	50C6	M540006	1.112	94	1045	50C7	M540007	1.113	93	1035	50C8	M540008	1.114	92	1025	50C9	M540009	1.115	91	1015	50C10	M540010	1.116	90	1005	50C12	M540012	1.117	88	985
Name	Number	Sp. Grav.	Vol.(%by wt.)	VOC (g/L)																																																				
50C2	M540002	1.108	98	1085																																																				
50C3	M540003	1.109	97	1075																																																				
50C4	M540004	1.110	96	1065																																																				
50C5	M540005	1.111	95	1055																																																				
50C6	M540006	1.112	94	1045																																																				
50C7	M540007	1.113	93	1035																																																				
50C8	M540008	1.114	92	1025																																																				
50C9	M540009	1.115	91	1015																																																				
50C10	M540010	1.116	90	1005																																																				
50C12	M540012	1.117	88	985																																																				

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** Stable under normal use conditions
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid**
Heat, flames and sparks. Extremes of temperature and direct sunlight.
Contact with incompatible materials.
- **10.5 Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Hydrogen chloride (HCl)
Possible traces of Phosgene

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - **Acute toxicity**
Harmful if swallowed or if inhaled.
 - **LD/LC50 values relevant for classification:**
- | | |
|-------------------------------|-----------------------|
| 108-90-7 Chlorobenzene | |
| Oral | LD50 2290 mg/kg (Rat) |
- **Primary irritant effect:**
 - **Skin corrosion/irritation**
Causes skin irritation.
 - **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
 - **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 6)

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure**
Causes damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

 · **12.1 Toxicity**

 · **Aquatic toxicity:**
108-90-7 Chlorobenzene

EC50/24 h	4.30-16.00 mg/l (daphnia magna)
LC100/48 h	0.03-28 mg/l (golden orfe)
LC50/76 h	4.5-7.4 mg/l (Lepomis macrochirus (Bluegill))
EC50/96 hr	12.5 mg/l (algae)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxic effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made in accordance with International, National, and regional regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.


EU

(Contd. on page 8)

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 7)

SECTION 14: Transport information

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1866
· 14.2 UN proper shipping name	
· ADR, IMDG, IATA	RESIN SOLUTION
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	30
· EMS Number:	F-E,S-E
· Segregation groups	Liquid halogenated hydrocarbons
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Transport category	3
· Tunnel restriction code	D/E
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category
- E2 Hazardous to the Aquatic Environment
- P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

EU

(Contd. on page 9)

Trade name: 50 PMMA Series Resists in Chlorobenzene

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

· Department issuing SDS: Product safety department**· Contact: Tom Cole, EHS Manager (tcole@kayakuAM)****· Revision History:**

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2