

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** 950 PMMA Series Resists in Chlorobenzene
- **Article number:**
 950C1, 950C2, 950C3, 950C4, 950C4.5, 950C5, 950C6, 950C6.5, 950C7, 950C7.5, 950C8, 950C9, 950C10, 950C11, 950C12, 950C15
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use** SU16 Manufacture of computer, electronic and optical products, electrical equipment
- **Application of the substance / the mixture** Photoresist
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Kayaku Advanced Materials
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818
- **Further information obtainable from:**
 Product Safety
 Email: productsafety@kayakuAM.com
- **1.4 Emergency telephone number:**
 Kayaku Advanced Materials : 617-965-5511
 Chemtrec USA Emergency : 800-424-9300 (24 hr)
 Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
 Acute Tox. 4 H332 Harmful if inhaled.
 Skin Irrit. 2 H315 Causes skin irritation.
 STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 1)

· 2.2 Label elements
· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms


GHS02 GHS07 GHS08 GHS09

· Signal word Danger
· Hazard-determining components of labelling:

Chlorobenzene

· Hazard statements

- H226 Flammable liquid and vapour.
 H302+H332 Harmful if swallowed or if inhaled.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
 P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.
 P370+P378 In case of fire: Use for extinction: Carbon dioxide.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards
· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.08.2019

Version number 3

Revision: 14.08.2019

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 2)

· Dangerous components:

CAS: 108-90-7 EINECS: 203-628-5 Index number: 602-033-00-1	Chlorobenzene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H336	85-100%
--	---	---------

· Additional Components:

CAS: 9011-14-7 EC number: 618-466-4	Poly(methyl methacrylate)	1-15%
--	---------------------------	-------

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures
· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media
· Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents: Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

In case of fire, the following can be released:

Hydrogen chloride (HCl)

Phosgene gas

· 5.3 Advice for firefighters
· Protective equipment: Wear self-contained respiratory protective device.

EU

(Contd. on page 4)

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Use explosion-proof apparatus / fittings and spark-proof tools.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· **Requirements to be met by storerooms and containers:** No special requirements.

· **Information about storage in one common storage facility:**

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

108-90-7 Chlorobenzene

IOELV Short-term value: 70 mg/m³, 15 ppm

Long-term value: 23 mg/m³, 5 ppm

(Contd. on page 5)

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 4)

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from food and beverages.
 Wash hands before breaks and at the end of work.
- **Respiratory protection:**
 In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves** Nitrile rubber, NBR
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	132 °C
- **Flash point:** 28 °C
- **Flammability (solid, gas):** Not applicable.
- **Ignition temperature:** 590 °C
- **Decomposition temperature:** Not determined.
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.08.2019

Version number 3

Revision: 14.08.2019

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 5)

· Explosion limits:	
Lower:	1.3 Vol %
Upper:	11.0 Vol %
· Vapour pressure at 20 °C:	
12 hPa	
· Density:	
Not determined	
· Relative density	
See Table 1 Other Information	
· Vapour density	
Not determined.	
· Evaporation rate	
Not determined.	
· Solubility in / Miscibility with water:	
Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	
Not determined.	
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
· Solids content:	
6.0 %	
· 9.2 Other information	
Name Number Sp.Grav. Vol.(%by wt.) VOC (g/L)	
950C1 M240001 1.106 99 1095	
950C2 M240002 1.107 98 1085	
950C3 M240003 1.108 97 1075	
950C4 M240004 1.109 96 1065	
950C4.5 M240504 1.109 95.5 1060	
950C5 M240005 1.110 95 1055	
950C6 M240006 1.111 94 1045	
950C6.5 M240506 1.112 93.5 1040	
950C7 M240007 1.113 93 1035	
950C7.5 M240507 1.113 92.5 1030	
950C8 M240008 1.114 92 1025	
950C9 M240009 1.115 91 1015	
950C10 M240010 1.115 90 1005	
950C11 M240011 1.116 89 995	
950C12 M240012 1.117 88 985	
950C15 M240015 1.120 85 950	

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** Stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid**
Heat, flames and sparks. Extremes of temperature and direct sunlight.
Contact with incompatible materials.
- **10.5 Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide

(Contd. on page 7)

Trade name: 950 PMMA Series Resists in Chlorobenzene

Hydrogen chloride (HCl)
Possible traces of Phosgene

(Contd. of page 6)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed or if inhaled.

LD/LC50 values relevant for classification:

108-90-7 Chlorobenzene

Oral	LD50	1110 mg/kg (Rat)
Dermal	LD50	>7940 mg/kg (rabbit)
Inhalative	LC50	13.9 mg/L (Rat)

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Experience with humans: No further relevant information available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

108-90-7 Chlorobenzene

EC50/24 h	4.30-16.00 mg/l (daphnia magna)
EC50/96 hr	12.5 mg/l (algae)
LC100/48 h	0.03-28 mg/l (golden orfe)
LC50/76 h	4.5-7.4 mg/l (Lepomis macrochirus (Bluegill))

12.2 Persistence and degradability Expected to biodegrade

12.3 Bioaccumulative potential Not expected to bioaccumulate.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.08.2019

Version number 3

Revision: 14.08.2019

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 7)

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

 · **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods
· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made in accordance with International, National, and regional regulations.

· Uncleaned packaging:

 · **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

 · **ADR, IMDG, IATA**

UN1866

· 14.2 UN proper shipping name

 · **ADR, IATA**

RESIN SOLUTION

 · **IMDG**

 RESIN SOLUTION (CHLOROBENZENE), MARINE
 POLLUTANT

· 14.3 Transport hazard class(es)

 · **ADR, IMDG, IATA**

 · **Class**

3 Flammable liquids.

 · **Label**

3

· 14.4 Packing group

 · **ADR, IMDG, IATA**

III

· 14.5 Environmental hazards:

 Product contains environmentally hazardous substances:
 Chlorobenzene

 · **Marine pollutant:**

Yes

· 14.6 Special precautions for user

Warning: Flammable liquids.

 · **Danger code (Kemler):**

30

 · **EMS Number:**

F-E,S-D

 · **Segregation groups**

Liquid halogenated hydrocarbons

**· 14.7 Transport in bulk according to Annex II of
 Marpol and the IBC Code**

Not applicable.

(Contd. on page 9)

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 8)

· Transport/Additional information:
· ADR
· Limited quantities (LQ)

5L

· Transport category

3

· Tunnel restriction code

D/E

· UN "Model Regulation":

UN1866, RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

· Department issuing SDS: Product safety department
· Contact: Tom Cole, EHS Manager (tcole@kayakuAM)
· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

*Printing date 14.08.2019**Version number 3**Revision: 14.08.2019****Trade name: 950 PMMA Series Resists in Chlorobenzene****STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1**(Contd. of page 9)**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

EU