

Printing date 08/14/2019

Reviewed on 08/14/2019

- 1 Identification
- · Product identifier
- · Trade name: 950 PMMA Series Resists in Chlorobenzene
- *Product number:* 950C1, 950C2, 950C3, 950C4, 950C4.5, 950C5, 950C6, 950C6.5, 950C7, 950C7.5, 950C8, 950C9, 950C10, 950C11, 950C12, 950C15
- · Application of the substance / the mixture Photoresist
- Details of the supplier of the safety data sheet • Manufacturer/Supplier: Kayaku Advanced Materials
- 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818
- Information department: Product Safety Email: productsafety@kayakuAM.com
- Emergency telephone number: Kayaku Advanced Materials : <u>617-965-5511</u> Chemtrec USA Emergency : <u>800-424-9300</u> Chemtrec International Emergency : <u>703-527-3887</u>

2 Hazard(s) identification

	f the substance or mixture
GHS0	02 Flame
Flam. Liq. 3	H226 Flammable liquid and vapor.
GHS0	08 Health hazard
STOT RE 1	H372 Causes damage to organs through prolonged or repeated exposure.
GHS0	09 Environment
Aquatic Chronic	c 2 H411 Toxic to aquatic life with long lasting effects.
GHS	07
Acute Tox. 4	H302 Harmful if swallowed.
Acute Tox. 4	H332 Harmful if inhaled.
Skin Irrit. 2	H315 Causes skin irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.
 Label elements GHS label elem 	eents The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)



Reviewed on 08/14/2019

Trade name: 950 PMMA Series Resists in Chlorobenzene



Safety Data Sheet acc. to OSHA HCS



HEALTH1Health = 1FIRE3Fire = 3REACTIVITY0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment

• **PBT:** Not applicable.

(Contd. on page 3)

US -



Printing date 08/14/2019

Reviewed on 08/14/2019

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 2)

85-100%

1-15%

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

· Additional Components:

9011-14-7 Poly(methyl methacrylate)

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- Alcohol resistant foam Fire-extinguishing powder
- Carbon dioxide
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail. In case of fire, the following can be released:

- Hydrogen chloride (HCl)
- Phosgene gas

(Contd. on page 4)

US ·

(Contd. of page 3)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/14/2019

Reviewed on 08/14/2019

Trade name: 950 PMMA Series Resists in Chlorobenzene

- · Advice for firefighters
- · Protective equipment: Wear SCBA.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
Ensure adequate ventilation
Keep away from ignition sources
Wear protective equipment. Keep unprotected persons away.

Environmental precautions:
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Use explosion-proof apparatus / fittings and spark-proof tools. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions). Do not store together with oxidizing and acidic materials.

- Further information about storage conditions: Keep container well-sealed in cool, dry location.
- Protect from heat and direct sunlight.
- Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

us —



Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/14/2019

Trade name: 950 PMMA Series Resists in Chlorobenzene

Com	rol parameters ponents with limit values that require monitoring at the workplace:
	20-7 Chlorobenzene
	350 mg/m ³ , 75 ppm
	46 mg/m ³ , 10 ppm
0	edients with biological limit values: 00-7 Chlorobenzene
	100 mg/g creatinine Madium uning
	Medium: urine Time: and of shift at and of workwork
	Time: end of shift at end of workweek
	Parameter: 4-Chlorocatechol with hydrolysis (nonspecific)
	20 mg/g creatinine
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: p-Chlorophenol with hydrolysis (nonspecific)
	iratory equipment:
	se of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. Section of hands: Protective gloves
Proto The a Mate	se of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. ection of hands:
Proto The a Mate	se of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. action of hands: Protective gloves glove material has to be impermeable and resistant to the product/ the substance/ the preparation. rial of gloves Nitrile rubber, NBR tration time of glove material Contact glove manufacture for break-through time.

- · General Information
- · Appearance:
- Form:
- Color:
- · Odor:
- Odor threshold:

Fluid Clear to light yellow Etheral Not determined.

(Contd. on page 6)



Reviewed on 08/14/2019

Trade name: 950 PMMA Series Resists in Chlorobenzene

	(Contd. of page
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	132 °C (269.6 °F)
· Flash point:	28 °C (82.4 °F)
Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	590 °C (1,094 °F)
• Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo
	mixtures are possible.
· Explosion limits:	
Lower:	1.3 Vol %
Upper:	11.0 Vol %
• Vapor pressure at 20 •C (68 •F):	12 hPa (9 mm Hg)
· Density:	Not determined.
· Relative density	See Table 1 Other Information
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Water miscible No
Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
	(Contd. on page

Safety Data Sheet acc. to OSHA HCS



Printing date 08/14/2019

Reviewed on 08/14/2019

Trade name: 950 PMMA Series Resists in Chlorobenzene

		(Contd. of page
Solids content:	6.0 %	
Other information	Table 1. Product specific gravity and VOC data.	
	Name Number Sp.Grav. Vol.(%by wt.) VOC (g	/L)
	950C1 M240001 1.106 99 1095	
	950C2 M240002 1.107 98 1085	
	950C3 M240003 1.108 97 1075	
	950C4 M240004 1.109 96 1065	
	950C4.5 M240504 1.109 95.5 1060	
	950C5 M240005 1.110 95 1055	
	950C6 M240006 1.111 94 1045	
	950C6.5 M240506 1.112 93.5 1040	
	950C7 M240007 1.113 93 1035	
	950C7.5 M240507 1.113 92.5 1030	
	950C8 M240008 1.114 92 1025	
	950C9 M240009 1.115 91 1015	
	950C10 M240010 1.115 90 1005	
	950C11 M240011 1.116 89 995	
	950C12 M240012 1.117 88 985	
	950C15 M240015 1.120 85 950	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- *Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.*
- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- Hazardous decomposition products:
- Carbon monoxide and carbon dioxide
- Hydrogen chloride (HCl)
- Possible traces of Phosgene

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

108-90-7 Chlorobenzene

Oral LD50 1110 mg/kg (Rat)

Dermal LD50 >7940 mg/kg (rabbit)

Inhalative LC50 13.9 mg/L (Rat)

- · Primary irritant effect:
- on the skin: No irritant effect.
- \cdot on the eye: No irritating effect.

(Contd. on page 8)

[–] US



Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/14/2019

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 7)

3

- Sensitization: No sensitizing effects known.
- Experience with humans: No further relevant information available.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

9011-14-7 Poly(methyl methacrylate)

 \cdot NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

• Aquatic toxicity:

108-90-7 Chlorobenzene

EC50/24 h 4.30-16.00 mg/l (daphnia magna)

EC50/96 hr 12.5 mg/l (algae)

LC100/48 h 0.03-28 *mg/l* (golden orfe)

LC50/76 h 4.5-7.4 mg/l (Lepomis macrochirus (Bluegill))

• Persistence and degradability Expected to biodegrade

· Behavior in environmental systems:

- Bioaccumulative potential Not expected to bioaccumulate.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:

· Remark: Toxic for fish

- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- Also poisonous for fish and plankton in water bodies.
- Toxic for aquatic organisms
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.

• **vPvB:** Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.

(Contd. on page 9)

(Contd. of page 8)

EXAMPLA KU Advanced materials Printing date 08/14/2019

Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/14/2019

Trade name: 950 PMMA Series Resists in Chlorobenzene

· Uncleaned packagings:

• Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

UN-Number	
DOT, ADR, IMDG, IATA	UN1866
UN proper shipping name	
DOT, ADR	Resin solution
IMDG	RESIN SOLUTION (CHLOROBENZENE), MARINE POLLUTANT
IATA	RESIN SOLUTION
Transport hazard class(es)	
DOT	
2	
Class	3 Flammable liquids
Label	3
Class	3 Flammable liquids
Label	3
Packing group	
DOT, ADR, IMDG, IATA	111
Environmental hazards:	Product contains environmentally hazardous substance.
	Chlorobenzene
Marine pollutant:	Yes
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	30
EMS Number:	F-E,S-D
Segregation groups	Liquid halogenated hydrocarbons
	f
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 10)



Printing date 08/14/2019

Reviewed on 08/14/2019

Trade name: 950 PMMA Series Resists in Chlorobenzene

(Contd. of page 9)

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

 \cdot Section 355 (extremely hazardous substances):

None of the ingredients are listed.

• Section 313 (Specific toxic chemical listings):

108-90-7 Chlorobenzene

• TSCA (Toxic Substances Control Act):

One or more of the components of this formulation is (are) not in compliance with TSCA. All ingredients are listed or comply with TSCA regulations.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

108-90-7 Chlorobenzene

• TLV (Threshold Limit Value established by ACGIH)

108-90-7 Chlorobenzene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

108-90-7 Chlorobenzene

· New Jersey State Right To Know List

108-90-7 Chlorobenzene

· Pennsylvania Hazardous Substances List

108-90-7 Chlorobenzene

· California SCAQMD Rule 443.1 VOC's: See Table 1 - Section 9

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• Hazard-determining components of labeling: Chlorobenzene D

A3



Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/14/2019

Trade name: 950 PMMA Series Resists in Chlorobenzene

	(Contd. of page 10)
• Hazard sta	itements
H226	Flammable liquid and vapor.
H302+H3.	32 Harmful if swallowed or if inhaled.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
· Precaution	nary statements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P31	0 If swallowed: Immediately call a poison center/doctor.
P302+P35	<i>If on skin: Wash with plenty of soap and water.</i>
P304+P34	0 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P35	1+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P333+P31	<i>3 If skin irritation or rash occurs: Get medical advice/attention.</i>
P337+P31	<i>3 If eye irritation persists: Get medical advice/attention.</i>
P370+P37	In case of fire: Use for extinction: Alcohol resistant foam.
P370+P37	8 In case of fire: Use for extinction: Fire-extinguishing powder.
P370+P37	In case of fire: Use for extinction: Carbon dioxide.
P403+P23	5 Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
. Chamical	safety assessment: A Chamical Safety Assessment has not been carried out

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM)

· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

· Date of preparation / last revision 08/14/2019 / 2

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- DOT: US Department of Transportation IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 12)

LD50: Lethal dose, 50 percent



Reviewed on 08/14/2019

(Contd. of page 11)

Trade name: 950 PMMA Series Resists in Chlorobenzene

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Safety Data Sheet acc. to OSHA HCS