

Printing date 16.08.2019

Version number 2

Revision: 16.08.2019

	entifier
Trade name: 1	
Article numbe CAS Number:	r: M010100
97-64-3 <b>EC number:</b> 202-598-0	
<i>Index number</i> 607-129-00-7	
Sector of Use	lentified uses of the substance or mixture and uses advised against SU16 Manufacture of computer, electronic and optical products, electrical equipment the substance / the mixture Thinner, Diluent
	he supplier of the safety data sheet
Manufacturer Kayaku Advan	
200 Flanders	Road
Westborough, Tel: (617) 965	
Fax: (617) 905	
. ,	nation obtainable from:
Product Safety	
	rtsafety@kayakuAM.com v <b>telephone number:</b>
	ced Materials : 617-965-5511
Chemtrec USA	Emergency : 800-424-9300 (24 hr)
Chemtrec Inter	national Emergency <u>: 703-527-3887 (24 hr)</u>
SECTION 2	e: Hazards identification
52011011	
	on of the substance or mixture
2.1 Classificat	ion of the substance or mixture according to Regulation (EC) No 1272/2008
2.1 Classificat Classification	according to Regulation (EC) No 1272/2008
2.1 Classificat Classification	
2.1 Classificat Classification	according to Regulation (EC) No 1272/2008
2.1 Classificat Classification	according to Regulation (EC) No 1272/2008
2.1 Classificat Classification GH: Flam. Liq. 3 F	according to Regulation (EC) No 1272/2008 502 flame 1226 Flammable liquid and vapour.
2.1 Classificat Classification GH: Flam. Liq. 3 F	according to Regulation (EC) No 1272/2008
2.1 Classificat Classification GH: Flam. Liq. 3 H	according to Regulation (EC) No 1272/2008 502 flame 1226 Flammable liquid and vapour. 505 corrosion
2.1 Classificat Classification GH: Flam. Liq. 3 F	according to Regulation (EC) No 1272/2008 502 flame 1226 Flammable liquid and vapour. 505 corrosion
2.1 Classificat Classification GH: Flam. Liq. 3 H	according to Regulation (EC) No 1272/2008 502 flame 1226 Flammable liquid and vapour. 505 corrosion 1318 Causes serious eye damage.
2.1 Classificat Classification GHS Flam. Liq. 3 H Eye Dam. 1 H	according to Regulation (EC) No 1272/2008 502 flame 1226 Flammable liquid and vapour. 505 corrosion 1318 Causes serious eye damage. 507
2.1 Classificat Classification GH: Flam. Liq. 3 H Eye Dam. 1 H Composition GH: Skin Irrit. 2 H	according to Regulation (EC) No 1272/2008 502 flame 1226 Flammable liquid and vapour. 505 corrosion 1318 Causes serious eye damage. 507

EU -



Printing date 16.08.2019

Version number 2

Revision: 16.08.2019

Trade name: ELThinner

	GHS05 GHS07
C'	Danger
Signal word	Dunger
Hazard-dete	rmining components of labelling:
Ethyl lactate	
Hazard state	ments
	Flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
Н335-Н336	May cause respiratory irritation. May cause drowsiness or dizziness.
Precautional	ry statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. <i>S</i> smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a positi comfortable for breathing.
P305+P351-	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
<i>P337+P313</i>	If eye irritation persists: Get medical advice/attention.
<i>P370+P378</i>	In case of fire: Use for extinction: Alcohol resistant foam.
<i>P370+P378</i>	In case of fire: Use for extinction: Fire-extinguishing powder.
<i>P370+P378</i>	In case of fire: Use for extinction: Carbon dioxide.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internation regulations.
2.3 Other ha	
	BT and vPvB assessment
<b>PBT:</b> Not ap	

## SECTION 3: Composition/information on ingredients

- · 3.1 Chemical characterisation: Substances
- · CAS No. Description
- 97-64-3 ethyl lactate
- Identification number(s)
- EC number: 202-598-0
- Index number: 607-129-00-7

(Contd. on page 3)

EU



Version number 2

Revision: 16.08.2019

Trade name: ELThinner

Printing date 16.08.2019

(Contd. of page 2)

#### **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing: If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- Alcohol resistant foam Fire-extinguishing powder Carbon dioxide
- For safety reasons unsuitable extinguishing agents: Water with full jet

Water

- 5.2 Special hazards arising from the substance or mixture Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

#### **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources.
  6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
  6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- Dispose contaminated material as waste according to item 13.
- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 4)



Version number 2

Revision: 16.08.2019

Trade name: ELThinner

(Contd. of page 3)

### SECTION 7: Handling and storage · 7.1 Precautions for safe handling Keep receptacles tightly sealed. Ensure good ventilation/exhaust at the workplace. Keep away from heat and direct sunlight. · Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges. · 7.2 Conditions for safe storage, including any incompatibilities · Storage: • Requirements to be met by storerooms and containers: No special requirements. Store in a cool location. · Information about storage in one common storage facility: Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions). · Further information about storage conditions: Keep container tightly sealed. Protect from heat and direct sunlight. Store receptacle in a well ventilated area. Store under lock and key and with access restricted to technical experts or their assistants only. · 7.3 Specific end use(s) No further relevant information available. SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

- · Ingredients with limit values that require monitoring at the workplace: Not required.
- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes. • **Respiratory protection:**

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves Butyl rubber, BR

(Contd. on page 5)

<sup>· 8.1</sup> Control parameters

<sup>-</sup> *F*U



Version number 2

Revision: 16.08.2019

(Contd. of page 4)

#### Trade name: ELThinner

Printing date 16.08.2019

Nitrile rubber, NBR

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Tightly sealed goggles

	chemical properties	
General Information		
Appearance:		
Form:	Liquid	
Colour:	Colourless	
Odour:	Fruit-like	
Odour threshold:	Not determined.	
pH-value at 20 °C:	4	
Change in condition		
Melting point/freezing point:	-25 °C	
Initial boiling point and boiling range	e: 154 °C	
Flash point:	46 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	400 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Not determined.	
Explosive properties:	Not determined.	
Explosion limits:		
Lower:	1 Vol %	
Upper:	17 Vol %	
Vapour pressure at 20 °C:	2 hPa	
Density at 20 °C:	1.03 g/cm <sup>3</sup>	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	< 1	
Solubility in / Miscibility with		
water:	Fully miscible.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic: Organic solvents:	Not determined. 100.0 %	

- EU -



Version number 2

Revision: 16.08.2019

(Contd. of page 5)

Trade name: ELThinner

Printing date 16.08.2019

• 9.2 Other information

No further relevant information available.

### SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability Stable

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct sunlight.

• 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases

• 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

#### SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

#### 97-64-3 Ethyl lactate

Oral	LD50	8200 mg/kg (Rat)
Dermal	LD50	5000 mg/kg (rabbit)
Inhalative	LC50 8 hr	5.4 mg/l (Rat)

· Primary irritant effect:

- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

#### SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

97-64-3 Ethyl lactate

LC50/96 h 320 mg/l (zebra fish)

• 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)

EU -



Version number 2

Revision: 16.08.2019

(Contd. of page 6)

Trade name: ELThinner

Printing date 16.08.2019

• Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

- **vPvB:** Not applicable.
- $\cdot$  12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	tion	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1192	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1192 ETHYL LACTATE ETHYL LACTATE	
· 14.3 Transport hazard class(es)		
· ADR, IMDG, IATA		
· Class · Label	3 Flammable liquids. 3	
· 14.4 Packing group · ADR, IMDG, IATA	III	
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No	
<ul> <li>14.6 Special precautions for user</li> <li>Danger code (Kemler):</li> <li>EMS Number:</li> </ul>	Warning: Flammable liquids. 30 F-E,S-D	
· 14.7 Transport in bulk according to Ann Marpol and the IBC Code	<b>ex II of</b> Not applicable.	
· Transport/Additional information:		
· ADR · Limited quantities (LQ)	5L	
		(Contd. on page



Printing date 16.08.2019

Version number 2

Revision: 16.08.2019

Trade name: ELThinner

	(Contd. of page 7)
· Transport category	3
• Tunnel restriction code	D/E
· UN "Model Regulation":	UN1192 ETHYLLACTATE 3 III

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Classification according to Regulation (EC) No 1272/2008 Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.
- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM)

## • **Revision History:** The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3
- Skin Irrit. 2: Skin corrosion/irritation Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3