

## 1 Identification of the substance/mixture and of the company

· **Product identifier**

- **Trade name:** *UV-2531 UV Curable Glossy Dielectric - Blue, Clear, or Green*
- **Application of the substance / the mixture** *Functional Electronic Insulating Ink*

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Applied Ink Solutions  
17 Hampshire Drive, Unit 8  
Hudson, NH 03051  
USA

· **Information department:**

Product Safety  
Email: [sales@appliedinksolutions.com](mailto:sales@appliedinksolutions.com)

· **Emergency telephone number:**

Chemtrec USA Emergency : 800-424-9300  
Chemtrec International Emergency : 703-527-3887  
Applied Ink Solutions : 603-595-6221

## 2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS08 Health hazard

Muta. 1B                      H340                      May cause genetic defects.  
Carc. 1B                      H350                      May cause cancer.



GHS09 Environment

Aquatic Chronic 2 H411                      Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2                      H315                      Causes skin irritation.  
Eye Irrit. 2A                      H319                      Causes serious eye irritation.  
Skin Sens. 1                      H317                      May cause an allergic skin reaction.  
STOT SE 3                      H335-H336                      May cause respiratory irritation. May cause drowsiness or dizziness.  
Aquatic Acute 2                      H401                      Toxic to aquatic life.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07



GHS08



GHS09

Printing date 11/30/2016

Reviewed on 11/30/2016

**Trade name: UV-2531 UV Curable Glossy Dielectric**

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*Urethane acrylate oligomer*  
*Dicyclopentenylloxyethyl acrylate*  
*Proprietary Defoamer*  
*Proprietary Dye*

· **Hazard statements**

*H315 Causes skin irritation.*  
*H319 Causes serious eye irritation.*  
*H317 May cause an allergic skin reaction.*  
*H340 May cause genetic defects.*  
*H350 May cause cancer.*  
*H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.*  
*H401 Toxic to aquatic life.*  
*H411 Toxic to aquatic life with long lasting effects.*

· **Precautionary statements**

*P261 Avoid breathing dust/fume/gas/mist/vapors/spray*  
*P280 Wear protective gloves/protective clothing/eye protection/face protection.*  
*P273 Avoid release to the environment.*  
*P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.*  
*P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*  
*P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.*  
*P333+P313 If skin irritation or rash occurs: Get medical advice/attention.*  
*P337+P313 If eye irritation persists: Get medical advice/attention.*  
*P302+P352 IF ON SKIN: Wash with plenty of soap and water.*  
*P403+P233 Store in a well-ventilated place. Keep container tightly closed.*  
*P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



*Health = 1*  
*Fire = 1*  
*Reactivity = 0*

· **HMIS-ratings (scale 0 - 4)**



*Health = \*1*  
*Fire = 1*  
*Reactivity = 0*

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*

· **vPvB:** *Not applicable.*

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** *Mixture of the substances listed below with nonhazardous additions.*

(Contd. on page 3)

**Trade name: UV-2531 UV Curable Glossy Dielectric**

(Contd. of page 2)

**· Dangerous components:**

	Urethane acrylate oligomer ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317	60-80%
65983-31-5	Dicyclopentenxyloxyethyl acrylate ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335-H336	25-50%
24650-42-8	2,2-dimethoxy-2-phenylacetophenone ⚠ Aquatic Acute 1, H400; Aquatic Chronic 2, H411	1-5%
	Acrylic leveling agent ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	1-5%
	Proprietary Dye ⚠ Eye Irrit. 2A, H319; Skin Sens. 1A, H317	<1%
119-61-9	Benzophenone ⚠ Carc. 2, H351; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<1%
	Proprietary Defoamer ⚠ Flam. Liq. 3, H226; ⚠ Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304	<1%

#### 4 First-aid measures

**· Description of first aid measures**
**· General information:** Immediately remove any clothing soiled by the product.

**· After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

**· After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**· After eye contact:**

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

**· After swallowing:**

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

**· Information for doctor:**
**· Most important symptoms and effects, both acute and delayed** No further relevant information available.

**· Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

#### 5 Fire-fighting measures

**· Extinguishing media**
**· Suitable extinguishing agents:**

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

**· For safety reasons unsuitable extinguishing agents:** Water with full jet

**· Special hazards arising from the substance or mixture** No further relevant information available.

**· Advice for firefighters**
**· Protective equipment:** Wear SCBA.

US

(Contd. on page 4)

Printing date 11/30/2016

Reviewed on 11/30/2016

**Trade name: UV-2531 UV Curable Glossy Dielectric**

(Contd. of page 3)

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

119-61-9	Benzophenone	1.5 mg/m3
----------	--------------	-----------

- **PAC-2:**

119-61-9	Benzophenone	90 mg/m3
----------	--------------	----------

- **PAC-3:**

119-61-9	Benzophenone	310 mg/m3
----------	--------------	-----------

## 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaust at the workplace.

Open and handle container with care.

Prevent formation of aerosols.

- **Information about protection against explosions and fires: Keep respirator available.**

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and containers: No special requirements.**

- **Information about storage in one common storage facility:**

Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

- **Further information about storage conditions:**

Keep container well-sealed in cool, dry location.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

- **Specific end use(s) No further relevant information available.**

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems: No further data; see item 7.**

(Contd. on page 5)

Printing date 11/30/2016

Reviewed on 11/30/2016

Trade name: UV-2531 UV Curable Glossy Dielectric

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

**119-61-9 Benzophenone**

WEEL Long-term value: 0.5 mg/m<sup>3</sup>

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Respiratory equipment:**

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves** Nitrile rubber, NBR

· **Penetration time of glove material** Contact glove manufacture for break-through time.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Thick liquid

Color: Clear or colored

· **Odor:** Sweet

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 113 °C (235 °F)

· **Flash point:** 94 °C (201 °F)

· **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 6)

Printing date 11/30/2016

Reviewed on 11/30/2016

**Trade name: UV-2531 UV Curable Glossy Dielectric**

(Contd. of page 5)

· <b>Ignition temperature:</b>	
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
· <b>Vapor pressure at 20 °C (68 °F):</b>	10 hPa (8 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.10208 g/cm <sup>3</sup> (9.197 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	1.6-2.3 (BuAc=1)
· <b>Solubility in / Miscibility with Water:</b>	Water miscible No
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	0.0 %
<b>Solids content:</b>	100%
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal use conditions
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**  
Heat, flames and sparks. Extremes of temperature and direct sunlight.  
Contact with incompatible materials.
- **Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>Proprietary Defoamer</b>		
Oral	LD50	> 6000 mg/kg (Rat)
Dermal	LD50	> 3000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 7.8 mg/l (Rat)

(Contd. on page 7)

Printing date 11/30/2016

Reviewed on 11/30/2016

**Trade name: UV-2531 UV Curable Glossy Dielectric**

(Contd. of page 6)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
 The product shows the following dangers according to internally approved calculation methods for preparations:  
 Irritant  
 Carcinogenic.  
 The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

119-61-9 Benzophenone

2B

- **NTP (National Toxicology Program)**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

24650-42-8 2,2-dimethoxy-2-phenylacetophenone

EC50/48 h 26 mg/l (daphnia magna)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
 Water hazard class 2 (Self-assessment): hazardous for water  
 Do not allow product to reach ground water, water course or sewage system.  
 Danger to drinking water if even small quantities leak into the ground.  
 Also poisonous for fish and plankton in water bodies.  
 Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
 Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.  
 Disposal must be made in accordance with Federal, State, and Local regulations.

(Contd. on page 8)



Printing date 11/30/2016


Reviewed on 11/30/2016

Trade name: UV-2531 UV Curable Glossy Dielectric

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made in accordance with Federal, State, and Local regulations.

### 14 Transport information

· <b>UN-Number</b>	UN3082
· <b>DOT, ADR, IMDG, IATA</b>	
· <b>UN proper shipping name</b>	Environmentally hazardous substances, liquid, n.o.s. (2,2-dimethoxy-2-phenylacetophenone, Benzophenone)
· <b>DOT, ADR</b>	
· <b>IMDG</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-dimethoxy-2-phenylacetophenone, Benzophenone), MARINE POLLUTANT
· <b>IATA</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-dimethoxy-2-phenylacetophenone, Benzophenone)
· <b>Transport hazard class(es)</b>	
· <b>DOT, ADR, IMDG, IATA</b>	
	
· <b>Class</b>	9 Miscellaneous dangerous substances and articles
· <b>Label</b>	9
· <b>Packing group</b>	
· <b>DOT, ADR, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	Product contains environmentally hazardous substances: 2,2-dimethoxy-2-phenylacetophenone
· <b>Marine pollutant:</b>	Yes (DOT)
· <b>Special precautions for user</b>	Warning: Miscellaneous dangerous substances and articles
· <b>Danger code (Kemler):</b>	90
· <b>EMS Number:</b>	F-A,S-F
· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)



**Trade name: UV-2531 UV Curable Glossy Dielectric**

(Contd. of page 8)

 · **UN "Model Regulation":**

 UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES,  
 LIQUID, N.O.S. (2,2-DIMETHOXY-2-PHENYLACETOPHENONE,  
 BENZOPHENONE), 9, III

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

 · **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

 · **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

 · **TSCA (Toxic Substances Control Act):** All ingredients are listed or comply with TSCA regulations.

 · **Proposition 65**

 · **Chemicals known to cause cancer:**

119-61-9 | Benzophenone

 · **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

 · **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

 · **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

 · **Carcinogenic categories**

 · **EPA (Environmental Protection Agency)**

None of the ingredients are listed.

 · **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients are listed.

 · **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

 · **California SCAQMD Rule 443.1 VOC's:** No information available.

 · **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

 · **Hazard pictograms**


GHS07    GHS08    GHS09

 · **Signal word** Danger

 · **Hazard-determining components of labeling:**

Urethane acrylate oligomer

Dicyclopentenylloxyethyl acrylate

Proprietary Defoamer

Proprietary Dye

(Contd. on page 10)

Printing date 11/30/2016

Reviewed on 11/30/2016

**Trade name: UV-2531 UV Curable Glossy Dielectric**

(Contd. of page 9)

**· Hazard statements**

- H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.  
H401 Toxic to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.

**· Precautionary statements**

- P261 Avoid breathing dust/fume/gas/mist/vapors/spray  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P273 Avoid release to the environment.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· National regulations:****· Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

**· Other regulations, limitations and prohibitive regulations**

RoHS 2 2011/65/EU along with EU Directive 2002/95/EC – Waste from Electrical and Electronic Equipment (WEEE):

Applied Ink Solutions products do not exceed the amount of allowable levels concerning: Cadmium (Cd); Hexavalent Chromium (CrVI); Mercury (Hg); Lead (Pb); Polybrominated Biphenyls (PBB's) as bromide; Polybrominated Diphenyl Ethers (PBDEs) as bromide, decaBDE.

Applied Ink Solutions has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Department issuing SDS:** Product safety department**· Contact:** Mr. Cole**· Revision History:** New SDS**· Date of preparation / last revision** 11/30/2016 / -**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. on page 11)

Printing date 11/30/2016

Reviewed on 11/30/2016

**Trade name: UV-2531 UV Curable Glossy Dielectric**

(Contd. of page 10)

*EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Flam. Liq. 3: Flammable liquids – Category 3**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A**Skin Sens. 1: Skin sensitisation – Category 1**Skin Sens. 1A: Skin sensitisation – Category 1A**Skin Sens. 1B: Skin sensitisation – Category 1B**Muta. 1B: Germ cell mutagenicity – Category 1B**Carc. 1B: Carcinogenicity – Category 1B**Carc. 2: Carcinogenicity – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

US