Printing date 01/31/2019 Reviewed on 01/31/2019

## 1 Identification of the substance/mixture and of the company

- · Product identifier
- · Trade name: WB-101 Water-Based Silver Conductive Ink
- · Application of the substance / the mixture: Film coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Applied Ink Solutions 200 Flanders Road

Westborough, MA 01581

USA

· Information department:

Product Safety

Email: sales@appliedinksolutions.com

· Emergency telephone number:

Chemtrec USA Emergency: 800-424-9300

Chemtrec International Emergency: 703-527-3887

Applied Ink Solutions: 617-965-5511

### 2 Hazard(s) identification

· Classification of the substance or mixture:



GHS08 Health hazard

H360 May damage fertility or the unborn child. Repr. 1B



GHS09 Environment

H400 Very toxic to aquatic life. Aquatic Acute 1

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eve Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- GHS label elements: The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms:







GHS07

GHS08

GHS09

- · Signal word: Danger
- · Hazard-determining components of labeling: Silver

(Contd. on page 2)

Printing date 01/31/2019 Reviewed on 01/31/2019

Trade name: WB-101 Water-Based Silver Conductive Ink

(Contd. of page 1)

#### · Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### · Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

*P273* Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention. P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system
- · NFPA ratings (scale 0 4):



Health = 1 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4):



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
7440-22-4		60-80%
	🔖 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	Urethane acrylate oligomer	10-25%
	💠 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317	
	N-methyl-2-pyrrolidinone	1-5%
	🔖 Repr. 1B, H360; 🕠 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Flam. Liq. 4, H227	

(Contd. on page 3)



Printing date 01/31/2019 Reviewed on 01/31/2019

Trade name: WB-101 Water-Based Silver Conductive Ink

	(Con	td. of page 2
· Additional Components:		
577-11-7 Dioctyl sodium sulfosuccinate	<b>♦</b> Acute Tox. 4, H302; Eye Irrit. 2A, H319	<1%
7732-18-5 Water		10-25%

### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- · Information for doctor
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet.
- · Special hazards arising from the substance or mixture: No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear SCBA.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Printing date 01/31/2019 Reviewed on 01/31/2019

Trade name: WB-101 Water-Based Silver Conductive Ink

(Contd. of page 3)

## 7 Handling and storage

- · Handling
- · Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Protect against electrostatic charges.

Keep ignition sources away - Do not smoke.

- · Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

· Further information about storage conditions:

Keep container well-sealed in cool, dry location.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· Specific end use(s): No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

### 872-50-4 N-methyl-2-pyrrolidinone

WEEL Long-term value: 10 ppm Skin

· Ingredients with biological limit values:

### 872-50-4 N-methyl-2-pyrrolidinone

BEI 100 mg/L

Medium: urine Time: end of shift

Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



Printing date 01/31/2019 Reviewed on 01/31/2019

Trade name: WB-101 Water-Based Silver Conductive Ink

 $(Contd.\ of\ page\ 4)$ 

- $\cdot \textit{Material of gloves:} \ \textit{Nitrile rubber, NBR}$
- · Penetration time of glove material: Contact glove manufacture for break-through time.
- · Eye protection:



Tightly sealed goggles

Color: Odor: Odor: Odor threshold:  PH-value:  Change in condition Melting point/Melting range: Boiling point/Boiling range: Itash point:  Flammability (solid, gaseous):  Ignition temperature  Decomposition temperature:  Number of explosion:  PExplosion limits Lower:  Note that St.	Liquid Cilver-colored Characteristic Not determined.  Vindetermined.  Vindetermined.
Appearance Form: Color: Solor: Odor: Odor threshold:  PH-value:  Change in condition Melting point/Melting range: Boiling point/Boiling range: Itash point: Flammability (solid, gaseous):  Ignition temperature  Decomposition temperature:  Number of explosion:  PExplosion limits Lower:  Note Color:  Auto igniting:  PExplosion limits Lower:  Note Color: Solor:	Silver-colored Characteristic Not determined. Not determined.  Undetermined.  100 °C (212 °F) 14 °C (201 °F) Not applicable.  Product is not self-igniting.
Form: Color: Color: St. Odor: Odor threshold:  PH-value: Change in condition Melting point/Melting range: Boiling point/Boiling range: Itash point: Flammability (solid, gaseous):  Ignition temperature Decomposition temperature: Natto igniting: Panger of explosion: PExplosion limits Lower: National Color St. Lower:  Lower:  Lower:  Lower:  PODO Color St. No. Color	Silver-colored Characteristic Not determined. Not determined.  Undetermined.  100 °C (212 °F) 14 °C (201 °F) Not applicable.  Product is not self-igniting.
Odor: Odor threshold:  PH-value:  Change in condition Melting point/Melting range: Boiling point/Boiling range: Itash point:  Flammability (solid, gaseous):  Ignition temperature  Decomposition temperature:  Number of explosion:  PExplosion limits Lower:  Note that the should be supported by the same of the should be supported by the same of the same of the should be supported by the same of the sam	Characteristic Not determined.  Not determined.  Undetermined.  100 °C (212 °F)  14 °C (201 °F)  Not applicable.  Product is not self-igniting.
Odor threshold:  pH-value:  Change in condition  Melting point/Melting range: Boiling point/Boiling range: Italian point:  Flash point:  Flammability (solid, gaseous):  Note that I be a seem of the performance of the perfo	Not determined.  Not determined.  Undetermined.  00 °C (212 °F)  04 °C (201 °F)  Not applicable.  Not determined.  Product is not self-igniting.
pH-value:  Change in condition Melting point/Melting range: Boiling point/Boiling range: Itash point:  Flash point:  Flammability (solid, gaseous):  Note that it is a second of the period of the per	Not determined.  Undetermined.  100 °C (212 °F)  14 °C (201 °F)  Not applicable.  Not determined.  Product is not self-igniting.
Change in condition Melting point/Melting range: Boiling point/Boiling range: Items point: Flash point: Flammability (solid, gaseous): Note that I be a second position temperature: Decomposition temperature: Auto igniting: Panger of explosion: Explosion limits Lower: Note that I be a second point po	Undetermined. 100 °C (212 °F) 14 °C (201 °F) Not applicable.  Not determined.  Product is not self-igniting.
Melting point/Melting range: Boiling point/Boiling range: Its Flash point:  Flammability (solid, gaseous):  Ignition temperature  Decomposition temperature:  Auto igniting:  Panger of explosion:  Explosion limits Lower:	Not determined.  Product is not self-igniting.
Boiling point/Boiling range: 10 Flash point: 90 Flammability (solid, gaseous): No Ignition temperature Decomposition temperature: No Auto igniting: P Danger of explosion: P Explosion limits Lower: No	Not determined.  Product is not self-igniting.
Flash point: 9.  Flammability (solid, gaseous): N  Ignition temperature  Decomposition temperature: N  Auto igniting: P  Danger of explosion: P  Explosion limits  Lower: N	Not applicable.  Not determined.  Product is not self-igniting.
Flammability (solid, gaseous): N Ignition temperature Decomposition temperature: N Auto igniting: P Danger of explosion: P Explosion limits Lower: N	Not applicable.  Not determined.  Product is not self-igniting.
Ignition temperature  Decomposition temperature:  Nuto igniting:  Panger of explosion:  Explosion limits Lower:  N	Not determined.  Product is not self-igniting.
Decomposition temperature: N Auto igniting: P Danger of explosion: P Explosion limits Lower: N	Product is not self-igniting.
Auto igniting: P Danger of explosion: P Explosion limits Lower: N	Product is not self-igniting.
Danger of explosion: P  Explosion limits Lower: N	
Explosion limits Lower: N	Product does not present an explosion hazard.
Lower: N	
	Not determined.
Upper: N	Not determined.
Vapor pressure:	Not determined.
Density at 20 °C (68 °F): 2.	2.6 g/cm³ (21.697 lbs/gal)
	Not determined.
1	Not determined.
Evaporation rate: 1.	.6-2.3 (BuAc=1)
Solubility in / Miscibility with	
Water:	Vater miscible No
Partition coefficient (n-octanol/water): N	Not determined.
Viscosity	
<b>3</b> *** *** *	Not determined.
Kinematic: N	Not determined.
Solvent content:	
8	2.3 % 7.0 %



Printing date 01/31/2019 Reviewed on 01/31/2019

Trade name: WB-101 Water-Based Silver Conductive Ink

(Contd. of page 5)

VOC content:	2.3 %	
Solids content: Other information:	80% +/- $2%No further relevant information available.$	

### 10 Stability and reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal use conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid:

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50	· LD/LC50 values that are relevant for classification:		
872-50-4 N	V-methyl-2	-pyrrolidinone	
Oral	LD50	3914 mg/kg (Rat)	
Dermal	LD50	8000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>5.0 mg/l (Rat)	

- · Primary irritant effect:
- · On the skin: May cause skin irritation.
- · On the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer):	
None of the ingredients are listed.	
· NTP (National Toxicology Program):	
None of the ingredients are listed.	
· OSHA-Ca (Occupational Safety & Health Administration	on):
None of the ingredients are listed.	



Printing date 01/31/2019 Reviewed on 01/31/2019

Trade name: WB-101 Water-Based Silver Conductive Ink

(Contd. of page 6)

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

#### 7440-22-4 Silver

LC50/96 h (static) 0.0062 mg/l (Lepomis macrochirus (Bluegill))

0.00155-0.00293 mg/l (Pimephales promelas)

- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

- · Uncleaned packagings
- Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

1 / M		C	, •
/ Tranc	nort in	Orma	tron
	port ini	K <i>VJ M I I I</i> 4 4 4	44011

•	UN-Number
---	-----------

· DOT, ADR, IMDG, IATA: UN3082

· UN proper shipping name

• DOT, ADR: Environmentally hazardous substances, liquid, n.o.s. (Silver).

· IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (Silver), MARINE POLLUTANT.

• IATA: Environmentally hazardous substance, liquid, n.o.s. (Silver).

- · Transport hazard class(es)
- · DOT, ADR, IMDG, IATA:



· Class: 9 Miscellaneous dangerous substances and articles.

· Label:

(Contd. on page 8)



Printing date 01/31/2019 Reviewed on 01/31/2019

Trade name: WB-101 Water-Based Silver Conductive Ink

	(Contd. of pag
Packing group	
DOT, ADR, IMDG, IATA:	III
Environmental hazards:	Product contains environmentally hazardous substances: Silver.
· Marine pollutant:	Yes (DOT)
Special precautions for user:	Warning: Miscellaneous dangerous substances and articles
· Danger code (Kemler): 90	
EMS Number:	F- $A$ , $S$ - $F$
· Stowage Category	A
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
· DOT	
Quantity limitations:	On passenger aircraft/rail: No limit
~ .	On cargo aircraft only: No limit
· <i>ADR</i>	
Excepted quantities (EQ):	Code: E1
• • • • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ): 5L	
Excepted quantities $(\widetilde{EQ})$ :	Code: E1
-	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE
	LIQUID, N.O.S. (SILVER), 9, III.

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

Sara	
· Section 35	5 (extremely hazardous substances):
None of th	e ingredients are listed.
· Section 31	3 (Specific toxic chemical listings):
7440-22-4	Silver
872-50-4	N-methyl-2-pyrrolidinone
· TSCA (To	xic Substances Control Act):

- All ingredients are listed or comply with TSCA regulations.
- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

(Contd. on page 9)



Printing date 01/31/2019 Reviewed on 01/31/2019

Trade name: WB-101 Water-Based Silver Conductive Ink

	(Contd. of pag
· Chemicals known to cause developmental toxicity:	
872-50-4 N-methyl-2-pyrrolidinone	
· Carcinogenic categories	
· EPA (Environmental Protection Agency):	
7440-22-4   Silver	
· TLV (Threshold Limit Value established by ACGIH):	
None of the ingredients are listed.	
· NIOSH-Ca (National Institute for Occupational Safety and Health):	
None of the ingredients are listed.	
· Massachusetts State Right To Know List:	
7440-22-4 Silver	
872-50-4 N-methyl-2-pyrrolidinone	
· New Jersey State Right To Know List:	
7440-22-4   Silver	
872-50-4 N-methyl-2-pyrrolidinone	
Pennsylvania Hazardous Substances List:	
7440-22-4   Silver	
872-50-4 N-methyl-2-pyrrolidinone	

- · California SCAOMD Rule 443.1 VOC's: No information available.
- · GHS label elements: The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms:







GHS07

GHS08

GHS09

- · Signal word: Danger
- · Hazard-determining components of labeling:

Silver

#### · Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

### · Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

*P280* Wear protective gloves/protective clothing/eye protection/face protection.

*P273* Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention. P302+P352 IF ON SKIN: Wash with plenty of soap and water.

(Contd. on page 10)



Printing date 01/31/2019 Reviewed on 01/31/2019

Trade name: WB-101 Water-Based Silver Conductive Ink

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(Contd. of page 9)

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other regulations, limitations and prohibitive regulations

RoHS (EU)2015/863 along with EU Directive 2022/19/EU – Waste from Electrical and Electronic Equipment (WEEE):

Applied Ink Solutions products do not exceed the amount of allowable levels concerning: Cadmium (Cd); Mercury (Hg); Lead (Pb); Hexavalent chromium (Cr6+); Polybrominated biphenyls (PBB); Polybrominated diphenyl ethers (PBDE); Bis(2-Ethylhexyl) phthalate (DEHP); Benzyl butyl phthalate (BBP); Dibutyl phthalate (DBP); Diisobutyl phthalate (DIBP); Bis(2-Ethylhexyl) phthalate (DEHP); Benzyl butyl phthalate (BBP); Dibutyl phthalate (DIBP).

Applied Ink Solutions has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the **Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.** 

Registration, Evaluation and Authorization of Chemicals (REACH) & Substances of Very High Concern (SVHC): This product contains a substance on the SVHC list: CAS# 872-50-4 1-Methyl-2-pyrrolidone.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Mr. Cole
- · Revision History: Rev 1.
- Date of preparation / last revision 10/20/2017 / 01/31/2019
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitization - Skin, Hazard Category 1

Skin Sens. 1B: Sensitization - Skin, Hazard Category 1B

Repr. 1B: Reproductive toxicity, Hazard Category 1B

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1