

Printing date 08/05/2022 Reviewed on 08/05/2022

1 Identification

- · Product identifier
- · Trade name: AG-919 Heat Stable Silver Ink
- · Application of the substance / the mixture Functional electronic screen printing ink
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Kayaku Advanced Materials, Inc.

200 Flanders Road

Westborough, MA 01581

Tel: (617) 965-5511 Fax: (617) 965-5818

· Information department:

Product Safety

Email: productsafety@kayakuAM.com

Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300

Chemtrec International Emergency: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS09 Environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Skin Irrititation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07 GHS09

- · Signal word Warning
- · Hazard-determining components of labeling:

Proprietary Resin

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 2)



Printing date 08/05/2022 Reviewed on 08/05/2022

Trade name: AG-919 Heat Stable Silver Ink

(Contd. of page 1)

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
7440-22-4	Silver	40-60%
	🔖 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
112-15-2	Diethylene glycol monoethyl ether acetate	25-50%
	💠 Eye Irritation 2A, H319	
	Proprietary Resin	5-15%
	Aquatic Chronic 2, H411; Acute Toxicity - Dermal 4, H312; Skin Irrititation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	-



Printing date 08/05/2022 Reviewed on 08/05/2022

Trade name: AG-919 Heat Stable Silver Ink

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear SCBA.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

7440-22-4 Silver

 $0.3 \, \text{mg/m3}$

(Contd. on page 4)



Printing date 08/05/2022 Reviewed on 08/05/2022

Trade name: AG-919 Heat Stable Silver Ink

		(Contd. of page
112-15-2	Diethylene glycol monoethyl ether acetate	16 mg/m3
	Proprietary Resin	90 mg/m ³
PAC-2:		·
7440-22-4	Silver	170 mg/m
112-15-2	Diethylene glycol monoethyl ether acetate	170 mg/m
	Proprietary Resin	990 mg/m
PAC-3:		
7440-22-4	Silver	990 mg/m3
112-15-2	Diethylene glycol monoethyl ether acetate	1,000 mg/m
	Proprietary Resin	5,900 mg/m

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

No special measures required.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

· Further information about storage conditions:

Keep container well-sealed in cool, dry location.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

(Contd. on page 5)



Printing date 08/05/2022 Reviewed on 08/05/2022

Trade name: AG-919 Heat Stable Silver Ink

(Contd. of page 4)

Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

· Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material Contact glove manufacture for break-through time.
- · Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and	chemical properties
· General Information · Appearance:	
Form:	Liquid
Color:	Silver-colored
· Odor:	Sweet
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	217 °C (422.6 °F)
· Flash point:	98 °C (208.4 °F)
· Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	310 °C (590 °F)
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density:	See other information
· Relative density	Not determined.
· Vapor density	Not determined.

(Contd. on page 6)



Printing date 08/05/2022 Reviewed on 08/05/2022

Trade name: AG-919 Heat Stable Silver Ink

		(Contd. of page .	
Evaporation rate	1.6-2.3 (BuAc=1)		
Solubility in / Miscibility with			
Water:	Water miscible No		
Partition coefficient (n-octano	ol/water): Not determined.		
Viscosity:			
Dynamic:	Not determined.		
Kinematic:	Not determined.		
Solvent content:			
Organic solvents:	0.0 %		
VOC content:	0.0%		
Solids content:	66 - 70 %		
Other information	Other information No further relevant information available.		

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:						
Propriet	Proprietary Resin					
Oral	LD50	30000 mg/kg (Rat)				
Dermal	LD50	>1200 mg/kg (Rat)				

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

Γ	· IARC (International Agency for Research on Cancer)		
	None of the ingredients are listed.		
_	·	(0 . 1	

(Contd. on page 7)



Printing date 08/05/2022 Reviewed on 08/05/2022

Trade name: AG-919 Heat Stable Silver Ink

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

7440-22-4 Silver

LC50/96 h (static) 0.0062 mg/l (Lepomis macrochirus (Bluegill))

0.00155-0.00293 mg/l (Pimephales promelas)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.

Disposal must be made in accordance with Federal, State, and Local regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA

UN3082

(Contd. on page 8)



Printing date 08/05/2022 Reviewed on 08/05/2022

Trade name: AG-919 Heat Stable Silver Ink

	(Contd. of page		
· UN proper shipping name · DOT, ADR	Environmentally hazardous substances, liquid, n.o.s. (Silver, 4,4		
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI. N.O.S. (Silver, 4,4'-Isopropylidenediphenol- Epichlorohydr Copolymer)		
· Transport hazard class(es)			
DOT, ADR, IMDG, IATA			
· Class · Label	9 Miscellaneous dangerous substances and articles 9		
· Packing group · DOT, ADR, IMDG, IATA	III		
Environmental hazards: Marine pollutant:	Product contains environmentally hazardous substances: Silver Yes (DOT)		
Special precautions for user Hazard identification number (Kemler code):			
· EMS Number: · Stowage Category	F-A,S-F A		
	71		
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.		
Transport/Additional information:			
· DOT · Quantity limitations	On passenger aircraft/rail: No limit On cargo aircraft only: No limit		
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml		
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml		
	Maximum net quantity per outer packaging: 1000 ml		



Printing date 08/05/2022 Reviewed on 08/05/2022

Trade name: AG-919 Heat Stable Silver Ink

(Contd. of page 8)

· UN ''Model Regulation'':

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (SILVER, 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN COPOLYMER), 9, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355 (extremely hazardous substance	ces	substan	zardous	v İ	(extremel	355	· Section	
--	-----	---------	---------	-----	-----------	-----	-----------	--

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

7440-22-4 Silver

112-15-2 Diethylene glycol monoethyl ether acetate

- · TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.
- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

7440-22-4 Silver

 ν

· TLV (Threshold Limit Value)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

7440-22-4 Silver

· New Jersey State Right To Know List

7440-22-4 Silver

112-15-2 Diethylene glycol monoethyl ether acetate

Pennsylvania Hazardous Substances List

7440-22-4 Silver

112-15-2 Diethylene glycol monoethyl ether acetate

- · California SCAQMD Rule 443.1 VOC's: No information available.
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)



Printing date 08/05/2022 Reviewed on 08/05/2022

Trade name: AG-919 Heat Stable Silver Ink

(Contd. of page 9)

· Hazard pictograms



· Signal word Warning

· Hazard-determining components of labeling:

Proprietary Resin

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· National regulations:

· Other regulations, limitations and prohibitive regulations

RoHS 2 2011/65/EU along with EU Directive 2022/19/EU – Waste from Electrical and Electronic Equipment (WEEE):

Applied Ink Solutions products do not exceed the amount of allowable levels concerning: Cadmiu (Cd); Hexavalent Chromium (CrVI); Mercury (Hg); Lead (Pb); Polybrominated Biphenyls (PBB's) as bromide; Polybrominated Diphenyl Ethers (PBDEs) as bromide, decaBDE.

Applied Ink Solutions has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

Registration, Evaluation and Authorization of Chemicals (REACH) & Substances of Very High Concern(SVHC): This product does not contain substances on the SVHC list.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)



Printing date 08/05/2022 Reviewed on 08/05/2022

Trade name: AG-919 Heat Stable Silver Ink

(Contd. of page 10)

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

· Revision History: The manufacturer's information in Section 1 has been updated.

· Date of preparation / last revision 08/05/2022

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Toxicity - Dermal 4: Acute toxicity - Category 4

Skin Irrititation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2