

Printing date 05/15/2020

1 Identification

· Product identifier

- Trade name: <u>Antistat-268 Water Based Carbon Resistive Coating</u>
- · Application of the substance / the mixture Aqueous carbon coating
- Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818

- Information department: Product Safety Email: productsafety@kayakuAM.com • Emergency telephone number:
- Kayaku Advanced Materials : <u>617-965-5511</u> Chemtrec USA Emergency : <u>800-424-9300</u> Chemtrec International Emergency : <u>703-527-3887</u>

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Repr. 1B

GHS07

Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

Flam. Liq. 4 H227 Combustible liquid.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*

_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _



H315 Causes skin irritation.

Signal word Danger
Hazard-determining components of labeling: N-methyl-2-pyrrolidinone
Hazard statements H227 Combustible liquid.

(Contd. on page 2)

Reviewed on 05/15/2020

[–] US

US



Safety Data Sheet acc. to OSHA HCS

05/15/2020 **л** . . . 1

05/15/2020 . 1

Printing date 05/15	/2020	Reviewed on 05/15/202
Frade name: Antist	at-268 Water Based Carbon Resistive Coating	
		(Contd. of page 1
H319 Causes se	erious eye irritation.	
	e an allergic skin reaction.	
	age fertility or the unborn child.	
• Precautionary s	statements	
P261	Avoid breathing dust/fume/gas/mist/vapors/spray	
P280	Wear protective gloves/protective clothing/eye protective	
P301+P310	If swallowed: Immediately call a poison center/docte)r.
P302+P352	If on skin: Wash with plenty of soap and water.	
P304+P341	If inhaled: If breathing is difficult, remove perso breathing.	
P305+P351+P	338 If in eyes: Rinse cautiously with water for several n and easy to do. Continue rinsing.	
P333+P313	If skin irritation or rash occurs: Get medical advice/	'attention.
P337+P313	If eye irritation persists: Get medical advice/attentio	n.
P370+P378	In case of fire: Use to extinguish: Alcohol resistant j dioxide.	foam, Fire-extinguishing powder, Carbo
P403+P235	Store in a well-ventilated place. Keep cool.	
P501	Dispose of contents/container in accordance wit regulations.	h local/regional/national/internationa
· Classification s · NFPA ratings (
	Iealth = 2	
	ire = 2	
	eactivity = 0	
· HMIS-ratings ((scale 0 - 4)	
HEALTH *2	Health = *2	
FIRE 2	Fire = 2	
REACTIVITY 0	Reactivity = 0	
• Other hazards		
-	and vPvB assessment	
• PBT: Not appli		
• vPvB: Not appl		
3 Composition	/information on ingredients	
· Chemical chard	acterization: Mixtures	

• Chemical characterization: Mixtures • Description: Mixture of the substances listed below with nonhazardous additions.

	Urethane acrylate oligomer	10-25%
	🚯 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317	1
1333-86-4	Carbon black Scarc. 2, H351	5-15%
872-50-4	N-methyl-2-pyrrolidinone Acute Tox. 3, H331; & Repr. 1B, H360; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335; Flam. Liq. 4, H227	1-5%



Printing date 05/15/2020

Reviewed on 05/15/2020

Trade name: Antistat-268 Water Based Carbon Resistive Coating

		(Contd. of page 2)
577-11-7	Dioctyl sodium sulfosuccinate	1-5%
· Additional	Components:	
	Proprietary surfactant	1-5%
7732-18-5	Water	60-80%

4 First-aid measures

· Description of first aid measures

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed Treat symptomatically.

<u>5 Fire</u>-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- Alcohol resistant foam
- Carbon dioxide
- Fire-extinguishing powder
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear SCBA.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

• **Reference to other sections** See Section 7 for information on safe handling.

(Contd. on page 4)

US -



Printing date 05/15/2020

Reviewed on 05/15/2020

Trade name: Antistat-268 Water Based Carbon Resistive Coating

(Contd. of page 3)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaust at the workplace.
- Open and handle container with care.
- Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep respirator available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:
- Do not store together with alkalis (caustic solutions). Do not store together with oxidizing and acidic materials.
- Further information about storage conditions: Keep container well-sealed in cool, dry location. Protect from heat and direct sunlight.
- Store receptacle in a well ventilated area.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

1555-	86-4 Carbon black	
PEL	Long-term value: 3.5 mg/m ³	
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs;See Pocket Guide Apps.A+C	
TLV	Long-term value: 3* mg/m ³ *inhalable fraction	
872-5	0-4 N-methyl-2-pyrrolidinone	
WEEI	, Long-term value: 10 ppm Skin	
Ingre	lients with biological limit values:	
872-5	0-4 N-methyl-2-pyrrolidinone	
	00 mg/L	



Printing date 05/15/2020

· Exposure controls

Reviewed on 05/15/2020

Trade name: Antistat-268 Water Based Carbon Resistive Coating

(Contd. of page 4)

Personal protective equipment:
General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

• Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA. • Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • *Material of gloves Nitrile rubber, NBR*

- · Penetration time of glove material Contact glove manufacture for break-through time.
- Eye protection:



Tightly sealed goggles

· Information on basic physical and · General Information	chemical properties	
· Appearance:		
Form:	Liquid	
Color:	Black	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	86 °C (186.8 °F)	
· Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
• Explosion limits:		
Lower:	Not determined.	



Printing date 05/15/2020

Reviewed on 05/15/2020

Trade name: Antistat-268 Water Based Carbon Resistive Coating

		(Contd. of page
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density:	See other information	
Relative density	Not determined.	
Vapor density	Not determined.	
Solubility in / Miscibility with		
Water:	Water miscible No	
Partition coefficient (n-octand	ol/water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	1-5 %	
Water:	60-80 %	
VOC content:	1-5 %	
Solids content:	30-34 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid
- Contact with incompatible materials.
- Heat, flames and sparks. Extremes of temperature and direct sunlight.
- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- Hazardous decomposition products:
- Carbon monoxide and carbon dioxide
- No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50	values	that are	relevant	for	classification:

872-50-4 N-methyl-2-pyrrolidinone

Oral	LD50	3914 mg/kg (Rat)
Dermal		8000 mg/kg (rabbit)
Inhalative		>5.0 mg/l (Rat)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Irritating effect.

(Contd. on page 7)

[·]US·



Printing date 05/15/2020

Reviewed on 05/15/2020

Trade name: Antistat-268 Water Based Carbon Resistive Coating

(Contd. of page 6)

2B

- \cdot Sensitization: Sensitization possible through skin contact.
- \cdot Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1333-86-4 Carbon black

· NTP (National Toxicology Program)

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

• Aquatic toxicity:

872-50-4 N-methyl-2-pyrrolidinone

EC50/24 h > 1000 mg/l (daphnia magna)

LC50/96 h >500 mg/l (Leuciscus idus)

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

• Mobility in soil No further relevant information available.

• Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

• **vPvB:** Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

• Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

· Uncleaned packagings:

• Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

(Contd. on page 8)



Printing date 05/15/2020

Reviewed on 05/15/2020

Trade name: Antistat-268 Water Based Carbon Resistive Coating

(Contd. of page 7)

· UN-Number		
· DOT, ADR, ADN, IMDG, IATA	Not Regulated	
· UN proper shipping name · ADR, ADN, IMDG, IATA	Not Regulated	
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA		
· Class	Not Regulated	
· Packing group		
· DOT, ADR, IMDG, IATA	Not Regulated	
· Environmental hazards:	Not applicable.	
· Special precautions for user	Not applicable.	
· Stowage Code	SW1 Protected from sources of heat.	
· Handling Code	H2 Keep as cool as reasonably practicable	
· Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	
· UN ''Model Regulation'':	Not Regulated	

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

• Section 313 (Specific toxic chemical listings):

872-50-4 N-methyl-2-pyrrolidinone

• TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations. • Proposition 65

· Chemicals known to cause cancer:

1333-86-4 Carbon black

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

872-50-4 N-methyl-2-pyrrolidinone

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

(Contd. on page 9)

US -



Printing date 05/15/2020

Reviewed on 05/15/2020

Trade name: Antistat-268 Water Based Carbon Resistive Coating

(Contd. of page 8)

A4

• TLV (Threshold Limit Value established by ACGIH)

1333-86-4 Carbon black

· NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 Carbon black

· Massachusetts State Right To Know List

872-50-4 N-methyl-2-pyrrolidinone

· New Jersey State Right To Know List

872-50-4 N-methyl-2-pyrrolidinone

· Pennsylvania Hazardous Substances List

872-50-4 N-methyl-2-pyrrolidinone

· California SCAQMD Rule 443.1 VOC's: No information available.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



	ining components of labeling:
N-methyl-2-pyr	
Hazard stateme	ents
H227 Combusti	
H315 Causes sh	kin irritation.
H319 Causes se	prious eye irritation.
H317 May caus	e an allergic skin reaction.
H360 May dam	age fertility or the unborn child.
Precautionary s	statements
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P305+P351+P	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
<i>P337+P313</i>	<i>If eye irritation persists: Get medical advice/attention.</i>
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
	(Contd. on page 10)

IS —



Printing date 05/15/2020

Reviewed on 05/15/2020

Trade name: Antistat-268 Water Based Carbon Resistive Coating

(Contd. of page 9)

· National regulations:

• Other regulations, limitations and prohibitive regulations

Kayaku Advanced Materials has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- *Revision History:* The manufacturer's information in Section 1 has been updated.
- Date of preparation / last revision 05/15/2020 / 1
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 4: Flammable liquids - Category 4 Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 3: Acute toxicity - Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B Carc. 2: Carcinogenicity – Category 2 Repr. 1B: Reproductive toxicity - Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3