ADVANCED MATERIALS

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.09.2022

Version number 4

Revision: 16.09.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- Trade name: EP-600 Two Part Conductive Epoxy
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Functional electronic epoxy
- \cdot 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818

Further information obtainable from: Product Safety Email: productsafety@kayakuAM.com 1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

Muta. 2	H341 Suspected of causing genetic defects.
Carc. 2	H351 Suspected of causing cancer.
GH.	S09 environment
GH	

Skin Irrit. 2H315 Causes skin irritation.Eye Irrit. 2H319 Causes serious eye irritation.Skin Sens. 1H317 May cause an allergic skin reaction.

Skin Sens. 1 H51/ May cause an allergic skin reaction.

· 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

EU -



Printing date 16.09.2022

Version number 4

Revision: 16.09.2022

Trade name: EP-600 Two Part Conductive Epoxy



· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 7440-22-4	Silver	60-80%
EINECS: 231-131-3	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 28064-14-4	Phenol, polymer with formaldehyde, glycidyl ether	10-25%
	Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
		l. on pa



Printing date 16.09.2022

Version number 4

Revision: 16.09.2022

Trade name: EP-600 Two Part Conductive Epoxy

		l. of page 2)
CAS: 68953-36-6	Fatty acids, tall-oil, reaction products with tetraethylenepentamine Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	5-15%
CAS: 2426-08-6 EINECS: 219-376-4 Index number: 603-039-00-7	Butyl glycidyl ether Flam. Liq. 3, H226; S Muta. 2, H341; Carc. 2, H351; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	1-5%
CAS: 112-57-2 EINECS: 203-986-2 Index number: 612-060-00-0	Tetraethylenepentamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	1-5%
	Proprietary Resin Aquatic Chronic 2, H411; O Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	<1%

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

• *After skin contact: Immediately wash with water and soap and rinse thoroughly.*

• After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

• 5.1 Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

EU -

ADVANCED MATERIALS

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.09.2022

Version number 4

Revision: 16.09.2022

Trade name: EP-600 Two Part Conductive Epoxy

(Contd. of page 3)

Keep away from ignition sources.
6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.

- Information about fire and explosion protection: No special measures required. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Store in cool, dry conditions in well sealed containers. Protect from heat and direct sunlight.
- Store receptacle in a well ventilated area.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at
- *the workplace. Additional information: The lists valid during the making were used as basis.*
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from food and beverages.
- Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

• Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)



Printing date 16.09.2022

Version number 4

Revision: 16.09.2022

(Contd. of page 4)

Trade name: EP-600 Two Part Conductive Epoxy

· Protection of hands:



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- *Material of gloves* Nitrile rubber, NBR
- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

Appearance:		
Form:	Paste	
Colour: Odour:	Silver-coloured	
Odour: Odour threshold:	Strong Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range:	Undetermined.	
Flash point:	Not applicable.	
Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not determined.	
Density:	Not determined.	
Relative density	Not determined.	
Vapour density	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	

EU -



Printing date 16.09.2022

Version number 4

Revision: 16.09.2022

Trade name: EP-600 Two Part Conductive Epoxy

		(Contd. of page 5)
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.0 %	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.

• 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases

- · 10.6 Hazardous decomposition products:
- Carbon monoxide and carbon dioxide Nitrogen oxides (NOx) Ammonia

SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

2426-08-6 Butyl glycidyl ether

Oral LD50 2050 mg/kg (Rat)

Dermal LD50 2520 mg/kg (rabbit)

112-57-2 Tetraethylenepentamine

Dermal LD50 660 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity

Suspected of causing genetic defects.

• Carcinogenicity

Suspected of causing cancer.

(Contd. on page 7)

EU



Printing date 16.09.2022

Safety data sheet according to 1907/2006/EC, Article 31

Version number 4

Revision: 16.09.2022

(Contd. of page 6)

Trade name: EP-600 Two Part Conductive Epoxy

- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

7440-22-4 Silver

LC50/96 h (static) 0.0062 mg/l (Lepomis macrochirus (Bluegill))

0.00155-0.00293 mg/l (Pimephales promelas)

28064-14-4 Phenol, polymer with formaldehyde, glycidyl ether

EC50/48 h 1-10 mg/l (daphnia magna)

• 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- **Remark:** Harmful to fish
- Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· 12.5 Results of PBT and vPvB assessment

• *PBT:* Not applicable.

• **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA

UN3082

(Contd. on page 8)

EU —





Revision: 16.09.2022

Printing date 16.09.2022

Version number 4

Trade name: EP-600 Two Part Conductive Epoxy

	(Contd. of pag
14.2 UN proper shipping name	
ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUIN N.O.S. (Silver, Phenol, polymer with formaldehyde, glycia ether)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUIN N.O.S. (Silver, Phenol, polymer with formaldehyde, glycid ether), MARINE POLLUTANT
IATA	Environmentally hazardous substance, liquid, n.o.s. (Silve Phenol, polymer with formaldehyde, glycidyl ether)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles. 9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substance Phenol, polymer with formaldehyde, glycidyl ether
14.6 Special precautions for user Hazard identification number (Kemler code):	<i>Warning: Miscellaneous dangerous substances and articles. 90</i>
EMS Number:	50 F-A,S-F
Segregation groups	Alkalis
Stowage Category	A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	f Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: El
	Maximum net quantity per inner packaging: 30 ml
Transport of the own	Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
	(Contd. on page



Printing date 16.09.2022

Version number 4

Revision: 16.09.2022

(Contd. of page 8)

Trade name: EP-600 Two Part Conductive Epoxy

· UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (SILVER, PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER), 9, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

• Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category E1 Hazardous to the Aquatic Environment

• Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 10)



Printing date 16.09.2022

Version number 4

Revision: 16.09.2022

Trade name: EP-600 Two Part Conductive Epoxy

CAS: Chemical . LC50: Lethal co LD50: Lethal do PBT: Persistent,	Bioaccumulative and Toxic	(Contd. of page 9)
Flam. Liq. 3: Fla Acute Tox. 4: Ac Skin Corr. 1B: S Skin Irrit. 2: Ski Eye Irrit. 2: Seri	stent and very Bioaccumulative mmable liquids – Category 3 ute toxicity – Category 4 kin corrosion/irritation – Category 1B o corrosion/irritation – Category 2 ous eye damage/eye irritation – Category 2 n sensitisation – Category 1	
Muta. 2: Germ c Carc. 2: Carcino STOT SE 3: Spe Aquatic Acute 1. Aquatic Chronic Aquatic Chronic	ell mutagenicity – Category 1 ell mutagenicity – Category 2 genicity – Category 2 ific target organ toxicity (single exposure) – Category 3 Hazardous to the aquatic environment - acute aquatic hazard – Category 1 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	