

Printing date 09/15/2022

Reviewed on 09/15/2022

Identification	
Product identifier	
Trade name: <u>Solvent-10</u> CAS Number: 108-65-6 EC number: 203-603-9 Index number: 607-195-00-7 Application of the substance / the mixture Solvent for thinning and cleaning	
Details of the supplier of the safety data sheet Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818	
Information department:	
Product Safety Email: productsafety@kayakuAM.com Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 Chemtrec International Emergency : 703-527-3887	
Hazard(s) identification	
Classification of the substance or mixture	
Classification of the substance or mixture GHS02 Flame	
GHS02 Flame	and vapor
	and vapor.
GHS02 Flame	and vapor.
GHS02 Flame Flammable Liquids 3 H226 Flammable liquid	
GHS02 Flame Flammable Liquids 3 H226 Flammable liquid GHS07	ness or dizziness.
Flammable Liquids 3       H226 Flammable liquid         Flammable Liquids 3       H226 Flammable liquid         GHS07       GHS07         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsin         Label elements       GHS label elements         The substance is classified and labeled according to the Globally Harmonized	ness or dizziness.
Flammable Liquids 3       H226 Flammable liquid         Flammable Liquids 3       H226 Flammable liquid         GHS07       GHS07         Specific Target Organ Toxicity - Single Exposure 3       H336 May cause drowsin         Label elements       GHS label elements         The substance is classified and labeled according to the Globally Harmonized	ness or dizziness.
$\overbrace{Flammable Liquids 3}$ $Flammable Liquids 3$ $Flammable Liquids$	ness or dizziness.
Flammable Liquids 3       H226 Flammable liquid         Image: Constraint of the state of the substance is classified and labeled according to the Globally Harmonized Hazard pictograms       Hazard pictograms         Image: Constraint of the substance is classified and labeled according to the Globally Harmonized Hazard pictograms       Hazard pictograms         Image: Constraint of the substance is classified and labeled according to the Globally Harmonized Hazard pictograms       Hazard pictograms         Image: Constraint of the substance is classified and labeled according to the Globally Harmonized Hazard pictograms       Hazard pictograms         Image: Constraint of the substance is classified and labeled according to the Globally Harmonized Hazard pictograms       Hazard pictograms         Image: Constraint of the substance is classified and labeled according to the Globally Harmonized Hazard pictograms       Hazard pictograms         Image: Constraint of the substance is classified and labeled according to the Globally Harmonized Hazard pictograms       Hazard pictograms         Image: Constraint of the substance is classified according to the substance is classubstance is classified to the substance is classubstan	ness or dizziness.
$\overbrace{Flammable Liquids 3}$ $Flammable Liquids 3$ $Flammable Liquids$	ness or dizziness.

Safety Data Sheet acc. to OSHA HCS



Printing date 09/15/2022

Reviewed on 09/15/2022

Trade name: Solvent-10

<b></b>	(Contd. of page 1)
Hazard stateme	
	le liquid and vapor.
	e drowsiness or dizziness.
Precautionary s	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P305+P351+P3	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if presen and easy to do. Continue rinsing.
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbor dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internationa regulations.
F	$\begin{aligned} scale \ 0 - 4 \end{aligned}$ $\begin{aligned} tealth &= 0 \\ ire &= 2 \\ eactivity &= 0 \end{aligned}$
HMIS-ratings (	scale 0 - 4)
FIRE 2	Health = 0 Fire = 2 Reactivity = 0
Other hazards	
	and vPvB assessment
<b>PBT:</b> Not applie	
vPvB: Not appli	
Composition/	information on ingredients
Cnemical chara	cterization: Substances

- · CAS No. Description
- 108-65-6 1-Methoxy-2-propanol acetate
- · Identification number(s)
- EC number: 203-603-9
- · Index number: 607-195-00-7

### 4 First-aid measures

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)

US



Printing date 09/15/2022

Reviewed on 09/15/2022

Trade name: Solvent-10

(Contd. of page 2)

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

• Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed Treat symptomatically.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- Alcohol resistant foam
- Fire-extinguishing powder
- ABC powder
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment: Wear SCBA.

### 6 Accidental release measures

	Personal precautions, protective equipment and emergency procedures
	Wear protective equipment. Keep unprotected persons away.
	Ensure adequate ventilation
	Keep away from ignition sources
•	Environmental precautions:
	Dilute with plenty of water.
	Do not allow to enter sewers/ surface or ground water.
•	Methods and material for containment and cleaning up:
	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
•	Reference to other sections
	See Section 7 for information on safe handling.
	See Section 8 for information on personal protection equipment.
	See Section 13 for disposal information.
•	Protective Action Criteria for Chemicals
	PAC-1

• PAC-1:

· PAC-2:

50 ppm

1,000 ppm

(Contd. on page 4)

US —



Printing date 09/15/2022

Reviewed on 09/15/2022

Trade name: Solvent-10

· PAC-3:

(Contd. of page 3)

5000\* ppm

# 7 Handling and storage

#### · Handling:

- **Precautions for safe handling** Prevent formation of aerosols.
- Ensure good ventilation/exhaust at the workplace.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- Protect against electrostatic charges.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- Information about storage in one common storage facility: Do not store together with alkalis (caustic solutions).
- Do not store together with oxidizing and acidic materials.
- Further information about storage conditions:
- Keep container well-sealed in cool, dry location.
- Protect from heat and direct sunlight.
- Store receptacle in a well ventilated area.
- Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- $\cdot$  Components with limit values that require monitoring at the workplace:
- 108-65-6 1-Methoxy-2-propanol acetate
- WEEL Long-term value: 50 ppm
- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material Contact glove manufacture for break-through time.

(Contd. on page 5)




Printing date 09/15/2022

Trade name: Solvent-10

Reviewed on 09/15/2022

(Contd. of page 4)

• Eye protection:



Information on basic physical and c	hemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Characteristic
Odor threshold:	Not determined.
<i>pH-value at 20 °C (68 °F):</i>	4
Change in condition	
Melting point/Melting range:	< -67 °C (< -88.6 °F)
Boiling point/Boiling range:	146.4/1013mbar °C (295.5/1,855.4mbar °F)
Flash point:	46 °C (114.8 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	315 °C (599 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.5 Vol %
Upper:	10.8 Vol %
Vapor pressure at 20 $^{\circ}C$ (68 $^{\circ}F$ ):	5 hPa (3.8 mm Hg)
<i>Density at 20 °C (68 °F):</i>	0.9668 g/cm³ (8.06795 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	1.6-2.3 (BuAc=1)
Solubility in / Miscibility with	
<i>Water at 20 °C (68 °F):</i>	220 g/l
Partition coefficient (n-octanol/wate	<b>r</b> ): Not determined.
Viscosity:	
Dynamic at 20 $^{\circ}C$ (68 $^{\circ}F$ ):	1.2 mPas
Kinematic:	Not determined.
Organic solvents:	100.0 %
VOC content:	100.0 %

(Contd. of page 5)



Safety Data Sheet acc. to OSHA HCS

Printing date 09/15/2022

Reviewed on 09/15/2022

Trade name: Solvent-10

• Other information

No further relevant information available.

### 10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

*Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.* 

- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- Hazardous decomposition products: Carbon monoxide and carbon dioxide

### 11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

108-65-6 1-Methoxy-2-propanol acetate

 Oral
 LD50
 8532 mg/kg (Rat)

 Dermal
 LD50
 >5000 mg/kg (Rat)

Inhalative LC50/6 h 4345 ppm (Rat)

· Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

• Sensitization: No sensitizing effects known.

- Experience with humans: Target Organs: Central nervous system, kidney, liver, lungs
- Additional toxicological information:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

Substance is not listed.

· NTP (National Toxicology Program)

Substance is not listed.

· OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

# 12 Ecological information

· Toxicity

• Aquatic toxicity:

108-65-6 1-Methoxy-2-propanol acetate

ErC50 96 hour >1000 mg/l (Pseudokirchneriella subcapitata (algea))

(Contd. on page 7)

US –



Printing date 09/15/2022

Trade name: Solvent-10

Reviewed on 09/15/2022

(Contd. of page 6)

LC50 408-500 mg/l (daphnia magna)

100-180 mg/l (rainbow trout (Oncorhynchus mykiss))

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· *Bioaccumulative potential* No further relevant information available.

• *Mobility in soil* No further relevant information available.

• Additional ecological information:

· General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

• *PBT:* Not applicable.

• **vPvB:** Not applicable.

· Other adverse effects No further relevant information available.

### 13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number DOT, ADR, IMDG, IATA	UN3272	
UN proper shipping name		
DOT, ADR	Esters, n.o.s. (1-Methoxy-2-propanol acetate)	
IMDG, IATA	ESTERS, N.O.S. (1-Methoxy-2-propanol acetate)	
Class	3 Flammable liquids	
· Label	3	



Printing date 09/15/2022

Reviewed on 09/15/2022

Trade name: Solvent-10

	(Contd. of page
ADR, IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, ADR, IMDG, IATA	111
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-D
Stowage Category	A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
ADR	
Excepted quantities (EQ)	Code: E1
-	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3272 ESTERS, N.O.S. (1-METHOXY-2-PROPANO) ACETATE), 3, III

# 15 Regulatory information

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

• Section 355 (extremely hazardous substances):

Substance is not listed.

· Section 313 (Specific toxic chemical listings):

Substance is not listed.

• TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.

(Contd. on page 9)

<sup>-</sup> US



Printing date 09/15/2022

Reviewed on 09/15/2022

Trade name: Solvent-10

(Contd. of page 8)

· Proposition 65

· Chemicals known to cause cancer:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

Substance is not listed.

• TLV (Threshold Limit Value)

Substance is not listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· New Jersey State Right To Know List

108-65-6 1-Methoxy-2-propanol acetate

· Pennsylvania Hazardous Substances List

108-65-6 1-Methoxy-2-propanol acetate

· California SCAQMD Rule 443.1 VOC's: Not applicable

· GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Warning

· Hazard-determining components of labeling: 1-Methoxy-2-propanol acetate · Hazard statements H226 Flammable liquid and vapor. H336 May cause drowsiness or dizziness. · Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P261 Avoid breathing dust/fume/gas/mist/vapors/spray Wear protective gloves/protective clothing/eye protection/face protection. P280 P301+P310 If swallowed: Immediately call a poison center/doctor. P302+P352 If on skin: Wash with plenty of soap and water. If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for P304+P341 breathing.

(Contd. on page 10)

US



Printing date 09/15/2022

Reviewed on 09/15/2022

Trade name: Solvent-10

	(Contd. of page 9)
P305+P351+P3	38 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon
	dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
· Chomical safety	assassment. A Chemical Safety Assassment has not been carried out

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- · Revision History: The manufacturer's information in Section 1 has been updated. · Date of preparation / last revision 09/15/2022 • Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3