Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 15.05.2020

Printing date 15.05.2020

Version number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- Trade name: UV-3010 UV Curable Coating/Encapsulant
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Encapsulant

 \cdot 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818

Further information obtainable from: Product Safety
Email: productsafety@kayakuAM.com
1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

GHS08 health hazard

Carc. 2

H351 Suspected of causing cancer.

GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life. Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 *H319 Causes serious eye irritation.*

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

EU -

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2020

Version number 2

Revision: 15.05.2020

Trade name: UV-3010 UV Curable Coating/Encapsulant

(Contd. of page 1) · Hazard pictograms GHS07 GHS08 GHS09 · Signal word Warning · Hazard-determining components of labelling: Urethane acrylate oligomer Isobornyl acrylate Benzophenone · Hazard statements H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H335 May cause respiratory irritation. H410 Very toxic to aquatic life with long lasting effects. · Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P302+P352 IF ON SKIN: Wash with plenty of soap and water. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position *P304+P341* comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. *P337+P313* If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Keep container tightly closed. P403+P233 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

	Urethane acrylate oligomer	40-60%
	🐼 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317	
CAS: 5888-33-5	Isobornyl acrylate	25-50%
	♦ <i>Aquatic Acute 1, H400; Aquatic Chronic 1, H410;</i> ♦ <i>Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335</i>	

- EU -



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2020

Version number 2

Revision: 15.05.2020

Trade name: UV-3010 UV Curable Coating/Encapsulant

	(Contd. of page 2)
Aromatic Urethane Acrylate	10-25%
(1) Skin Irrit. 2, H315; Eye Irrit. 2, H319	1
CAS: 28961-43-5 Trimethylolpropane ethoxylate triacrylate	5-15%
Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
Proprietary Resin	5-15%
🚯 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
Proprietary photoinitiator	1-5%
Aquatic Acute 1, H400; Aquatic Chronic 2, H411	1
CAS: 119-61-9 Benzophenone	1-5%
EINECS: 204-337-6 🐼 Carc. 2, H351; 🚯 Aquatic Acute 1, H400; Aquatic Chronic	<i>1, H410</i>
Additional information: For the wording of the listed hazard phrases refer to section	<i>116</i> .

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- After swallowing: Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

(Contd. on page 4)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 2

Revision: 15.05.2020

Trade name: UV-3010 UV Curable Coating/Encapsulant

(Contd. of page 3)

Keep away from ignition sources. · 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. - 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). *Ensure adequate ventilation.* · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.

· Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions). Do not store together with oxidising and acidic materials.

• Further information about storage conditions: Store in cool, dry conditions in well sealed containers. Protect from heat and direct sunlight. Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

(Contd. on page 5)



Printing date 15.05.2020

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2020

Version number 2

Revision: 15.05.2020

Trade name: UV-3010 UV Curable Coating/Encapsulant

(Contd. of page 4)

• **Respiratory protection:** In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

- *The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR*
- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and	l chemical properties	
General Information		
Appearance:		
Form:	Liquid	
Colour:	Clear	
Odour:	Sweetish	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling ran	ge: Undetermined.	
Flash point:	93 °C	
Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not determined.	
Density at 20 °C:	1.15 lbs/gal	
Relative density	Not determined.	
Vapour density	Not determined.	

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2020

Version number 2

Revision: 15.05.2020

Trade name: UV-3010 UV Curable Coating/Encapsulant

		(Contd. of page
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
Solids content:	100 %	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

• 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases

• 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

5888-33-5 Isobornyl acrylate

Oral LD50 4890 mg/kg (Rat)

Dermal LD50 >5000 mg/kg (rabbit)

- · Primary irritant effect:
- Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity
- Suspected of causing cancer.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- STOT-single exposure
- May cause respiratory irritation.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2020

Version number 2

Revision: 15.05.2020

(Contd. of page 6)

Trade name: UV-3010 UV Curable Coating/Encapsulant

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

5888-33-5 Isobornyl acrylate

EC50/48 h 1.1 mg/l (daphnia magna)

Proprietary photoinitiator

EC50/48 h 26 mg/l (daphnia magna)

· 12.2 Persistence and degradability No further relevant information available.

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Very toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

- Very toxic for aquatic organisms • 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA

UN3082

· 14.2 UN proper shipping name · ADR, IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate, Benzophenone)

(Contd. on page 8)

EU -

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2020

Version number 2

Revision: 15.05.2020

Trade name: UV-3010 UV Curable Coating/Encapsulant

	(Contd. of page
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUIE N.O.S. (Isobornyl acrylate, Benzophenone), MARIN POLLUTANT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles. 9
14.4 Packing group ADR, IMDG, IATA	111
14.5 Environmental hazards:	Product contains environmentally hazardous substances Isobornyl acrylate
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number:	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F
Stowage Category	<u>A</u>
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	o f Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml
Transport category Tunnel restriction code	Maximum net quantity per outer packaging: 1000 ml 3 E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (ISOBORNYL ACRYLATE BENZOPHENONE), 9, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• Seveso category E1 Hazardous to the Aquatic Environment

(Contd. on page 9)

⁻ EU -

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.05.2020

Version number 2

Revision: 15.05.2020

Trade name: UV-3010 UV Curable Coating/Encapsulant

(Contd. of page 8)

- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t • Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · National regulations:
- Other regulations, limitations and prohibitive regulations

Kayaku Advanced Materials has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. · Classification according to Regulation (EC) No 1272/2008 Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes. · Department issuing SDS: Product safety department • *Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)* • **Revision History:** The manufacturer information in Section 1 has been updated. · Abbreviations and acronvms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

