

Printing date 09/15/2022 Reviewed on 09/15/2022

1 Identification

- · Product identifier
- · Trade name: UV-939 Curable Fluorescing Dielectric Ink
- · Application of the substance / the mixture Functional electronic insulating ink
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials, Inc.

200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818

· Information department:

Product Safety

Email: productsafety@kayakuAM.com

Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300

Chemtrec International Emergency: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Germ Cell Mutagenicity 1B H340 May cause genetic defects.

Carcinogenicity 1B H350 May cause cancer.



Skin Irrititation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

Flammable Liquids 4 H227 Combustible liquid.
Aquatic Acute 2 H401 Toxic to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07 GHS08

· Signal word Danger

(Contd. on page 2)



Printing date 09/15/2022 Reviewed on 09/15/2022

Trade name: UV-939 Curable Fluorescing Dielectric Ink

(Contd. of page 1)

Hazard-determining components of labeling:

Urethane acrylate oligomer

Proprietary Řesin

Proprietary Defoamer

· Hazard statements

H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H335 May cause respiratory irritation.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2 Fire = 1 Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.



Printing date 09/15/2022 Reviewed on 09/15/2022

Trade name: UV-939 Curable Fluorescing Dielectric Ink

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:	
Urethane acrylate oligomer	60-80%
Skin Irrititation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1B, H317	
Proprietary Resin	25-50%
Skin Irrititation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335; Flammable Liquids 4, H227	1
Proprietary photoinitiator Aquatic Acute 1, H400; Aquatic Chronic 2, H411	1-5%
W 1	1-5%
Acrylic leveling agent �️ Skin Irrititation 2, H315; Eye Irritation 2A, H319	
Proprietary Defoamer Flammable Liquids 3, H226; Acute Toxicity - Inhalation 3, H331; Germ Cell Mutagenicity 1B, H340; Carcinogenicity 1B, H350; Aspiration Hazard 1, H304	<1%
119-61-9 Benzophenone & Carcinogenicity 2, H351; & Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<1%
· Additional Components:	

1 2

Proprietary stabilizer

<1%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

(Contd. on page 4)



Printing date 09/15/2022 Reviewed on 09/15/2022

Trade name: UV-939 Curable Fluorescing Dielectric Ink

(Contd. of page 3)

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear SCBA.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
119-61-9 Benzophenone	1.5 mg/m3
· PAC-2:	
119-61-9 Benzophenone	90 mg/m3
PAC-3:	
119-61-9 Benzophenone	310 mg/m3

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Open and handle container with care.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respirator available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers: No special requirements.
- Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

· Further information about storage conditions:

Keep container well-sealed in cool, dry location.

Protect from heat and direct sunlight.

(Contd. on page 5)



Printing date 09/15/2022 Reviewed on 09/15/2022

Trade name: UV-939 Curable Fluorescing Dielectric Ink

(Contd. of page 4)

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

119-61-9 Benzophenone

WEEL | Long-term value: 0.5 mg/m³

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material Contact glove manufacture for break-through time.
- · Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Hazy-clear
Odor: Sweet

(Contd. on page 6)



Printing date 09/15/2022 Reviewed on 09/15/2022

Trade name: UV-939 Curable Fluorescing Dielectric Ink

		(Contd. of page
Odor threshold:	Not determined.	
pH-value:	Not applicable.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	93 °C (199.4 °F)	
Flammability (solid, gaseous):	Not determined.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not applicable.	
Density:	See other information	
Relative density	Not determined.	
Vapor density	2.6 (air=1)	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
Water:	Insoluble.	
Partition coefficient (n-octanol/wat	(er): Not determined.	
Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
Solvent content:		
Organic solvents:	0.0 %	
Solids content:	100.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide



Printing date 09/15/2022 Reviewed on 09/15/2022

Trade name: UV-939 Curable Fluorescing Dielectric Ink

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 1	values that	are relevant for classification:
Proprietar	y Defoame	er
Oral	LD50	> 6000 mg/kg (Rat)
Dermal	LD50	> 3000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 7.8 mg/l (Rat)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

Carcinogenic.

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
119-61-9 Benzophenone	2B
· NTP (National Toxicology Program)	
None of the ingredients are listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients are listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

Proprietary photoinitiator

EC50/48 h 26 mg/l (daphnia magna)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

(Contd. on page 8)



Printing date 09/15/2022 Reviewed on 09/15/2022

Trade name: UV-939 Curable Fluorescing Dielectric Ink

(Contd. of page 7)

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

UN-Number DOT, ADR, ADN, IMDG, IATA	Not Regulated
UN proper shipping name ADR, ADN, IMDG, IATA	Not Regulated
Transport hazard class(es)	
DOT, ADR, ADN, IMDG, IATA Class	Not Regulated
Packing group DOT, ADR, IMDG, IATA	Not Regulated
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
UN "Model Regulation":	Not Regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.

(Contd. on page 9)



Printing date 09/15/2022 Reviewed on 09/15/2022

Trade name: UV-939 Curable Fluorescing Dielectric Ink

(Contd. of page 8)

· Proposition 65

· Chemicals known to cause cancer:

119-61-9 Benzophenone

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

- · California SCAQMD Rule 443.1 VOC's: No information available.
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Urethane acrylate oligomer

Proprietary Resin

Proprietary Defoamer

· Hazard statements

H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H335 May cause respiratory irritation.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

(Contd. on page 10)



Printing date 09/15/2022 Reviewed on 09/15/2022

Trade name: UV-939 Curable Fluorescing Dielectric Ink

(Contd. of page 9)

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/attention. P333+P313

If eve irritation persists: Get medical advice/attention. P337+P313

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

Store in a well-ventilated place. Keep cool. P403+P235

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- · Revision History: New SDS
- · Date of preparation / last revision 09/15/2022
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids - Category 3

Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Inhalation 3: Acute toxicity - Category 3

Skin Irrititation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

Sensitization - Skin 1B: Skin sensitisation - Category 1B

Germ Cell Mutagenicity 1B: Germ cell mutagenicity - Category 1B

Carcinogenicity 1B: Carcinogenicity - Category 1B

Carcinogenicity 2: Carcinogenicity – Category 2



Printing date 09/15/2022 Reviewed on 09/15/2022

Trade name: UV-939 Curable Fluorescing Dielectric Ink

(Contd. of page 10)

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

Aspiration Hazard 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3