

Printing date 03/30/2020

Reviewed on 03/30/2020

1 Identification

- **Product identifier**
- **Trade name:** *UV-1006S UV Curable Dielectric*
- **Application of the substance / the mixture** *Screen printing ink*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Kayaku Advanced Materials, Inc.
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818
- **Information department:**
 Product Safety
 Email: productsafety@kayakuAM.com
- **Emergency telephone number:**
 Kayaku Advanced Materials : 617-965-5511
 Chemtrec USA Emergency : 800-424-9300
 Chemtrec International Emergency : 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS07

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

Polyester Resin

Epoxide Monomer

Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2020

Reviewed on 03/30/2020

Trade name: UV-1006S UV Curable Dielectric

(Contd. of page 1)

· Hazard statements

- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H317 May cause an allergic skin reaction.
- H402 Harmful to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P302+P352 If on skin: Wash with plenty of soap and water.
- P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:
· NFPA ratings (scale 0 - 4)

· HMIS-ratings (scale 0 - 4)

· Other hazards
· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures
· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

	Polyester Resin ⚠ Eye Dam. 1, H318	40-60%
	Epoxide Monomer ⚠ Eye Irrit. 2A, H319; Skin Sens. 1B, H317	25-50%
25085-96-8	Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317; Aquatic Acute 2, H401	10-25%

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/30/2020

Reviewed on 03/30/2020

Trade name: UV-1006S UV Curable Dielectric

(Contd. of page 2)

4 First-aid measures**· Description of first aid measures****· General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.**· After eye contact:**

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures**· Extinguishing media****· Suitable extinguishing agents:**

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

· For safety reasons unsuitable extinguishing agents: Water with full jet

· Special hazards arising from the substance or mixture No further relevant information available.

· Advice for firefighters

· Protective equipment: Wear SCBA.

6 Accidental release measures**· Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

Printing date 03/30/2020

Reviewed on 03/30/2020

Trade name: UV-1006S UV Curable Dielectric

(Contd. of page 3)

· Protective Action Criteria for Chemicals
· PAC-1:

None of the ingredients are listed.

· PAC-2:

None of the ingredients are listed.

· PAC-3:

None of the ingredients are listed.

7 Handling and storage
· Handling:
· Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities
· Storage:
· Requirements to be met by storerooms and containers: No special requirements.
· Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

· Further information about storage conditions: None.
· Specific end use(s) No further relevant information available.
8 Exposure controls/personal protection
· Additional information about design of technical systems: No further data; see item 7.
· Control parameters
· Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists that were valid during the creation were used as basis.
· Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

(Contd. on page 5)

Printing date 03/30/2020

Reviewed on 03/30/2020

Trade name: UV-1006S UV Curable Dielectric

(Contd. of page 4)

 · **Protection of hands:**


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

 · **Material of gloves** Nitrile rubber, NBR

 · **Penetration time of glove material** Contact glove manufacture for break-through time.

 · **Eye protection:**


Tightly sealed goggles

9 Physical and chemical properties

 · **Information on basic physical and chemical properties**

 · **General Information**

 · **Appearance:**

Form:	Liquid
Color:	Clear to light yellow
Odor:	Acrylic-like
Odor threshold:	Not determined.

 · **pH-value:** Not determined.

 · **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

 · **Flash point:** >100 °C (>212 °F)

 · **Flammability (solid, gaseous):** Not applicable.

 · **Decomposition temperature:** Not determined.

 · **Auto igniting:** Product is not selfigniting.

 · **Danger of explosion:** Product does not present an explosion hazard.

 · **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

 · **Vapor pressure:** Not determined.

Density:	See other information
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	1.6-2.3 (BuAc=1)

 · **Solubility in / Miscibility with Water:**

Water miscible No

 · **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2020

Reviewed on 03/30/2020

Trade name: UV-1006S UV Curable Dielectric

(Contd. of page 5)

· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
· Solids content:	
Other information	100 % No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
Heat, flames and sparks. Extremes of temperature and direct sunlight.
Contact with incompatible materials.
- **Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program)
--

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)
--

None of the ingredients are listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2020

Reviewed on 03/30/2020

Trade name: UV-1006S UV Curable Dielectric

(Contd. of page 6)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.
Disposal must be made in accordance with Federal, State, and Local regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made in accordance with Federal, State, and Local regulations.

14 Transport information

· UN-Number	
· DOT, ADR, ADN, IMDG, IATA	Not Regulated
· UN proper shipping name	
· ADR, ADN, IMDG, IATA	Not Regulated
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not Regulated
· Packing group	
· DOT, ADR, IMDG, IATA	Not Regulated
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	Not Regulated

(Contd. on page 8)

Printing date 03/30/2020

Reviewed on 03/30/2020

Trade name: UV-1006S UV Curable Dielectric

(Contd. of page 7)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):** All ingredients are listed or comply with TSCA regulations.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients are listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients are listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **California SCAQMD Rule 443.1 VOC's:** No information available.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Polyester Resin

Epoxide Monomer

Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers

· **Hazard statements**

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2020

Reviewed on 03/30/2020

Trade name: UV-1006S UV Curable Dielectric

(Contd. of page 8)

· **Precautionary statements**

- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P302+P352 If on skin: Wash with plenty of soap and water.
- P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Other regulations, limitations and prohibitive regulations**

Kayaku Advanced Materials has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department

· **Contact:** Tom Cole, EHS Manager (tcole@kayakuAM.com)

· **Revision History:** The manufacturer's information in Section 1 has been updated.

· **Date of preparation / last revision** 03/30/2020 / 1

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/30/2020

Reviewed on 03/30/2020

Trade name: UV-1006S UV Curable Dielectric

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. of page 9)

US