Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 30.03.2020

Printing date 30.03.2020

Version number 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: UV-2530 UV Curable Matte Dielectric

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

- Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Functional electronic insulating ink

 \cdot 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818

Further information obtainable from: Product Safety
Email: productsafety@kayakuAM.com
1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. • Hazard pictograms



· Signal word Warning

• Hazard-determining components of labelling: Urethane acrylate oligomer Proprietary Resin Proprietary Dye

(Contd. on page 2)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version number 3

Revision: 30.03.2020

Trade name: UV-2530 UV Curable Matte Dielectric

(Contd. of page 1) · Hazard statements H315 Causes skin irritation. H319 Causes serious eve irritation. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects. · Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210 smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P273 Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. P280 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. IF ON SKIN: Wash with plenty of soap and water. P302+P352 *P304+P341* IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. *P333+P313* P337+P313 If eye irritation persists: Get medical advice/attention. P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment

· **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

	Urethane acrylate oligomer	40-60%
	🚸 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317	
	Proprietary Resin	25-50%
	𝚯 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
	Proprietary photoinitiator	1-5%
	Aquatic Acute 1, H400; Aquatic Chronic 2, H411	
	Acrylic leveling agent	1-5%
	🚯 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
	Proprietary Dye	<1%
	🚯 Eye Irrit. 2, H319; Skin Sens. 1A, H317	
CAS: 119-61-9	Benzophenone	<1%
EINECS: 204-337-6	Scarc. 2, H351; 🚱 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	



Printing date 30.03.2020

Version number 3

Revision: 30.03.2020

Trade name: UV-2530 UV Curable Matte Dielectric

· Additional Components:

CAS: 14807-96-6 Talc (Mg3H2(SiO3)4) EINECS: 238-877-9

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air and to be sure call for a doctor.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



(Contd. of page 2)

10-25%

EU・



Printing date 30.03.2020

Version number 3

Revision: 30.03.2020

(Contd. of page 3)

Trade name: UV-2530 UV Curable Matte Dielectric

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and containers: No special requirements.

- · Information about storage in one common storage facility:
- Store away from reducing agents. Store away from oxidising agents.
- Further information about storage conditions: Store in cool, dry conditions in well sealed containers. Protect from heat and direct sunlight. Store receptacle in a well ventilated area.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version number 3

Revision: 30.03.2020

Trade name: UV-2530 UV Curable Matte Dielectric

(Contd. of page 4)

· Material of gloves Nitrile rubber, NBR

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and c	hemical properties	
General Information Appearance:		
Form:	Liquid	
Colour:	Matte - Green, Blue, Clear	
Odour:	Sweetish	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range	: Undetermined.	
Flash point:	93 °C	
Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not determined.	
Density:	Not determined.	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version number 3

Revision: 30.03.2020

Trade name: UV-2530 UV Curable Matte Dielectric

	(Contd. of page 5)
· Solvent content: Organic solvents:	0.0 %
Solids content: • 9.2 Other information	100 % No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.
- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure
- May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

Proprietary photoinitiator

EC50/48 h 26 mg/l (daphnia magna)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)

— EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

ADVANCED MATERIALS

Version number 3

Revision: 30.03.2020

(Contd. of page 6)

Trade name: UV-2530 UV Curable Matte Dielectric

· Ecotoxical effects:

- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

• Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR, IATA IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUII N.O.S. (2,2-dimethoxy-2-phenylacetophenone, Benzophenone) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUII N.O.S. (2,2-dimethoxy-2-phenylacetophenone, Benzophenone MARINE POLLUTANT
ADR, IMDG, IATA	9 Miscellaneous dangerous substances and articles.
	9 Miscellaneous dangerous substances and articles. 9 111
Class Label 14.4 Packing group	9



Revision: 30.03.2020

Printing date 30.03.2020

Version number 3

Trade name: UV-2530 UV Curable Matte Dielectric

	(Contd. of page 7)
· Hazard identification number (Kemler code):	90
• EMS Number:	F-A,S-F
· Stowage Category	A
· 14.7 Transport in bulk according to Annex II o	f
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
·ADR	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
• Transport category	3
• Tunnel restriction code	E
·IMDG	
· Limited quantities (LQ)	5L
• Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2, 2 - DIMETHOXY-2 - PHENYLACETOPHENONE, BENZOPHENONE), 9, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

- · National regulations:
- Other regulations, limitations and prohibitive regulations

Kayaku Advanced Materials has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation. H317 May cause an allergic skin reaction.

(Contd. on page 9)

EU

Revision: 30.03.2020

Printing date 30.03.2020

Version number 3

Trade name: UV-2530 UV Curable Matte Dielectric

	(Contd. of page 8)
H319 Causes serious eye irritation.	
H335 May cause respiratory irritation.	
H351 Suspected of causing cancer.	
H400 Very toxic to aquatic life.	
H410 Very toxic to aquatic life with long lasting effects.	
H411 Toxic to aquatic life with long lasting effects.	
Classification according to Regulation (EC) No 1272/2008	
Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.	
Department issuing SDS: Product safety department	
Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)	
Revision History: The manufacturer information in Section 1 has been updated.	
Abbreviations and acronyms:	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement c	on company the International
Carriage of Dangerous Goods by Road)	oncerning the international
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
<i>Eye Irrit. 2: Serious eye damage/eye irritation – Category 2</i>	
Skin Sens. 1: Skin sensitisation – Category 1	
Skin Sens. 1A: Skin sensitisation – Category 1A	
Skin Sens. 1B: Skin sensitisation – Category 1B	
Carc. 2: Carcinogenicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1	

