

Printing date 10.03.2020 Version number 2 Revision: 10.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: WB-101 Water-Based Silver Conductive Ink
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Application of the substance / the mixture Film coating
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Kayaku Advanced Materials, Inc.

200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818

Further information obtainable from:

Product Safety

Email: productsafety@kayakuAM.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Repr. 1B H360 May damage fertility or the unborn child.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 10.03.2020 Version number 2 Revision: 10.03.2020

Trade name: WB-101 Water-Based Silver Conductive Ink

(Contd. of page 1)

· Hazard pictograms







GHS07

GHS08

GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Urethane acrylate oligomer N-methyl-2-pyrrolidinone

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Restricted to professional users.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 7440-22-4	Silver	60-80%
EINECS: 231-131-3	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

(Contd. on page 3)



Printing date 10.03.2020 Version number 2 Revision: 10.03.2020

Trade name: WB-101 Water-Based Silver Conductive Ink

		(Con	ntd. of page
	Urethane acrylate oligo		5-15%
	♦ Skin Irrit. 2, H315; I	Eye Irrit. 2, H319; Skin Sens. 1B, H317	-]
CAS: 872-50-4	N-methyl-2-pyrrolidinor	ne e	1-5%
EINECS: 212-828-1 Index number: 606-02	Acute Tox. 3, H331; 21-00-7 Eye Irrit. 2, H319; STO	♦ Repr. 1B, H360D; ♦ Skin Irrit. 2, H315; T SE 3, H335	
· Additional Componer	nts:		
CAS: 7732-18-5 EINECS: 231-791-2	Water		10-25%
CAS: 577-11-7 EINECS: 209-406-4	Dioctyl sodium sulfosuccinate	♦ Acute Tox. 4, H302; Eye Irrit. 2, H319	<1%
· SVHC		•	•
872-50-4 N-methyl-2	-pyrrolidinone		
	**	hazard phrases refer to section 16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

ABC powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

(Contd. on page 4)



Printing date 10.03.2020 Version number 2 Revision: 10.03.2020

Trade name: WB-101 Water-Based Silver Conductive Ink

(Contd. of page 3)

• 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Protect against electrostatic charges.

Keep ignition sources away - Do not smoke.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

 \cdot 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

872-50-4 N-methyl-2-pyrrolidinone

IOELV Short-term value: 80 mg/m³, 20 ppm Long-term value: 40 mg/m³, 10 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)



Printing date 10.03.2020 Version number 2 Revision: 10.03.2020

Trade name: WB-101 Water-Based Silver Conductive Ink

· Protection of hands:

(Contd. of page 4)



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties	
· General Information · Appearance:	
Form:	Liquid
Colour:	Silver-coloured
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. Undetermined.
· Flash point:	94 °C
· Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.

(Contd. on page 6)



Printing date 10.03.2020 Version number 2 Revision: 10.03.2020

Trade name: WB-101 Water-Based Silver Conductive Ink

		(Contd. of page
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	1 - 5 %	
Water:	10 - 25 %	
Solids content:	78 - 82 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:	
872-50-4 N	872-50-4 N-methyl-2-pyrrolidinone	
Oral	LD50	3914 mg/kg (Rat)
Dermal	LD50	8000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5.0 mg/l (Rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

May cause skin irritation

Causes skin irritation.

- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 10.03.2020 Version number 2 Revision: 10.03.2020

Trade name: WB-101 Water-Based Silver Conductive Ink

(Contd. of page 6)

· Reproductive toxicity

May damage fertility or the unborn child.

- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

7440-22-4 Silver

LC50/96 h (static) 0.0062 mg/l (Lepomis macrochirus (Bluegill))

0.00155-0.00293 mg/l (Pimephales promelas)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

	SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN3082	
· 14.2 UN proper shipping name		
$\cdot ADR$	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUII	
	N.O.S. (Silver)	
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUII	
	N.O.S. (Silver), MARINE POLLUTANT	
· IATA	Environmentally hazardous substance, liquid, n.o.s. (Silver)	



Printing date 10.03.2020 Version number 2 Revision: 10.03.2020

Trade name: WB-101 Water-Based Silver Conductive Ink

	(Contd. of page
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	9 Miscellaneous dangerous substances and articles.
Label	9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances: Silv
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Hazard identification number (Kemler code):	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Transport in bulk according to Annex II	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN ''Model Regulation'':	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC
	LIQUID, N.O.S. (SILVER), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E1 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 30, 71, 72

(Contd. on page 9)



Printing date 10.03.2020 Version number 2 Revision: 10.03.2020

Trade name: WB-101 Water-Based Silver Conductive Ink

(Contd. of page 8)

- · National regulations:
- · Other regulations, limitations and prohibitive regulations

Kayaku Advanced Materials has confirmed with our precious metal suppliers that they do not use conflict minerals, as outlined in the Dodd-Frank Wall Street Reform and Consumer Protection Act in Title XV, Section 1502.

· Substances of very high concern (SVHC) according to REACH, Article 57

872-50-4 N-methyl-2-pyrrolidinone

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H360D May damage the unborn child.
- H400 Very toxic to aquatic life.
- *H410 Very toxic to aquatic life with long lasting effects.*
- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- · Revision History: The manufacturer information in Section 1 has been updated.
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - inhalation - Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 1B: Reproductive toxicity – Category 1B

Repr. 1B: Reproductive toxicity - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1