

Printing date 10/07/2020

1 Identification

· Product identifier

- Trade name: <u>KMPR® 2000 Series Resists</u>
- **Product number:** Y212064, Y212045, Y212031, Y212020 • **Application of the substance / the mixture** Photoresist
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Kayaku Advanced Materials, Inc.
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818
- Information department: Product Safety Email: productsafety@kayakuAM.com • Emergency telephone number: Kayaku Advanced Materials : 617-965-5511
- Chemtrec USA Emergency : 800-424-9300 Chemtrec International Emergency : 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



Flam. Liq. 3 H226 Flammable liquid and vapor.

GHS07

Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Warning

 Hazard-determining components of labeling: Epoxy Resin (CAS Proprietary)
 1-methoxy-2-propanol
 Cyclopentanone
 Hazard statements
 H226 Flammable liquid and vapor. Reviewed on 10/07/2020

(Contd. on page 2)



Printing date 10/07/2020

Reviewed on 10/07/2020

Trade name: KMPR® 2000 Series Resists

11 aue name. Mil 1	A 2000 Series Resists
	(Contd. of page 1)
H315 Causes sk	kin irritation.
H319 Causes se	prious eye irritation.
· Precautionary s	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P305+P351+P	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	<i>If eye irritation persists: Get medical advice/attention.</i>
P370+P378	In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378	In case of fire: Use for extinction: Fire-extinguishing powder.
P370+P378	In case of fire: Use for extinction: Carbon dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international
Additional info	regulations.
• Additional info	
	ixture consists of component(s) of unknown toxicity.
Classification s	
· NFPA ratings (scale 0 - 4)
	Iealth = 2
	ire = 3
	Peactivity = 0
• HMIS-ratings ((scale 0 - 4)
HEALTH 2	Health = 2
	Fire = 3
REACTIVITY 0	Reactivity = 0
• Other hazards	
	and vPvB assessment
• PBT: Not appli	
• vPvB: Not appl	
3 Composition	/information on ingredients
· Chemical char	acterization: Mixtures
	ixture of the substances listed below with nonhazardous additions.
-	
· Dangerous con	-

 • Dangerous components:
 30-80%

 120-92-3
 Cyclopentanone
 30-80%

 • Flam. Liq. 3, H226; • Skin Irrit. 2, H315; Eye Irrit. 2A, H319
 30-80%

 107-98-2
 1-methoxy-2-propanol
 2-8%

 • Flam. Liq. 3, H226; • STOT SE 3, H336
 (Contd. on page 3)



Printing date 10/07/2020

Reviewed on 10/07/2020

Trade name: KMPR® 2000 Series Resists

108-32-7 Propylene carbonate	(Contd. of page 2) 1-5%
Proprietary Photo Acid Generator	<1%
· Additional Components:	
Epoxy Resin (CAS Proprietary)	15-60%

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

• After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- Alcohol resistant foam Fire-extinguishing powder Carbon dioxide
- For safety reasons unsuitable extinguishing agents: Water with full jet Water
- Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- Advice for firefighters
- · Protective equipment: Wear SCBA.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

US -



Printing date 10/07/2020

Reviewed on 10/07/2020

Trade name: KMPR® 2000 Series Resists

(Contd. of page 3)

• *Environmental precautions:* Do not allow to enter sewers/surface or ground water. • *Methods and material for containment and cleaning up:*

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Keep away from heat and direct sunlight. Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Use explosion-proof apparatus / fittings and spark-proof tools. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- **Requirements to be met by storerooms and containers:** Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles. Store in a cool location.
- Information about storage in one common storage facility: Do not store together with amines.
 Do not store together with alkalis (caustic solutions).
 Do not store together with oxidizing and acidic materials.
 Further information about storage conditions:
- Further information about storage conditions:
- Protect from exposure to the light.
- Keep container tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

REL Short-term value: 540 mg/m³, 150 ppm

Long-term value: 360 mg/m³, 100 ppm

TLV Short-term value: 369 mg/m³, 100 ppm Long-term value: 184 mg/m³, 50 ppm

Long-term value: 184 mg/m³, 30 ppm

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

US –



Printing date 10/07/2020

Reviewed on 10/07/2020

Trade name: KMPR® 2000 Series Resists

(Contd. of page 4)

· Exposure controls
Personal protective equipment:
General protective and hygienic measures:
Do not eat or drink while working.
Keep away from food and beverages.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin. • Respiratory equipment:
In the case of vapour formation use a NIOSH approved respirator with filter for organic vapour.
• Protection of hands:
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
· Material of gloves
Nitrile rubber, NBR
Butyl rubber, BR
• Penetration time of glove material Contact glove manufacture for break-through time.
· Eye protection:
Tightly sealed goggles

9 Physical and chemical properties

General Information		
Appearance:		
Form:	Fluid	
Color:	Light yellow	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	130 °C (266 °F)	
Flash point:	30 °C (86 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	270 °C (518 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	



Printing date 10/07/2020

Reviewed on 10/07/2020

Trade name: K	<i>MPR</i> ® 2000	Series Resists	
---------------	-------------------	----------------	--

				(Contd. of	f page :
Danger of explosion:	Product is not ex mixtures are possi	•	, formation oj	f explosive air/	vapo
Explosion limits:					
Lower:	1.3 Vol %				
Upper:	Not determined.				
Vapor pressure at 20 °C (68 °F):	11 hPa (8.3 mm H	g)			
Density:	Not determined.				
Relative density	See Table 1 Other	Information			
Vapor density	Not determined.				
Evaporation rate	Not determined.				
Solubility in / Miscibility with					
Water:	Water miscible No				
Partition coefficient (n-octanol/wate	e r): Not determined.				
Viscosity:					
Dynamic:	Not determined.				
Kinematic:	Not determined.				
Solvent content:					
VOC content:	435-790 g/l				
Other information	Table 1. Product s	pecific gravity and	l VOC data.		
	Name	Product No.	Sp. Gravity	Vol (% by wt.)	VO
	(g/L)		1 2		
	KMPR 2001	Y212020	0.99	78-81	790
	KMPR 2002	Y212031	1.03	68-70	710
	KMPR 2005	Y212045	1.06	54-56	585
	KMPR 2025	Y212064	1.20	35-38	435

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Exothermic polymerization.
- · Conditions to avoid
- Heat, flames and sparks. Extremes of temperature and direct sunlight.
- Contact with incompatible materials.
- · Incompatible materials: Strong Oxidizing Agents, Strong Bases, Strong Acids, Amines
- Hazardous decomposition products: Carbon monoxide and carbon dioxide
- Corrosive gases/vapors
- Danger of toxic pyrolysis products.

(Contd. on page 7)

US



Printing date 10/07/2020

Trade name: KMPR® 2000 Series Resists

Reviewed on 10/07/2020

(Contd. of page 6)

Information Acute toxi		cological effects
	-	t are relevant for classification:
120-92-3 (Cyclopenta	none
Oral	LD50	1820 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>19.5 mg/l (Rat)
107-98-2	-methoxy-	-2-propanol
Oral	LD50	5660 mg/kg (Rat)
Dermal	LD50	13000 mg/kg (rabbit)
		54.6 mg/l (Rat)
108-32-71	Propylene	
Oral	LD50	>29000 mg/kg (Rat)
Dermal	LD50	>20,000 mg/kg (rabbit)
Irritant Carcinoge	-	
		Agency for Research on Cancer)
None of th	e ingredier	nts are listed.
		cology Program)
None of th	e ingredier	nts are listed.
	· -	ional Safety & Health Administration)
None of th	e ingredier	nts are listed.
Ecologic	al inform	nation
-		
Toxicity Aquatic to	xicity:	

EC50/72 h >100 mg/l (scenedesmus subspicatus)

LC50/48 hr 2950 mg/L (golden orfe)

LC50/96 h >100 mg/l (fish)

(Contd. on page 8)

US -



Printing date 10/07/2020

Trade name: KMPR® 2000 Series Resists

Reviewed on 10/07/2020

(Contd. of page 7)

107-98-2 1-methoxy-2-propanol EC50/96 hr 23300 mg/l (daphnia magna)

>1000 mg/l (green algae)

LC50/96 h 20800 mg/l (Pimephales promelas)

108-32-7 Propylene carbonate

EC50/17 h >10000 mg/l (Pseudomonas putida)

EC50/48 h >500 mg/l (daphnia magna)

EC50/72 h >500 mg/l (scenedesmus subspicatus)

LC50/96 h 2200 mg/l (Leuciscus idus)

· Persistence and degradability No further relevant information available.

- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

UN-Number		
DOT, ADR, IMDG, IATA	UN1866	
UN proper shipping name		
DOT, ADR	Resin solution	
IMDG, IATA	RESIN SOLUTION	
Transport hazard class(es)		
DOT		
Class	3 Flammable liquids	



Printing date 10/07/2020

Reviewed on 10/07/2020

Trade name: KMPR® 2000 Series Resists

	(Contd. of page
Label	3
ADR, IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, ADR, IMDG, IATA	111
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code EMS Number:	F-E,S-E
Stowage Category	A
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 50 mi Maximum net quantity per outer packaging: 1000 ml
	UN1866, Resin solution, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

• Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

This product is intended solely for export per 40 CFR §720.30(e) of the Toxic Substances Control Act (TSCA). • *Proposition 65*

Chemicals known to cause cancer:

None of the ingredients are listed.

(Contd. on page 10)

US –



Printing date 10/07/2020

Reviewed on 10/07/2020

Trade name: KMPR® 2000 Series Resists

(Contd. of page 9)

- Chemicals known to cause reproductive toxicity for females:
- None of the ingredients are listed.
- · Chemicals known to cause reproductive toxicity for males:
- None of the ingredients are listed.
- Chemicals known to cause developmental toxicity:
- None of the ingredients are listed.
- · Carcinogenic categories
- · EPA (Environmental Protection Agency)
- None of the ingredients are listed.
- · TLV (Threshold Limit Value established by ACGIH)
- None of the ingredients are listed.
- · NIOSH-Ca (National Institute for Occupational Safety and Health)
- None of the ingredients are listed.
- · Massachusetts State Right To Know List
- 120-92-3 Cyclopentanone
- 107-98-2 1-methoxy-2-propanol
- · New Jersey State Right To Know List
- 120-92-3 Cyclopentanone
- 107-98-2 1-methoxy-2-propanol
- · Pennsylvania Hazardous Substances List
- 120-92-3 Cyclopentanone
- 107-98-2 1-methoxy-2-propanol
- · California SCAQMD Rule 443.1 VOC's: See Table 1 Section 9
- *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Warning

· Hazard-determini	ing components of labeling:
Epoxy Resin (CAS	Proprietary)
1-methoxy-2-prop	anol
Cyclopentanone	
· Hazard statement	S
H226 Flammable	liquid and vapor.
H315 Causes skin	irritation.
H319 Causes serie	ous eye irritation.
· Precautionary sta	tements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.

(Contd. on page 11)

[—] US



Printing date 10/07/2020

Reviewed on 10/07/2020

Trade name: KMPR® 2000 Series Resists

	(Contd. of page 10)
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P305+P351+P33	8 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378	In case of fire: Use for extinction: Fire-extinguishing powder.
P370+P378	In case of fire: Use for extinction: Carbon dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
~	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

• Date of preparation / last revision 10/07/2020 / 1

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)
- VOC: Volatile Organic Compounds (USA,
- *LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent*
- *PBT: Persistent, Bioaccumulative and Toxic*
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- Flam. Liq. 3: Flammable liquids Category 3
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- *Eye Irrit. 2A: Serious eye damage/eye irritation Category 2A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*
