

Printing date 04.04.2025

Version number 9

Revision: 04.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

• Article number: G040100

• 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- Product category PC21 Laboratory chemicals
- · Application of the substance / the mixture Solvents

• 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier:

Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818

The appointed Only Representative* for the United Kingdom (UK): H2 COMPLIANCE UK Ltd, Mazars Tower Bridge House, St Katharine's Way, St Katharine's & Wapping, London, United Kingdom E1W 1DD Tel: +353-21-4868120 Email: info@h2compliance.com

*Only Representative for 1,3-dioxolane (EINICS 211-463-5, CAS 646-06-0) only. Other substances are being supported under UK- REACH by Only Representatives of Non-UK suppliers and others may be exempt from registration.

Further information obtainable from: Product Safety
Email: productsafety@kayakuam.com
1.4 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr) Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS

GHS08 health hazard

Repr. 1B H360FD May damage fertility. May damage the unborn child.

(Contd. on page 2)

⁻ GB



Revision: 04.04.2025

Printing date 04.04.2025

Version number 9

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

(Contd. of page 1) GHS05 corrosion Eye Dam. 1 H318 Causes serious eye damage. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms GHS02 GHS05 GHS08 · Signal word Danger · Hazard-determining components of labelling: 1,3-dioxolane · Hazard statements H225 Highly flammable liquid and vapour. H318 Causes serious eye damage. H360FD May damage fertility. May damage the unborn child. · Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210 smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P263 Avoid contact during pregnancy and while nursing. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P302+P352 IF ON SKIN: Wash with plenty of soap and water. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position P304+P341 comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. *P333+P313* If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. *P337+P313* P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable.

(Contd. on page 3)



Printing date 04.04.2025

Version number 9

Revision: 04.04.2025

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• **Description:** Solvent mixture

· Dangerous components:			
	-,	98-99.5%	
EINECS: 211-463-5	🚸 Flam. Liq. 2, H225; 🚸 Repr. 1B, H360FD; 🔣 Eye Dam. 1, H318		
	1-methoxy-2-propanol	0.5-2%	
EINECS: 203-539-1	🚸 Flam. Liq. 3, H226; 🜗 STOT SE 3, H336		
Additional information. For the wording of the listed hazard phrases refer to section 16			

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• *General information: Immediately remove any clothing soiled by the product.*

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• *After swallowing:* If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- Alcohol resistant foam Fire-extinguishing powder
- Carbon dioxide
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture In case of fire, the following can be released:
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

GB



Printing date 04.04.2025

Version number 9

Revision: 04.04.2025

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

(Contd. of page 3)

• 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and containers:

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products. Store in a cool location.

• Information about storage in one common storage facility: Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions).

• Further information about storage conditions: Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

• *Additional information:* The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

(Contd. on page 5)



Revision: 04.04.2025

Printing date 04.04.2025

Version number 9

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eves and skin. (Contd. of page 4)

• Respiratory protection: In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. · Material of gloves Butyl rubber, BR Nitrile rubber, NBR · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. • Eye protection: Tightly sealed goggles · Body protection: Long-sleeved work clothes **SECTION 9:** Physical and chemical properties • 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Colour: Clear to light yellow **Odour:** Characteristic • Odour threshold: Not determined. · pH-value: Not determined. Change in condition -26.4 °C Melting point/freezing point: *Initial boiling point and boiling range:* 75 °C · Flash point: -6 °C · Flammability Not applicable. 274 °C • Auto-ignition temperature: • Decomposition temperature: Not determined. · Ignition temperature: Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour · Explosive properties: mixtures are possible. (Contd. on page 6) GR

GB



Safety data sheet according to UK REACH

Printing date 04.04.2025

Version number 9

Revision: 04.04.2025

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

	(Contd. of page .
• Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure at 20 °C:	133 hPa
Density at 20 °C:	1.0355 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Polymerisation. Possible formation of peroxide.

· 10.4 Conditions to avoid

Contact with incompatible materials.

Heat, flames and sparks. Extremes of temperature and direct sunlight.

• 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases

- · 10.6 Hazardous decomposition products:
- Formaldehyde

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
646-06-0 1	1,3-dioxol	lane
Oral	LD50	3000 mg/kg (Rat)
Dermal	LD50	8480 mg/kg (rabbit)
Inhalative	LC50	68.4 mg/L (Rat)
107-98-21	-methoxy	y-2-propanol
Oral	LD50	5660 mg/kg (Rat)
	•	(Contd. on page 7)



Printing date 04.04.2025

Version number 9

Revision: 04.04.2025

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

L				(Contd. of page 6
	Dermal	LD50	13000 mg/kg (rabbit)	
	Inhalative	LC50/4 h	54.6 mg/l (Rat)	
	· Primary i	rritant effe	ct:	
l	· Skin corr	osion/irrita	tion Based on available data, the classification criteria are not met.	
	· Serious e	/e damage	<i>irritation</i>	

Causes serious eye damage.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

- Experience with humans: No further relevant information available.
- Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity
- May damage fertility. May damage the unborn child.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity: 646-06-0 1,3-dioxolane

14 day NOEC > 1000 mg/l (algae)LC50/48 hr 12000 mg/L (Sheepshead minnow) 107-98-2 1-methoxy-2-propanol EC50/96 hr 23300 mg/l (daphnia magna) >1000 mg/l (green algae) LC50/96 h 20800 mg/l (Pimephales promelas) · 12.2 Persistence and degradability The single components are biodegradable · 12.3 Bioaccumulative potential Due to the distribution coefficient n-octanol/water a worth-mentioning accumulation in organisms is not expected. · 12.4 Mobility in soil Component: Propylene glycol monomethyl ether, rapid dissipation in soil expected. Koc value between 1 and 50 indicating very high soil mobility. · Additional ecological information: · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. · 12.5 Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 8)



Printing date 04.04.2025

Version number 9

Revision: 04.04.2025

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

(Contd. of page 7)

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1166
· 14.2 UN proper shipping name · ADR, IMDG, IATA	DIOXOLANE
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	II
 14.5 Environmental hazards: Marine pollutant: 	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
 Hazard identification number (Kemler code): EMS Number: 	33 F-E,S-D
• 14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	of Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code	1L 2 D/E
· UN "Model Regulation":	UN1166, DIOXOLANE, 3, II

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 9)

GB –



Printing date 04.04.2025

Version number 9

Revision: 04.04.2025

Trade name: EBR DC Positive Radiation Resist Edge Bead Remover

(Contd. of page 8)

GB

·	Poisons	Act
---	---------	-----

• Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H360FD May damage fertility. May damage the unborn child.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Repr. 1B: Reproductive toxicity - Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3