

Printing date 19.12.2024 Version number 2 (replaces version 1) Revision: 19.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: KMPR® 3000 Series Resists
- · Article number: Y214020, Y214031, Y214043, Y214045, Y214051, Y214055, Y214060, Y214062, Y214064
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · **Product category** PC30 Photo-chemicals
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials, Inc.

200 Flanders Road

Westborough, MA 01581

Tel: (617) 965-5511 Fax: (617) 965-5818

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuam.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

(Contd. on page 2)



Printing date 19.12.2024 Version number 2 (replaces version 1) Revision: 19.12.2024

Trade name: KMPR® 3000 Series Resists

(Contd. of page 1)

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

44.8 % of the mixture consists of component(s) of unknown toxicity.

Contains 44.8 % of components with unknown hazards to the aquatic environment.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

Determination of endocrine-disrupting properties

None of the ingredients are included in the list established in accordance with Article 59(1) for having endocrine disrupting properties.

None of the ingredients are substances identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	Cyclopentanone Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2, H319	25-75%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	1-10%
CAS: 108-32-7 EINECS: 203-572-1 Index number: 607-194-00-1	Propylene carbonate Skin Irrit. 2, H315; Eye Irrit. 2, H319	0.25-3%

(Contd. on page 3)



Printing date 19.12.2024 Version number 2 (replaces version 1) Revision: 19.12.2024

Trade name: KMPR® 3000 Series Resists

	(Con	td. of page 2)
	6 =	0.25-3%
EINECS: 202-509-5	♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; STOT SE 3, H336	
· Additional Components:		
Proprietary Epoxy Resin		15-65%
Proprietary Photoacid Generator		<1%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Printing date 19.12.2024 Version number 2 (replaces version 1) Revision: 19.12.2024

Trade name: KMPR® 3000 Series Resists

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

IOELV Short-term value: 568 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection





Printing date 19.12.2024 Version number 2 (replaces version 1) Revision: 19.12.2024

Trade name: KMPR® 3000 Series Resists

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

· Body protection: Long-sleeved work clothes

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Mild

• Odour threshold: Not determined. • Melting point/freezing point: Undetermined.

Boiling point or initial boiling point

and boiling range 130.6 °C (120-92-3 Cyclopentanone)

• *Flammability* Not applicable.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined.

• Flash point: 30 °C (120-92-3 Cyclopentanone) • Auto-ignition temperature: 430 °C (120-92-3 Cyclopentanone)

• **Decomposition temperature:** Not determined. • **pH** Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

·Solubility

· water: Insoluble.

· Partition coefficient n-octanol/water

(log value) Not determined.

· Vapour pressure at 20 °C: 11 hPa (120-92-3 Cyclopentanone)

· Density and/or relative density

Density: See Other informationRelative density Not determined.

(Contd. on page 6)



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.12.2024 Version number 2 (replaces version 1) Revision: 19.12.2024

Trade name: KMPR® 3000 Series Resists

V J	N 1	1				
Vapour density	Not determine	ra.				
9.2 Other information	Name	Number	Sp. Grav.	VOC(%by wt.)	VOC(g/L)	
	KMPR 3001	<i>Y214020</i>	1.0028	75-80	775	
	KMPR 3002	Y214031	1.0337	65-70	690	
	KMPR 3005	Y214043	1.0599	55-60	615	
	KMPR 3006	Y214045	1.0739	50-55	580	
	KMPR 3010	Y214051	1.0899	45-50	525	
	KMPR 3015	Y214055	1.1045	40-45	475	
	KMPR 3025	<i>Y214060</i>	1.1171	<i>35-40</i>	440	
	KMPR 3035	Y214062	1.1229	35-40	420	
	KMPR 3050	Y214064	1.1287	30-35	400	
Appearance:						
Form:	Liquid					
Important information on protection of	f					
health and environment, and on safety						
Ignition temperature:	Product is not	selfigniting	g.			
Explosive properties:	Product is no	t explosive	. However	, formation of	explosive air/vap	
	mixtures are possible.					
Solvent content:	1					
VOC (EC)	<i>30-80</i> %					
Change in condition						
Evaporation rate	Not determine	ed.				
Information with regard to physical						
hazard classes						
Explosives	Not applicable	0				
Flammable gases	Not applicable					
Aerosols	Not applicable					
Oxidising gases	Not applicable					
Gases under pressure	Not applicable					
Flammable liquids	Flammable lie		nour			
Flammable solids	Not applicable		pour.			
Self-reactive substances and mixtures	Not applicable					
Pyrophoric liquids	Not applicable					
Pyrophoric aquas Pyrophoric solids	Not applicable					
Self-heating substances and mixtures	Not applicable					
Substances and mixtures, which emit	тої арріїсаві	ε.				
	Not applicable	a				
flammable gases in contact with water						
Oxidising liquids	Not applicable					
Oxidising solids	Not applicable					
Organic peroxides	Not applicable					
Corrosive to metals	Not applicable	٤.				

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable

· Desensitised explosives

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Not applicable.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 7)



Printing date 19.12.2024 Version number 2 (replaces version 1) Revision: 19.12.2024

Trade name: KMPR® 3000 Series Resists

(Contd. of page 6)

· 10.4 Conditions to avoid

Contact with incompatible materials.

Heat, flames and sparks. Extremes of temperature and direct sunlight.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Hydrocarbons

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

120-92-3 Cyclopentanone					
Oral	LD50	1,820 mg/kg (Rat)			

LD/LC50 values relevant for classification:

Oral	LD50	1,820 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	19.5 mg/l (Rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

· Germ cell mutagenicity

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

· Carcinogenicity

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

· Reproductive toxicity

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

· STOT-repeated exposure

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

· Aspiration hazard

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

• Experience with humans: Target Organs: Central nervous system, kidney, liver, lungs

(Contd. on page 8)



Printing date 19.12.2024 Version number 2 (replaces version 1) Revision: 19.12.2024

Trade name: KMPR® 3000 Series Resists

(Contd. of page 7)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:				
120-92-3 C	yclopentanone			
LC50/48 hr	2,950 mg/L (golden orfe)			
LC50/96 h	>100 mg/l (fish)			
EC50/48 h	3,600 mg/l (Ceriodaphnia dubia (water flea))			
	100 mg/l (daphnia magna)			
EC50/72 h	>100 mg/l (scenedesmus subspicatus)			

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

11	1	IIN	numi	hor	or	ID	numhor

· ADR, IMDG, IATA UN1866

· 14.2 UN proper shipping name

· ADR, IMDG, IATA RESIN SOLUTION

(Contd. on page 9)



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.12.2024 Version number 2 (replaces version 1) Revision: 19.12.2024

Trade name: KMPR® 3000 Series Resists

(Contd. of page 8)

· 14.3	Transport	hazard	class((es))
--------	------------------	--------	--------	------	---

· ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label

· 14.4 Packing group

· ADR, IMDG, IATA

· 14.5 Environmental hazards: Not applicable.

• 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30

· EMS Number: F-E,S-E · Stowage Category A

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

 \cdot ADR

· Limited quantities (LQ) 5L

• Excepted quantities (\overline{EQ}) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· Transport category 3 · Tunnel restriction code D/E

 \cdot IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 10)



Printing date 19.12.2024 Version number 2 (replaces version 1) Revision: 19.12.2024

Trade name: KMPR® 3000 Series Resists

(Contd. of page 9)

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)
- · Revision History: New SDS.
- · Version number of previous version: 1
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1



Printing date 19.12.2024 Version number 2 (replaces version 1) Revision: 19.12.2024

Trade name: KMPR® 3000 Series Resists

(Contd. of page 10)

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

CII.