

Printing date 13.06.2025 Version number 3 Revision: 13.06.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: KMPR® 3000 Series Resists
- · Article number: Y214020, Y214031, Y214043, Y214045, Y214051, Y214055, Y214060, Y214062, Y214064
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · **Product category** PC30 Photo-chemicals
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Manufacturer:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Telephone: (617) 965-5511 Fax: (617) 965-5818

Importer:

A-Gas Electronic Materials

Unit 3, IO Centre

Swift Valley

Rugby, Warwickshire

CV21 1TW, UK

Tel: +44-0-1788-537535 *Fax:* +44-0-1788-535835

Website: www.agasem.com

Email: customerservice.em@agas.com

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuam.com
• 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511

Example 19 Example 19 Exam

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

(Contd. on page 2)



Printing date 13.06.2025 Version number 3 Revision: 13.06.2025

Trade name: KMPR® 3000 Series Resists

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS0

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

44.8 % of the mixture consists of component(s) of unknown toxicity.

Contains 44.8 % of components with unknown hazards to the aquatic environment.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

| · Dangerous compone | nts: | |
|---------------------|---|--------|
| CAS: 120-92-3 | Cyclopentanone | 25-75% |
| EINECS: 204-435-9 | (A) Flam. Lia. 3. H226: (1) Skin Irrit. 2. H315: Eve Irrit. 2. H319 | |

(Contd. on page 3)



Printing date 13.06.2025 Version number 3 Revision: 13.06.2025

Trade name: KMPR® 3000 Series Resists

| | | (Contd. of page 2 |
|----------------------|---|-------------------|
| CAS: 107-98-2 | 1-methoxy-2-propanol | 1-10% |
| EINECS: 203-539-1 | ♠ Flam. Liq. 3, H226; ♦ STOT SE 3, H336 | |
| CAS: 108-32-7 | Propylene carbonate | 0.25-3% |
| EINECS: 203-572-1 | ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319 | |
| CAS: 96-48-0 | gamma-Butyrolactone | 0.25-3% |
| EINECS: 202-509-5 | ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; STOT SE 3, H336 | |
| · Additional Compone | ents: | |
| Proprietary Epoxy R | Pesin | 15-65% |
| Proprietary Photoac | cid Generator | <1% |
| Additional informat | ion: For the wording of the listed hazard phrases refer to section 16. | l l |

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)



Printing date 13.06.2025 Version number 3 Revision: 13.06.2025

Trade name: KMPR® 3000 Series Resists

(Contd. of page 3)

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

(Contd. of page 4)




Safety data sheet according to UK REACH

Printing date 13.06.2025 Version number 3 Revision: 13.06.2025

Trade name: KMPR® 3000 Series Resists

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Long-sleeved work clothes

SECTION 9: Physical and chemical properties

| 9.1 Information on basic physical and cl | hemical properties |
|--|---|
| · General Information · Appearance: | |
| Form: | Liquid |
| Colour: | Beige |
| · Odour: | Mild |
| · Odour threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range: | 130.6 °C |
| · Flash point: | 30 °C |
| · Flammability | Not applicable. |
| · Auto-ignition temperature: | 430 °C |
| · Decomposition temperature: | Not determined. |
| · Ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| · Vapour pressure at 20 °C: | 11 hPa |
| · Density: | See Other information |
| · Relative density | Not determined. |
| Vapour density | Not determined. |
| | |

(Contd. on page 6)



Printing date 13.06.2025 Version number 3 Revision: 13.06.2025

Trade name: KMPR® 3000 Series Resists

| | | | | | (Contd. of pag |
|---|---------------|---------|-----------|--------------|----------------|
| Evaporation rate | Not determine | rd. | | | |
| · Solubility in / Miscibility with | | | | | |
| water: | Insoluble. | | | | |
| Partition coefficient: n-octanol/water: | Not determine | rd. | | | |
| · Viscosity: | | | | | |
| Dynamic: | Not determine | ed. | | | |
| Kinematic: | Not determine | ed. | | | |
| · Solvent content: | | | | | |
| VOC (EC) | 30-80 % | | | | |
| 9.2 Other information | Name | Number | Sp. Grav. | VOC(%by wt.) | VOC(g/L) |
| | KMPR 3001 | Y214020 | 1.0028 | 75-80 | 775 |
| | KMPR 3002 | Y214031 | 1.0337 | 65-70 | 690 |
| | KMPR 3005 | Y214043 | 1.0599 | 55-60 | 615 |
| | KMPR 3006 | Y214045 | 1.0739 | 50-55 | 580 |
| | KMPR 3010 | Y214051 | 1.0899 | 45-50 | 525 |
| | KMPR 3015 | Y214055 | 1.1045 | 40-45 | 475 |
| | KMPR 3025 | Y214060 | 1.1171 | 35-40 | 440 |
| | KMPR 3035 | Y214062 | 1.1229 | 35-40 | 420 |
| | KMPR 3050 | Y214064 | 1.1287 | 30-35 | 400 |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Contact with incompatible materials.

Heat, flames and sparks. Extremes of temperature and direct sunlight.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Hydrocarbons

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 1 | values rele | vant for classification: |
|-------------|-------------|--------------------------|
| 120-92-3 C | Cyclopenta | none |
| Oral | LD50 | 1,820 mg/kg (Rat) |
| Dermal | LD50 | >2,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 19.5 mg/l (Rat) |

(Contd. on page 7)



Printing date 13.06.2025 Version number 3 Revision: 13.06.2025

Trade name: KMPR® 3000 Series Resists

(Contd. of page 6)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

120-92-3 Cyclopentanone

LC50/48 hr | 2,950 mg/L (golden orfe)

LC50/96 h > 100 mg/l (fish)

EC50/48 h | 3,600 mg/l (Ceriodaphnia dubia (water flea))

100 mg/l (daphnia magna)

EC50/72 h > 100 mg/l (scenedesmus subspicatus)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)



Printing date 13.06.2025 Version number 3 Revision: 13.06.2025

Trade name: KMPR® 3000 Series Resists

(Contd. of page 7)

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

| 14.1 UN-Number ADR, IMDG, IATA | UN1866 |
|---|--|
| 14.2 UN proper shipping name ADR, IMDG, IATA | RESIN SOLUTION |
| 14.3 Transport hazard class(es) | |
| ADR, IMDG, IATA | |
| Class | 3 Flammable liquids. |
| Label | 3 Frammable liquids. |
| 14.4 Packing group ADR, IMDG, IATA | III |
| 14.5 Environmental hazards: | Not applicable. |
| 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category | Warning: Flammable liquids. 30 F-E,S-E A |
| 14.7 Transport in bulk according to Annex II o | |
| Marpol and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| ADR Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml |
| Transport category Tunnel restriction code | Maximum net quantity per outer packaging: 1000 ml 3 D/E |
| IMDG Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |



Printing date 13.06.2025 Version number 3 Revision: 13.06.2025

Trade name: KMPR® 3000 Series Resists

(Contd. of page 8)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)
- · Abbreviations and acronvms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3