

Printing date 09/28/2021

1 Identification

· Product identifier

- · Trade name: <u>KMPR® 3000 Series Resists</u>
- **Product number:** Y214064, Y214045, Y214043, Y214031, Y214020 • **Application of the substance / the mixture** Photoresist
- Details of the supplier of the safety data sheet • Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road
- Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818
- Information department: Product Safety Email: productsafety@kayakuAM.com • Emergency telephone number:
- Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 Chemtrec International Emergency : 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



Flam. Liq. 3 H226 Flammable liquid and vapor.



Skin Irrit. 2 H315 Causes skin irritation. Eve Irrit. 2A H319 Causes serious eve irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



Signal word Warning
Hazard statements
H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray

Reviewed on 09/28/2021

(Contd. on page 2)

⁻⁻ US



Printing date 09/28/2021

Reviewed on 09/28/2021

Trade name: KMPR® 3000 Series Resists

	(Contd. of page 1)	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P301+P310	If swallowed: Immediately call a poison center/doctor.	
P302+P352	If on skin: Wash with plenty of soap and water.	
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.	
P305+P351+P3	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P332+P313	If skin irritation occurs: Get medical advice/attention.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.	
P403+P235	Store in a well-ventilated place. Keep cool.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	
S		
· HMIS-ratings (scale 0 - 4)	
HEALTH2Health = 2FIRE3Fire = 3REACTIVITY $Reactivity = 0$		
• Other hazards • Results of PBT and vPvB assessment • PBT: Not applicable. • vPvB: Not applicable.		

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

120-92-3	Cyclopentanone	25-75%
	🐼 Flam. Liq. 3, H226; 狄 Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
107-98-2	1-methoxy-2-propanol	1-10%
	� Flam. Liq. 3, H226; � STOT SE 3, H336	
108-32-7	Propylene carbonate	0.1-3%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
Additiona	l Components:	
Epoxy Re.	sin (CAS Proprietary)	15-65%
Proprieta	ry Photoacid Generator	0.5-2%

(Contd. on page 3)



Printing date 09/28/2021

Reviewed on 09/28/2021

Trade name: KMPR® 3000 Series Resists

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- After inhalation:
- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- Alcohol resistant foam
- Fire-extinguishing powder
- Carbon dioxide
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- Protective equipment: Wear SCBA.

6 Accidental release measures

).
0.87 ppr
100 ppn



Printing date 09/28/2021

Reviewed on 09/28/2021

Trade name: KMPR® 3000 Series Resists

108-32-7 Propylene carbonate	(Contd. of page 3) 34 mg/m ³
PAC-2:	
120-92-3 Cyclopentanone	9.5 ppm
107-98-2 1-methoxy-2-propanol	160 ppm
108-32-7 Propylene carbonate	370 mg/m ³
· PAC-3:	
120-92-3 Cyclopentanone	57 ppm
107-98-2 1-methoxy-2-propanol	660 ppm
108-32-7 Propylene carbonate	2,200 mg/m ³

7 Handling and storage

· Handling:

- *Precautions for safe handling* Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Use explosion-proof apparatus / fittings and spark-proof tools.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:
- Do not store together with alkalis (caustic solutions). Do not store together with oxidizing and acidic materials.
- Further information about storage conditions:
- *Keep container well-sealed in cool, dry location.*
- Protect from heat and direct sunlight.
- Store receptacle in a well ventilated area.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.


107-98-2	1-methoxy-2-propanol
	t-term value: 540 mg/m³, 150 ppm z-term value: 360 mg/m³, 100 ppm
	rt-term value: 369 mg/m³, 100 ppm g-term value: 184 mg/m³, 50 ppm
•	(Contd. on page 5)



Printing date 09/28/2021

Reviewed on 09/28/2021

Trade name: KMPR® 3000 Series Resists



Information on basic physical and General Information	chemical properties
Appearance:	
Form:	Liquid
Color:	Beige
Odor:	Solvent-like
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	120.3 °C (248.5 °F)
Flash point:	30 °C (86 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	270 °C (518 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.



Printing date 09/28/2021

Reviewed on 09/28/2021

Trade name: KMPR® 3000 Series Resists

		(Contd. of page
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	11 hPa (8.3 mm Hg)	
Density:	See other information	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	1.6-2.3 (BuAc=1)	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	30-80 %	
VOC content:	30-80 %	
Solids content:	20-66 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid
- Contact with incompatible materials.
- Heat, flames and sparks. Extremes of temperature and direct sunlight.
- · Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- Hazardous decomposition products:
- Hydrocarbons

Carbon monoxide and carbon dioxide Nitrogen oxides (NOx)

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:		
120-92-3 Cyclopentanone		
Oral	LD50	1,820 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
		(Contd. on page 7

- US



Printing date 09/28/2021

Trade name: KMPR® 3000 Series Resists

Reviewed on 09/28/2021

(Contd. of page 6)

Inhalative LC50/4 h 19.5 mg/l (Rat)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Experience with humans: Target Organs: Central nervous system, kidney, liver, lungs
- Additional toxicological information:
- *The product shows the following dangers according to internally approved calculation methods for preparations: Irritant*

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program)

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

• Aquatic toxicity:

120-92-3 Cyclopentanone

LC50/48 hr 2,950 mg/L (golden orfe)

LC50/96 h > 100 mg/l (fish)

EC50/48 h 3,600 mg/l (Ceriodaphnia dubia (water flea))

100 mg/l (daphnia magna)

EC50/72 h >100 mg/l (scenedesmus subspicatus)

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

• *PBT:* Not applicable.

- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

• Waste treatment methods

· Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.

(Contd. on page 8)

(Contd. of page 7)



Printing date 09/28/2021

Safety Data Sheet acc. to OSHA HCS

Reviewed on 09/28/2021

Trade name: KMPR® 3000 Series Resists

Disposal must be made in accordance with Federal, State, and Local regulations.

· Uncleaned packagings:

• Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

• Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
DOT, ADR, IMDG, IATA	UN1866
UN proper shipping name	
DOT ADR, IMDG, IATA	Resin solution RESIN SOLUTION
	RESIN SOLUTION
Transport hazard class(es)	
DOT	
LAMPAGE LODO	
Class	3 Flammable liquids
Label	3
ADR, IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, ADR, IMDG, IATA	111
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code).	: 30
EMS Number:	F-E, <u>S-E</u> A
Stowage Category	<u>A</u>
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L



Printing date 09/28/2021

Reviewed on 09/28/2021

Trade name: KMPR® 3000 Series Resists

ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN ''Model Regulation'':	UN 1866 RESIN SOLUTION, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

• Section 355 (extremely hazardous substances):		
None of the ingredients are listed.		
· Section 313 (Specific toxic chemical listings):		
None of the ingredients is listed.		
• TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.		
Cyclopentanone	ACTIVE	
1-methoxy-2-propanol	ACTIVE	
Propylene carbonate	ACTIVE	
· Hazardous Air Pollutants		
None of the ingredients are listed.		
· Proposition 65		
· Chemicals known to cause cancer:		
None of the ingredients are listed.		
• Chemicals known to cause reproductive toxicity for females:		
None of the ingredients are listed.		
· Chemicals known to cause reproductive toxicity for males:		
None of the ingredients are listed.		
· Chemicals known to cause developmental toxicity:		
None of the ingredients are listed.		
· Carcinogenic categories		
· EPA (Environmental Protection Agency)		
None of the ingredients are listed.		
• TLV (Threshold Limit Value)		
None of the ingredients are listed.		
	(Contd. on page 10)	

- US -



Printing date 09/28/2021

Reviewed on 09/28/2021

Trade name: KMPR® 3000 Series Resists

(Contd.	of page 9)
---------	------------

· NIOSH-Ca (National	Institute for Oc	cupational Safety	and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

120-92-3 Cyclopentanone

107-98-2 1-methoxy-2-propanol

· New Jersey State Right To Know List

120-92-3 Cyclopentanone

107-98-2 1-methoxy-2-propanol

· Pennsylvania Hazardous Substances List

120-92-3 Cyclopentanone

107-98-2 1-methoxy-2-propanol

· California SCAQMD Rule 443.1 VOC's: No information available.

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



a , 1 1 117	
• Signal word War	0
• Hazard statement	
H226 Flammable	liquid and vapor.
H315 Causes skin	n irritation.
H319 Causes seri	ous eye irritation.
· Precautionary sta	itements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P305+P351+P33	88 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	<i>If eye irritation persists: Get medical advice/attention.</i>
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Chemical safety d	assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.



Printing date 09/28/2021

Trade name: KMPR® 3000 Series Resists

	(Contd. of page 10)
Department issuing SDS: Product safety department	
Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)	
Contact. Tom Cole, ETTS Manager (Icole@kayakuAM.com)	
Revision History: New SDS	
Date of preparation / last revision 09/28/2021 / -	
Abbreviations and acronyms:	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement C	Concerning the International
Carriage of Dangerous Goods by Road)	oneer ning me inter national
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Flam. Liq. 3: Flammable liquids – Category 3	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
	US -

Reviewed on 09/28/2021