

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/14/2023

Reviewed on 04/14/2023

1 Identification

- **Product identifier**
- **Trade name:** SU-8 2000 Series Resists
- **Product number:**
 Y111004, Y111007, Y111014, Y111022, Y111029, Y111045, Y111053, Y111058, Y111064, Y111069, Y111070, Y111072, Y111074, Y111075
- **Application of the substance / the mixture** Photoresist
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Kayaku Advanced Materials, Inc.
 200 Flanders Road
 Westborough, MA 01581
 Tel: (617) 965-5511
 Fax: (617) 965-5818
- **Information department:**
 Product Safety
 Email: productsafety@kayakuam.com
- **Emergency telephone number:**
 Kayaku Advanced Materials : 617-965-5511
 Chemtrec USA Emergency : 800-424-9300
 Chemtrec International Emergency : 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Aquatic Acute 2 H401 Toxic to aquatic life.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/14/2023

Reviewed on 04/14/2023

Trade name: SU-8 2000 Series Resists

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labeling:

Epoxy resin

Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate (1-) (1:2)

Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)

· Hazard statements

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



HEALTH 2 Health = 2

FIRE 3 Fire = 3

REACTIVITY 0 Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/14/2023

Reviewed on 04/14/2023

Trade name: SU-8 2000 Series Resists

 · **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

 · **Chemical characterization:** Mixtures

 · **Description:** Mixture of the substances listed below with nonhazardous additions.

 · **Dangerous components:**

	Epoxy resin ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	3-75%
120-92-3	Cyclopentanone ⚠ Flammable Liquids 3, H226; ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319	15-96%
108-32-7	Propylene carbonate ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319	0.1-5%
71449-78-0	Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Sensitization - Skin 1, H317	0.05-2.5%
89452-37-9	Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate (1-) (1:2) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Sensitization - Skin 1, H317	0.05-2.5%

4 First-aid measures

 · **Description of first aid measures**

 · **General information:** Immediately remove any clothing soiled by the product.

 · **After inhalation:** Supply fresh air and to be sure call for a doctor.

 · **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

 · **After eye contact:**

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

 · **After swallowing:** Do not induce vomiting; immediately call a doctor.

 · **Information for doctor:**

 · **Most important symptoms and effects, both acute and delayed** No further relevant information available.

 · **Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

5 Fire-fighting measures

 · **Extinguishing media**

 · **Suitable extinguishing agents:**

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

 · **For safety reasons unsuitable extinguishing agents:** Water with full jet

 · **Special hazards arising from the substance or mixture** No further relevant information available.

 · **Advice for firefighters**

 · **Protective equipment:** Wear SCBA.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/14/2023

Reviewed on 04/14/2023

Trade name: SU-8 2000 Series Resists

(Contd. of page 3)

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

120-92-3	Cyclopentanone	0.87 ppm
108-32-7	Propylene carbonate	34 mg/m ³

· **PAC-2:**

120-92-3	Cyclopentanone	9.5 ppm
108-32-7	Propylene carbonate	370 mg/m ³

· **PAC-3:**

120-92-3	Cyclopentanone	57 ppm
108-32-7	Propylene carbonate	2,200 mg/m ³

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and containers:**

Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.

· **Information about storage in one common storage facility:**

Do not store together with alkalis (caustic solutions).

Do not store together with acids.

Do not store together with oxidizing materials.

· **Further information about storage conditions:**

Protect from heat and direct sunlight.

Keep container well-sealed in cool, dry location.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/14/2023

Reviewed on 04/14/2023

Trade name: SU-8 2000 Series Resists

(Contd. of page 4)

- Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

71449-78-0 Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)	
NIOSH IDLH	ACGIH TLV TWA: Long-term value: 0.5 mg/m ³
OSHA PEL	Long-term value: 50 mg/m ³
	Long-term value: 0.5 mg/m ³
89452-37-9 Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate (1-) (1:2)	
ACGIH TLV TWA	Long-term value: 0.5 mg/m ³
NIOSH IDLH	Long-term value: 50 mg/m ³
OSHA PEL	Long-term value: 0.5 mg/m ³

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from food and beverages.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.
- **Respiratory equipment:**
 In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves** Nitrile rubber, NBR
- **Penetration time of glove material** Contact glove manufacture for break-through time.
- **Eye protection:**



Tightly sealed goggles

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/14/2023

Reviewed on 04/14/2023

Trade name: SU-8 2000 Series Resists

(Contd. of page 5)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid
 Color: Clear to light yellow

· **Odor:** Sweet

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.
 Boiling point/Boiling range: 130 °C (266 °F)

· **Flash point:** 30 °C (86 °F)

· **Flammability (solid, gaseous):** Flammable.

· **Auto igniting:** 430 °C (806 °F)

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: Not determined.
 Upper: Not determined.

· **Vapor pressure:** Not determined.

· **Density:** See other information

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** 1.6-2.3 (BuAc=1)

· **Solubility in / Miscibility with**

Water: Water miscible No

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/14/2023

Reviewed on 04/14/2023

Trade name: SU-8 2000 Series Resists

(Contd. of page 6)

Kinematic:	Not determined.				
Other information	<i>Name</i>	<i>Number</i>	<i>Sp. Grav.</i>	<i>Vol. (%by wt.)</i>	<i>VOC (g/L)</i>
	SU-8 2000.1	Y111004	0.955	96	920
	SU-8 2000.2	Y111007	0.962	93	900
	SU-8 2000.5	Y111014	0.981	86	840
	SU-8 2001	Y111022	0.998	78	780
	SU-8 2002	Y111029	1.024	71	725
	SU-8 2005	Y111045	1.072	55	590
	SU-8 2007	Y111053	1.092	47	520
	SU-8 2010	Y111058	1.104	42	460
	SU-8 2015	Y111064	1.124	36	410
	SU-8 2025	Y111069	1.133	31	355
	SU-8 2035	Y111070	1.137	30	340
	SU-8 2050	Y111072	1.142	28	322
	SU-8 2075	Y111074	1.146	26	300
	SU-8 2100	Y111075	1.151	25	285

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
 Contact with incompatible materials.
 Heat, flames and sparks. Extremes of temperature and direct sunlight.
- **Incompatible materials:** Strong Oxidizing Agents, Strong Acids, Strong Bases
- **Hazardous decomposition products:**
 Carbon monoxide and carbon dioxide
 Corrosive gases/vapors
 Danger of toxic pyrolysis products.
 Antimony oxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

120-92-3 Cyclopentanone		
Oral	LD50	1,820 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	19.5 mg/l (Rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/14/2023

Reviewed on 04/14/2023

Trade name: SU-8 2000 Series Resists

(Contd. of page 7)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients are listed.

· **NTP (National Toxicology Program)**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

120-92-3 Cyclopentanone

LC50/48 hr	2,950 mg/L (golden orfe)
LC50/96 h	>100 mg/l (fish)
EC50/48 h	3,600 mg/l (Ceriodaphnia dubia (water flea))
	100 mg/l (daphnia magna)
EC50/72 h	>100 mg/l (scenedesmus subspicatus)

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Ecotoxical effects:**

· **Remark:** Toxic for fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.

Disposal must be made in accordance with Federal, State, and Local regulations.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/14/2023



Reviewed on 04/14/2023

Trade name: SU-8 2000 Series Resists

(Contd. of page 8)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made in accordance with Federal, State, and Local regulations.

14 Transport information

· UN-Number	UN1866
· DOT, ADR, IMDG, IATA	
· UN proper shipping name	Resin solution
· DOT	RESIN SOLUTION
· ADR, IATA	RESIN SOLUTION (Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-)) (1:1), Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate(1-)) (1:2)), MARINE POLLUTANT
· IMDG	
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Marine pollutant:	Yes (DOT)
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E,S-E
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/14/2023

Reviewed on 04/14/2023

Trade name: SU-8 2000 Series Resists

(Contd. of page 9)

· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

71449-78-0 Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)

89452-37-9 Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate (1-) (1:2)

- TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.

· Hazardous Air Pollutants

None of the ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

120-92-3 Cyclopentanone

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/14/2023

Reviewed on 04/14/2023

Trade name: SU-8 2000 Series Resists

(Contd. of page 10)

· New Jersey State Right To Know List

120-92-3 Cyclopentanone

· Pennsylvania Hazardous Substances List

120-92-3 Cyclopentanone

· California SCAQMD Rule 443.1 VOC's: No information available.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms


GHS02 GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labeling:

Epoxy resin

Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-, (OC-6-11)-hexafluoroantimonate (1-) (1:2)

Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)

· Hazard statements

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/14/2023

Reviewed on 04/14/2023

Trade name: SU-8 2000 Series Resists

(Contd. of page 11)

· **Contact:** Tom Cole, EHS Manager (tcole@kayakuam.com)· **Revision History:** New SDS· **Date of preparation / last revision** 04/14/2023· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

US