Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.10.2021

ADVANCED MATERIALS

#### Version number 8

Revision: 13.10.2021



- - - / - - GB

GB



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.10.2021

Version number 8

Revision: 13.10.2021

Trade name: SU-8 3000 Series Resists

	(Contd. of page 2
$\wedge$	
Acute Tox. 4	H332 Harmful if inhaled.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
· 2.2 Label eleme · Labelling accor	nts ding to Regulation (EC) No 1272/2008
	lassified and labelled according to the CLP regulation.
· Hazard pictogra	
	¥↓
GHS02 GHS	607 GHS09
· Signal word Wa	urning
-	ning components of labelling:
Epoxy resin	ning components of tubetting.
Epoxy resin Epoxy novolac p	nalvmer
Proprietary poly	
	enyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)
	di-4, 1-phenylene) bis[diphenyl-,(OC-6-11)-hexafluoroantimonate (1-) (1:2)
· Hazard stateme	
-	le liquid and vapour.
H332 Harmful i	
H315 Causes sk	
H319 Causes se	rious eye irritation.
H317 May caus	e an allergic skin reaction.
H411 Toxic to a	quatic life with long lasting effects.
• Precautionary s	tatements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. N
	smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a positio
D205 + D251 + D	comfortable for breathing.
r 303+P331+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,
P333+P313	present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention.
P333+P313 P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbo
1 5/0 1 5/0	dioxide.
	Store in a well-ventilated place. Keep cool.
P403+P235	Nore in a well-ventilated blace. Keep cool



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.10.2021

Version number 8

Revision: 13.10.2021

Trade name: SU-8 3000 Series Resists

P501

(Contd. of page 2) Dispose of contents/container in accordance with local/regional/national/international regulations.

• Additional information:

15.2 % of the mixture consists of component(s) of unknown toxicity.

Contains 15.2 % of components with unknown hazards to the aquatic environment.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- **vPvB**: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

	Epoxy resin	45-75%
	🐼 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 120-92-3	Cyclopentanone	10-25%
EINECS: 204-435-9	📀 Flam. Liq. 3, H226; 🚸 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 108-32-7	Propylene carbonate	1-5%
EINECS: 203-572-1	🐼 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
	Proprietary polyglycidyl ether	1-5%
	𝐼 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 89452-37-9	Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11)-hexafluoroantimonate	1-5%
	(1-) (1:2)	
	🔖 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; 🚸 Skin Sens. 1, H317	
CAS: 71449-78-0	Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-)	1-5%
	(1:1)	
	🚱 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; 🚸 Skin Sens. 1, H317	
	Epoxy Compound	1-5%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

- After inhalation: Supply fresh air and to be sure call for a doctor.
- After skin contact:
- If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

(Contd. on page 4)

GB -

Printing date 13.10.2021

## Safety data sheet according to 1907/2006/EC, Article 31

Version number 8

Revision: 13.10.2021

(Contd. of page 3)

Trade name: SU-8 3000 Series Resists

- After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

• Suitable extinguishing agents:

Alcohol resistant foam Fire-extinguishing powder

Carbon dioxide

• For safety reasons unsuitable extinguishing agents: Water with full jet

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

#### **SECTION 6:** Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation Keep away from ignition sources.
 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. • 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• **6.4 Reference to other sections** See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

• 7.1 Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols. Keep away from heat and direct sunlight.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

• Storage:

• **Requirements to be met by storerooms and containers:** Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.

(Contd. on page 5)

GB -

Printing date 13.10.2021

## Safety data sheet according to 1907/2006/EC, Article 31

Version number 8

Revision: 13.10.2021

Trade name: SU-8 3000 Series Resists

(Contd. of page 4)

• Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions). Do not store together with amines.

• Further information about storage conditions: Store in cool, dry conditions in well sealed containers. Protect from heat and direct sunlight. Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

- *The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR*
- Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

(Contd. on page 6)



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.10.2021

Version number 8

Revision: 13.10.2021

Trade name: SU-8 3000 Series Resists

9.1 Information on basic physical and constrained and constrai	hemical properties		
Appearance:			
Form:	Liquid		
Colour:	Light yellow		
Odour:	Mild		
Odour threshold:	Not determined.		
pH-value:	Not determined.		
Change in condition	I. J. down in ad		
Melting point/freezing point: Initial boiling point and boiling range	Undetermined. 130 °C		
Flash point:	30 °C		
Flammability (solid, gas):	Not applicable.		
Ignition temperature:	430 °C		
Decomposition temperature:	Not determined.		
Auto-ignition temperature:	Product is not selfigniting.		
Explosive properties:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.		
Explosion limits:			
Lower:	Not determined. Not determined.		
Upper:			
Vapour pressure:	Not determined.		
Density:	Not determined.		
Vapour density	Not determined.		
Evaporation rate	1.6-2.3 (BuAc=1)		
Solubility in / Miscibility with water:	Not miscible or difficult to mix.		
Partition coefficient: n-octanol/water:	Not determined.		
Viscosity:			
Dynamic:	Not determined.		
9.2 Other information	Name Sp. Grav. Vol.(%by wt.) VOC (g/L)		
	SU-8 3005 1.075 48-52 538		
	SU-8 3010 1.106 38-42 442		
	SU-8 3025 1.143 26-30 320		
	SU-8 3035         1.150         24-28         300           SU-8 3050         1.153         22-27         288		

## SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 7)

GB -

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.10.2021

10.2 Chemical stability

Version number 8

Revision: 13.10.2021

Trade name: SU-8 3000 Series Resists

(Contd. of page 6)

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- 10.4 Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.
- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Bases, Strong Acids, Amines
- · 10.6 Hazardous decomposition products:
- Carbon monoxide
- Carbon dioxide
- Danger of forming toxic pyrolysis products.
- Corrosive gases/vapours

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- Acute toxicity
- Harmful if inhaled.

_pony.es	in		
Oral	LD50	>2000 mg/kg (Rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50	>5 mg/L (Rat)	
Epoxy Co	mpound		
Oral	LD50	8030 mg/kg (Rat)	
Dermal	LD50	4248 mg/kg (Rat)	
Inhalative	LC50/4 h	> 5.3 mg/l (Rat)	
120-92-3	Cyclopenta	none	
Oral	LD50	1820 mg/kg (Rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	19.5 mg/l (Rat)	
Proprietar	ry polyglyci	dyl ether	
Oral	LD50	>2000 mg/kg (Rat)	
<b>Skin corre</b> Causes ski <b>Serious ey</b>	rritant effe osion/irrita in irritation ve damage/ rious eye ir rv or skin s	tion irritation	



Printing date 13.10.2021

## Safety data sheet according to 1907/2006/EC, Article 31

Version number 8

Revision: 13.10.2021

(Contd. of page 7)

Trade name: SU-8 3000 Series Resists

· Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

Aquatic toxicity.	•
Epoxy resin	
100 < LC/EC/IC	$50 \leq 1000 \text{ mg/l} (algae)$
	$\leq 1000 mg/l (fish)$
	$\leq 1000 \text{ mg/l} (invertebrates)$
89452-37-9 Sulf	onium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11)-hexafluoroantimonate (1-) (1:2)
LC50/24 h	4.4 mg/l (daphnia)
LC50/48 hr	0.68 mg/L (daphnia)
71449-78-0 Sulf	onium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)
LC50/24 h	4.4 mg/l (daphnia)
LC50/48 hr	0.68 mg/L (daphnia)
Ероху Сотроин	ıd
EC50/48 h	30 mg/l (daphnia magna)
EC50/72 h	255 mg/l (Desmodesmus subscipatus (green algae))
LC50/96 h	55 mg/l (Cyprinus carpio (common carp))
120-92-3 Cyclop	pentanone
EC50/48 h	3600 mg/l (Ceriodaphnia dubia (water flea))
	100 mg/l (daphnia magna)
EC50/72 h	>100 mg/l (scenedesmus subspicatus)
LC50/48 hr	2950 mg/L (golden orfe)
LC50/96 h	>100 mg/l (fish)
2.2 Persistence 2.3 Bioaccumu	and degradability No further relevant information available. Jative potential No further relevant information available. soil No further relevant information available.
Ecotoxical effec	
Remark: Toxic f	
Additional ecolo	gical information:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies.
- Toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 9)

GB

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.10.2021

Version number 8

Revision: 13.10.2021

Trade name: SU-8 3000 Series Resists

(Contd. of page 8)

## SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• *Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.* 

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

- 14.1 UN-Number ADR, IMDG, IATA	UN1866
14.2 UN proper shipping name ADR, IATA IMDG	RESIN SOLUTION RESIN SOLUTION, MARINE POLLUTANT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	Product contains environmentally hazardous substance. Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11) hexafluoroantimonate (1-) (1:2) Yes
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number:	Warning: Flammable liquids. 33 F-E, <u>S-E</u>
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	<b>f</b> Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Transport category Tunnel restriction code	5L 3 D/E
UN ''Model Regulation'':	UN1866, RESIN SOLUTION, 3, III

(Contd. on page 10)

Advanced materials

Printing date 13.10.2021

## Safety data sheet according to 1907/2006/EC, Article 31

Version number 8

Revision: 13.10.2021

Trade name: SU-8 3000 Series Resists

(Contd. of page 9)

## SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

• Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2