ADVANCED MATERIALS


Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.04.2022

Version number 8

Revision: 26.04.2022



EU



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.04.2022

Version number 8

Revision: 26.04.2022

Trade name: SU-8 Series Resists

Hazard pictogra	(Contd. of page 1)
nazara piciogra	uns -
\land	
<∼₹>< ĭ	
$\sim \sim$	
GHS05 GHS	507 GHS09
Signal word Da	nger
Hazard stateme	
H315 Causes sk	in irritation.
H318 Causes se	rious eye damage.
	e an allergic skin reaction.
	e drowsiness or dizziness.
	quatic life with long lasting effects.
Precautionary s	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
<i>P337+P313</i>	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/internationa regulations.
2.3 Other hazar	ds

• **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

	Epoxy resin	35-75%
	𝐼 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 96-48-0	gamma-Butyrolactone	20-60%
EINECS: 202-509-5	� Eye Dam. 1, H318; 𝒱 Acute Tox. 4, H302; STOT SE 3, H336	
CAS: 108-32-7	Propylene carbonate	1-5%
EINECS: 203-572-1	𝒱 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
Index number: 607-194-00-1		
CAS: 89452-37-9	Sulfonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11)- hexafluoroantimonate (1-) (1:2)	0.5-5%
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; $$ Skin Sens. 1, H317	



Printing date 26.04.2022

Version number 8

Revision: 26.04.2022

Trade name: SU-8 Series Resists

		d. of page 2)
CAS: 71449-78-0	Sulfonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)- hexafluoroantimonate(1-) (1:1) Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	0.5-5%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

• After swallowing: Do not induce vomiting; call for medical help immediately.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents:

Fire-extinguishing powder Alcohol resistant foam

ABC powder

· For safety reasons unsuitable extinguishing agents: Water with full jet

 \cdot 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released: Creber manual (CO)

Carbon monoxide (CO) Hvdrogen fluoride (HF)

Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

EU -

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.04.2022

Version number 8

Revision: 26.04.2022

Trade name: SU-8 Series Resists

(Contd. of page 3)

• **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling
- Ensure good ventilation/exhaust at the workplace. Store in cool, dry place in tightly closed receptacles. Prevent formation of aerosols.
- Information about fire and explosion protection: Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges. Keep ignition sources away - Do not smoke.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and containers:** Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles. Store in a cool location.
- Information about storage in one common storage facility: Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions).
- Further information about storage conditions: Protect from exposure to the light. Store in cool, dry conditions in well sealed containers. This product is hygroscopic.
 7.3 Specific end use(s) No further relevant information available.
- SECTION 8: Exposure controls/personal protection
- · 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eves and skin.

(Contd. on page 5)



⁻ EU



Printing date 26.04.2022

Version number 8

Revision: 26.04.2022

Trade name: SU-8 Series Resists

(Contd. of page 4)

Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

- *The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR*
- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and ch	nemical properties	
General Information		
Appearance: Form:	Fluid	
Colour:	Clear to light yellow	
Odour:	Mild	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range:	205 °C	
Flash point:	100 °C (クローズドカップ)	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	445 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	2.7 Vol %	
Upper:	15.6 Vol %	
Vapour pressure at 20 °C:	1 hPa	
Density:	See Table 1 Other Information below	
Relative density	Not determined.	



Printing date 26.04.2022

Version number 8

Revision: 26.04.2022

Trade name: SU-8 Series Resists

	(Contd. of page 5	
· Vapour density · Evaporation rate	Not determined. Not determined.	
· Solubility in / Miscibility with water:	Partly miscible.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
•9.2 Other information	Name Number Sp. Grav. Vol.(%by wt.) VOC (g/L) SU8-2 Y131240 1.123 60.5 680 SU8-5 Y131252 1.164 45-50 560 SU8-5 Y131259 1.187 35-40 490 SU8-25 Y131263 1.200 35-40 440 SU8-25 Y131265 1.210 33-37 425 SU8-40 Y131265 1.219 30-35 380 SU8-50 Y131273 1.233 20-30 330 SU8-100 Y131274 1.236 20-30 320 SU8-500+ Y131275 1.237 20-30 310	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- · 10.4 Conditions to avoid
- Heat, flames and sparks. Extremes of temperature and direct sunlight.
- Contact with incompatible materials.
- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:
- Carbon monoxide and carbon dioxide
- Antimony oxide
- Corrosive gases/vapours
- Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
Epoxy resin			
Oral	LD50	>2000 mg/kg (Rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50	5 mg/L (Rat)	
		(Contd. on page 7)	

— EU



Printing date 26.04.2022

Version number 8

Revision: 26.04.2022

Trade name: SU-8 Series Resists

		(Coi	ntd. of page 6)
96-48-0 g	amma-But	yrolactone	
Oral	LD50	1540 mg/kg (Rat)	
Dermal	LD50	5000 mg/kg (gui)	
Inhalative	e LC50/4 h	>5.1 mg/l (Rat)	
108-32-7	Propylene	carbonate	
Oral	LD50	29000 mg/kg (Rat)	
Dermal	LD50	>20,000 mg/kg (rabbit)	
· Primary i	rritant effe	ect:	
· Skin corr	osion/irrita	ntion	
Causes sk	in irritation	n.	
· Serious e	ye damage/	/irritation	
Causes se	rious eye d	lamage.	
• Respirato	ry or skin s	sensitisation	
May caus	e an allergi	ic skin reaction.	
• Additiona	l toxicolog	rical information:	
· CMR effe	cts (carcin	ogenity, mutagenicity and toxicity for reproduction)	
· Germ cell	l mutagenio	city Based on available data, the classification criteria are not met.	
· Carcinog	enicity Bas	ed on available data, the classification criteria are not met.	
		y Based on available data, the classification criteria are not met.	
	gle exposu		
	•	ss or dizziness.	
•		osure Based on available data, the classification criteria are not met.	
-	-	ased on available data, the classification criteria are not met.	

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

$\frac{1}{100 < 1 C/FC/IC}$	$50 \leq 1000 \text{ mg/l} (algae)$
100 ~LC/LC/IC	
	$\leq 1000 \text{ mg/l} \text{ (fish)}$
	$\leq 1000 \text{ mg/l} (invertebrates)$
96-48-0 gamma	n-Butyrolactone
EC50/17 h	>10000 mg/l (bacterium)
EC50/48 h	>500 mg/l (daphnia magna)
EC50/72 h	360 mg/l (green algae)
LC50/96 h	>220 - <460 mg/l (golden orfe)
89452-37-9 Sul	fonium, (thiodi-4,1-phenylene) bis[diphenyl-,(OC-6-11)-hexafluoroantimonate (1-) (1:2)
LC50/24 h	4.4 mg/l (daphnia)
LC50/48 hr	0.68 mg/L (daphnia)
71449-78-0 Sul	fonium, diphenyl[4-(phenylthio)phenyl]-, (OC-6-11)-hexafluoroantimonate(1-) (1:1)
LC50/24 h	4.4 mg/l (daphnia)
LC50/48 hr	0.68 mg/L (daphnia)

(Contd. on page 8)



Printing date 26.04.2022

Version number 8

Revision: 26.04.2022

(Contd. of page 7)

Trade name: SU-8 Series Resists

• 12.4 Mobility in soil No further relevant information available.

· Ecotoxical effects:

• **Remark:** Toxic for fish

• Additional ecological information:

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

• Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
ADR, IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUII
IMDG	N.O.S. (Hexafluoroantimonate salt, Triarylsulfonium salt) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUII
IMDG	N.O.S. (Hexafluoroantimonate salt, Triarylsulfonium salt
	MARINE POLLUTANT
14.3 Transport hazard class(es)	
-	
ADR, IMDG, IATA	
Class	9 Miscellaneous dangerous substances and articles.
Label	9
14.4 Packing group	
	111
ADR, IMDG, IATA	
ADR, IMDG, IATA 14.5 Environmental hazards:	Product contains environmentally hazardous substance. Triarylsulfonium salt



Printing date 26.04.2022

Version number 8

Revision: 26.04.2022

Trade name: SU-8 Series Resists

	(Contd. of page
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	f Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (HEXAFLUOROANTIMONATE SALT TRIARYLSULFONIUM SALT), 9, III

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Directive 2012/18/EU

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 10)

EU -

ADVANCED MATERIALS

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.04.2022

Version number 8

Revision: 26.04.2022

Trade name: SU-8 Series Resists

• **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out. (Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- · Classification according to Regulation (EC) No 1272/2008
- Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.
- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

- Abbreviations and acronyms:
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- *PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative*
- Acute Tox. 4: Acute toxicity Category 4
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- *Eye Dam. 1: Serious eye damage/eye irritation Category 1*
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- Skin Sens. 1: Skin sensitisation Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- Aquatic Acute 1: Hazardous to the aquatic environment acute aquatic hazard Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment long-term aquatic hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment long-term aquatic hazard Category 2

EU -