


Printing date 05/25/2023

1 Identification

· Product identifier

- Trade name: <u>SU-8 TF 6000 Series Resists</u>
- **Product number:** Y143007, Y143010, Y143015, Y143027, Y143037, Y143051, Y143061 • **Application of the substance / the mixture** Photoresist
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818
- Information department: Product Safety Email: productsafety@kayakuam.com
 Emergency telephone number: Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300
- Chemtrec International Emergency: 703-527-3887

2 Hazard(s) identification



Reviewed on 05/25/2023



Printing date 05/25/2023

Reviewed on 05/25/2023

Trade name: SU-8 TF 6000 Series Resists

	(Contd. of page 1)	
Hazard-determ	ining components of labeling:	
Proprietary Epo		
Cyclopentanone		
gamma-Butyrol		
Hazard stateme		
	le liquid and vapor.	
H315 Causes sk		
	erious eye damage.	
	e an allergic skin reaction.	
	e drowsiness or dizziness.	
Precautionary s		
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.	
P261	Avoid breathing dust/fume/gas/mist/vapors/spray	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P301+P310	If swallowed: Immediately call a poison center/doctor.	
P302+P352	If on skin: Wash with plenty of soap and water.	
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.	
<i>P305+P351+P</i> .	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if presen and easy to do. Continue rinsing.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbor dioxide.	
P403+P235	Store in a well-ventilated place. Keep cool.	
P501	Dispose of contents/container in accordance with local/regional/national/internationa regulations.	
Classification s NFPA ratings (ystem:	
	Iealth = 3	
	Fire = 3 Deactivity = 0	
HMIS-ratings ((scale 0 - 4)	
	Health = *3	
	Fire = 3 $Reactivity = 0$	

- *PBT:* Not applicable. *vPvB:* Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

- US -



Printing date 05/25/2023

Trade name: SU-8 TF 6000 Series Resists

Reviewed on 05/25/2023

0	us components:	
120-92-3	Cyclopentanone	20-50
	\bigcirc Flammable Liquids 3, H226; \bigcirc Skin Irritation 2, H315; Eye Irritation 2A, H319	1
	Epoxy resin	5-609
	Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	1
108-65-6	1-Methoxy-2-propanol acetate	10-40
	\bigotimes Flammable Liquids 3, H226; \bigotimes Specific Target Organ Toxicity - Single Exposure 3, H336	
96-48-0	gamma-Butyrolactone	1-109
	Eye Damage 1, H318; Acute Toxicity - Oral 4, H302; Specific Target Organ Toxicity - Single Exposure 3, H336	
Addition	al Components:	

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Alcohol resistant foam Fire-extinguishing powder Carbon dioxide
- Carbon aloxiae
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.
- Advice for firefighters
- **Protective equipment:** Wear SCBA.

(Contd. on page 4)



Printing date 05/25/2023

Reviewed on 05/25/2023

Trade name: SU-8 TF 6000 Series Resists

(Contd. of page 3)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources • Environmental precautions: Do not allow to enter sewers/ surface or ground water. Do not allow product to reach sewage system or any drains. Inform respective authorities in case of seepage into water course or sewage system. • Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- Precautions for safe handling
 Ensure good ventilation/exhaust at the workplace.
 Prevent formation of aerosols.
 Keep receptacles tightly sealed.
 Information about protection against explosions and fires:
- Keep ignition about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Use explosion-proof apparatus / fittings and spark-proof tools.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and containers: Store in a cool location.
- *Information about storage in one common storage facility:* Do not store together with oxidizing and acidic materials. Do not store together with amines.
- Further information about storage conditions: Keep container well-sealed in cool, dry location. Store receptacle in a well ventilated area. Protect from heat and direct sunlight.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

(Contd. on page 5)

⁻ US



Printing date 05/25/2023

Reviewed on 05/25/2023

Trade name: SU-8 TF 6000 Series Resists

At this time, the other constituents have no known exposure limits. 108-65-6 1-Methoxy-2-propanol acetate WEEL Long-term value: 50 ppm • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. • Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
WEEL Long-term value: 50 ppm • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. • Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
 Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
 Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
 Personal protective equipment: General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
 General protective and hygienic measures: Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. • Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. • Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
Avoid contact with the eyes and skin. • Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
• Respiratory equipment: In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. \cdot Material of gloves Nitrile rubber, NBR
• <i>Penetration time of glove material</i> Contact glove manufacture for break-through time. • <i>Eye protection:</i>
Tightly sealed goggles

· Body protection: Long-sleeved work clothes

Information on basic physical and	chemical properties	
General Information		
Appearance: Form:	Liquid	
Form: Color:	Liquid Clean to light wellow	
· Odor:	Clear to light yellow	
	Sweet	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	130 °C (266 °F)	
Flash point:	30 °C (86 °F)	
Flammability (solid, gaseous):	Not applicable.	
Auto igniting:	315 °C (599 °F)	



Printing date 05/25/2023

Reviewed on 05/25/2023

Trade name: SU-8 TF 6000 Series Resists

					(Contd. of page
Decomposition temperature:	Not determined.				
Ignition temperature:	Product is not set	figniting.			
Danger of explosion:	Product is not e mixtures are poss	1	lowever, fo	ormation of expl	osive air/vapo
Explosion limits: Lower: Upper:	1.3 Vol % 10.8 Vol %				
Vapor pressure at 20 °C (68 °F):	11 hPa (8.3 mm l	Hg)			
Density: Relative density Vapor density Evaporation rate	See Other inform Not determined. Not determined. Not determined.	ation			
Solubility in / Miscibility with Water:	Partly miscible.				
Partition coefficient (n-octanol/wate	er): Not determined.				
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.				
Other information	Name SU-8 TF 6000.1 SU-8 TF 6000.2 SU-8 TF 6000.5 SU-8 TF 6001 SU-8 TF 6002 SU-8 TF 6005 SU-8 TF 6010	Number Y143007 Y143010 Y143015 Y143027 Y143037 Y14305 Y143061	Sp. Grav. 0.980 0.988 0.999 1.025 1.050 1.085 1.150	VOC(%by wt.) 80-85 80-85 75-80 65-70 55-60 40-45 30-35	VOC (g/L) 830 810 770 680 600 480 400

10 Stability and reactivity

· Reactivity No further relevant information available.

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Exothermic polymerization.
- Conditions to avoid
- *Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.*
- · Incompatible materials: Strong Oxidizing Agents, Strong Bases, Strong Acids, Amines
- · Hazardous decomposition products:
- Carbon monoxide and carbon dioxide
- Danger of toxic pyrolysis products.
- *Corrosive gases/vapors*

(Contd. on page 7)

[·] Chemical stability Stable



Printing date 05/25/2023

Trade name: SU-8 TF 6000 Series Resists

Reviewed on 05/25/2023

(Contd. of page 6)

3

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Irritant
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

96-48-0 gamma-Butyrolactone

· NTP (National Toxicology Program)

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:

• General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

· Uncleaned packagings:

• Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

(Contd. on page 8)



Printing date 05/25/2023

Reviewed on 05/25/2023

Trade name: SU-8 TF 6000 Series Resists

(Contd. of page 7)

· UN-Number · DOT, ADR, IMDG, IATA	UN1866	
· UN proper shipping name · DOT, ADR · IMDG, IATA	Resin solution RESIN SOLUTION	
· Transport hazard class(es)		
·DOT		
· Class	3 Flammable liquids	
· Label · ADR, IMDG, IATA	3	
· Class	3 Flammable liquids	
· Class · Label	3 Flammable liquids 3	
· Label · Packing group	3	
• Label • Packing group • DOT, ADR, IMDG, IATA • Environmental hazards: • Marine pollutant: • Special precautions for user	3 III No Warning: Flammable liquids	
· Label · Packing group · DOT, ADR, IMDG, IATA · Environmental hazards: · Marine pollutant:	3 III No Warning: Flammable liquids	
 Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Hazard identification number (Kemler compared to the second second	3 III No Warning: Flammable liquids ode): 30 F-E, <u>S-E</u>	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

• Section 355 (extremely hazardous substances):

None of the ingredients are listed.

• Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations.

(Contd. on page 9)

²⁹⁾ — US



Printing date 05/25/2023

· Proposition 65

Reviewed on 05/25/2023

Trade name: SU-8 TF 6000 Series Resists

(Contd. of page 8)

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

• TLV (Threshold Limit Value)

None of the ingredients are listed.

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

120-92-3 Cyclopentanone

· New Jersey State Right To Know List

120-92-3 Cyclopentanone

Pennsylvania Hazardous Substances List

120-92-3 Cyclopentanone

· California SCAQMD Rule 443.1 VOC's: No information available.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: Proprietary Epoxy Resin Cyclopentanone gamma-Butyrolactone
Hazard statements H226 Flammable liquid and vapor. H315 Causes skin irritation. H318 Causes serious eye damage. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.
Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 10)

[–] US



Printing date 05/25/2023

Reviewed on 05/25/2023

Trade name: SU-8 TF 6000 Series Resists

	(Contd. of page 9)
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P305+P351+P3	238 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Chemical safety	assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

- · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

• Date of preparation / last revision 05/25/2023

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Acute Toxicity - Oral 4: Acute toxicity - Category 4 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Damage 1: Serious eye damage/eye irritation - Category 1

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Sensitization - Skin 1: Skin sensitisation – Category 1

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

US -