


Printing date 11/01/2022

1 Identification

· Product identifier

- · Trade name: SU-8 TF 6000 Series Resists
- · Product number: Y143015, Y143027, Y143037, Y143051, Y143061 · Application of the substance / the mixture Photoresist
- · Details of the supplier of the safety data sheet • Manufacturer/Supplier: Kayaku Advanced Materials, Inc. 200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511 Fax: (617) 965-5818
- · Information department: Product Safety Email: productsafety@kayakuAM.com Emergency telephone number: Kayaku Advanced Materials: 617-965-5511 Chemtrec USA Emergency : 800-424-9300 Chemtrec International Emergency: 703-527-3887

2 Hazard(s) identification



Reviewed on 11/01/2022

US



Printing date 11/01/2022

Reviewed on 11/01/2022

Trade name: SU-8 TF 6000 Series Resists

	(Contd. of page 1)
	ining components of labeling:
Proprietary Epo	
Cyclopentanone	
gamma-Butyrol	
Hazard stateme	
	le liquid and vapor.
H315 Causes sh	
	erious eye damage.
	se an allergic skin reaction.
	se drowsiness or dizziness.
Precautionary	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of soap and water.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P305+P351+P	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	<i>If eye irritation persists: Get medical advice/attention.</i>
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbor dioxide.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Classification s	ystem:
F	$\begin{aligned} Health &= 3\\ Fire &= 3\\ Reactivity &= 0 \end{aligned}$
HMIS-ratings (
HEALTH*3FIRE3	Health = *3 Fire = 3 Reactivity = 0

- *Results of PBT and vI PBT:* Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

⁻ US -



Printing date 11/01/2022

Trade name: SU-8 TF 6000 Series Resists

Reviewed on 11/01/2022

	(Contd. of page 2
· Dangerous components:	
120-92-3 Cyclopentanone	20-50%
6 Flammable Liquids 3, H226; 1 Skin Irritation 2, H315; Eye Irritation 2A, H319	
108-65-6 1-Methoxy-2-propanol acetate	10-40%
Specific Target Organ Toxicity - Single Exposure 3, H336	
Epoxy resin	10-60%
Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	
96-48-0 gamma-Butyrolactone	1-10%
Superative Section 2. H318; Acute Toxicity - Oral 4, H302; Specific Target Organ Toxic - Single Exposure 3, H336	ity
· Additional Components:	
Proprietary Photoacid Initiator	0.5-3%
Aquatic Chronic 2, H411; 🚯 Acute Toxicity - Oral 4, H302; Acute Toxicity - Inhalation 4, H332	2

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed Treat symptomatically.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Alcohol resistant foam Fire-extinguishing powder Carbon dioxide
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Water
- · Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

(Contd. on page 4)

US —

(Contd. of page 3)



Safety Data Sheet acc. to OSHA HCS

Printing date 11/01/2022

Reviewed on 11/01/2022

Trade name: SU-8 TF 6000 Series Resists

• Advice for firefighters

· Protective equipment: Wear SCBA.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources • Environmental precautions: Do not allow to enter sewers/ surface or ground water. Do not allow product to reach sewage system or any drains. Inform respective authorities in case of seepage into water course or sewage system. • Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaust at the workplace. Prevent formation of aerosols. Keep receptacles tightly sealed.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Use explosion-proof apparatus / fittings and spark-proof tools.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and containers: Store in a cool location.
- Information about storage in one common storage facility: Do not store together with oxidizing and acidic materials. Do not store together with amines.
- Further information about storage conditions: Keep container well-sealed in cool, dry location. Store receptacle in a well ventilated area. Protect from heat and direct sunlight.
- \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

US



Printing date 11/01/2022

Reviewed on 11/01/2022

Trade name: SU-8 TF 6000 Series Resists

	(Contd. of page
Control parame	
	h limit values that require monitoring at the workplace:
	onstituent is the only constituent of the product which has a PEL, TLV or other recommend
<i>exposure limit.</i>	
	other constituents have no known exposure limits.
	noxy-2-propanol acetate
WEEL Long-ter	m value: 50 ppm
Additional info	mation: The lists that were valid during the creation were used as basis.
Exposure contro	
Personal protec	
	ve and hygienic measures:
	food and beverages.
	ove all soiled and contaminated clothing.
	ore breaks and at the end of work.
	th the eyes and skin.
Respiratory equ	pment:
In case of low ex	posure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.
Protection of ha	nds:
Prot	ctive gloves
1 TOR	sure giores
The glove mater	al has to be impermeable and resistant to the product/ the substance/ the preparation.
	es Nitrile rubber, NBR
	e of glove material Contact glove manufacture for break-through time.
Eye protection:	of give material Contact give manufacture for break-infough time.
Lye protection.	
Tight (Tight	ly sealed goggles

Information on basic physical and General Information	chemical properties	
Appearance:		
Form:	Liquid	
Color:	Clear to light yellow	
Odor:	Sweet	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	130 °C (266 °F)	
Flash point:	30 °C (86 °F) (クローズドカップ)	



Printing date 11/01/2022

Reviewed on 11/01/2022

Trade name: SU-8 TF 6000 Series Resists

	(Contd. of page
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	315 °C (599 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.3 Vol %
Upper:	10.8 Vol %
Vapor pressure at 20 °C (68 °F):	11 hPa (8.3 mm Hg)
Density:	See Table 1 Other Information below
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Partly miscible.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
VOC content:	See Table 1 below
Other information	Table 1. Product specific gravity and VOC data.
	Name Product Sp. Grav. Vol.(%by wt.) VOC (g/L)
	SU-8 TF 6000.5 Y143015 0.999 75-80 770
	SU-8 TF 6001 Y143027 1.025 65-70 680
	SU-8 TF 6002 Y143037 1.050 55-60 600
	SU-8 TF 6005 Y143051 1.085 40-45 480
	SU-8 TF 6010 Y143061 1.150 30-35 400

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Exothermic polymerization.
- · Conditions to avoid
- Heat, flames and sparks. Extremes of temperature and direct sunlight.
- Contact with incompatible materials.
- · Incompatible materials: Strong Oxidizing Agents, Strong Bases, Strong Acids, Amines
- · Hazardous decomposition products:
- Carbon monoxide and carbon dioxide
- Danger of toxic pyrolysis products.

(Contd. on page 7)

[•] US •



Printing date 11/01/2022

Reviewed on 11/01/2022

Trade name: SU-8 TF 6000 Series Resists

(Contd. of page 6)

3

Corrosive gases/vapors

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

• Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Irritating effect.

· Sensitization: Sensitization possible through skin contact.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

96-48-0 gamma-Butyrolactone

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- · Recommendation:

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system. Disposal must be made in accordance with Federal, State, and Local regulations.

(Contd. on page 8)

US



Reviewed on 11/01/2022

Printing date 11/01/2022

Trade name: SU-8 TF 6000 Series Resists

(Contd. of page 7)

· Uncleaned packagings:

• Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

UN-Number		
DOT, ADR, IMDG, IATA	UN1866	
UN proper shipping name DOT, ADR IMDG, IATA	Resin solution RESIN SOLUTION	
Transport hazard class(es)		
DOT		
Class	3 Flammable liquids	
Label	3	
Class	3 Flammable liquids	
Label	3	
Packing group DOT, ADR, IMDG, IATA	111	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
Hazard identification number (Kemle EMS Number:	r code): 30 F-E, <u>S-E</u>	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	: II of Not applicable.	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

• Section 355 (extremely hazardous substances):

None of the ingredients are listed.

(Contd. on page 9)

- US

(Contd. of page 8)



Safety Data Sheet acc. to OSHA HCS

Printing date 11/01/2022

Reviewed on 11/01/2022

Trade name: SU-8 TF 6000 Series Resists

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act): All ingredients are listed or comply with TSCA regulations. • Proposition 65

· Chemicals known to cause cancer:

None of the ingredients are listed.

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

• TLV (Threshold Limit Value)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· Massachusetts State Right To Know List

120-92-3 Cyclopentanone

· New Jersey State Right To Know List

120-92-3 Cyclopentanone

· Pennsylvania Hazardous Substances List

120-92-3 Cyclopentanone

· California SCAQMD Rule 443.1 VOC's: No information available.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: Proprietary Epoxy Resin Cyclopentanone gamma-Butyrolactone

• Hazard statements

H226 Flammable liquid and vapor.

- H315 Causes skin irritation.
- H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

(Contd. on page 10)



Printing date 11/01/2022

Reviewed on 11/01/2022

Trade name: SU-8 TF 6000 Series Resists

	(Contd. of page 9)			
H336 May cause drowsiness or dizziness.				
· Precautionary sta	Precautionary statements			
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.			
P261	Avoid breathing dust/fume/gas/mist/vapors/spray			
P280	Wear protective gloves/protective clothing/eye protection/face protection.			
P301+P310	If swallowed: Immediately call a poison center/doctor.			
P302+P352	If on skin: Wash with plenty of soap and water.			
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for			
	breathing.			
P305+P351+P33	88 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present			
	and easy to do. Continue rinsing.			
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.			
P337+P313	<i>If eye irritation persists: Get medical advice/attention.</i>			
P370+P378	In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon			
	dioxide.			
P403+P235	Store in a well-ventilated place. Keep cool.			
P501	Dispose of contents/container in accordance with local/regional/national/international			
	regulations.			
• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.				

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)

· Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

• Date of preparation / last revision 11/01/2022

• Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Acute Toxicity - Oral 4: Acute toxicity - Category 4 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Damage 1: Serious eye damage/eye irritation - Category 1 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Sensitization - Skin 1: Skin sensitisation - Category 1 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3