

Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: LOR C Series Resists
- · Article number: G713708, G713711, G713713, G713714, G713716
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Product category PC30 Photo-chemicals
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials, Inc.

200 Flanders Road Westborough, MA 01581 Tel: (617) 965-5511

Fax: (617) 965-5818

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuAM.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 1B H360 May damage fertility or the unborn child.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)



Revision: 09.09.2022 Printing date 09.09.2022 Version number 5

Trade name: LOR C Series Resists

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS05

GHS07

#### · Signal word Danger

#### · Hazard-determining components of labelling:

gamma-Butyrolactone

Tetrahydrofurfuryl alcohol

#### · Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

#### Precautionary statements

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P280

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position P304+P341

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 *If eye irritation persists: Get medical advice/attention.* 

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

Restricted to professional users.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

	(Cont	d. of page 2)
· Dangerous components:		
CAS: 120-92-3 EINECS: 204-435-9 Index number: 606-025-00-9 Reg.nr.: 01-2119495595-21-0000	Cyclopentanone  Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2, H319	40-60%
CAS: 96-48-0 EINECS: 202-509-5	gamma-Butyrolactone  Eye Dam. 1, H318; Acute Tox. 4, H302; STOT SE 3, H336	25-50%
CAS: 102322-80-5	Polyaliphatic imide copolymer  Skin Irrit. 2, H315; Eye Irrit. 2, H319	5-20%
CAS: 97-99-4 EINECS: 202-625-6 Index number: 603-061-00-7	Tetrahydrofurfuryl alcohol ❖ Repr. 1B, H360; ❖ Eye Irrit. 2, H319	1-5%
	Proprietary Dye B  ••• Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

*Fire-extinguishing powder* 

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

(Contd. of page 3)

· 5.3 Advice for firefighters

· **Protective equipment:** Wear self-contained respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

*Ensure adequate ventilation.* 

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Use only under yellow light

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers:

Store in a cool location.

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

(Contd. of page 4)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Colour: Yellow-brown
Odour: Sweetish
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

**Melting point/freezing point:** Undetermined. **Initial boiling point and boiling range:** 130 °C

· Flash point: 30 °C (クローズドカップ)

· Flammability (solid, gas): Not applicable.

• Ignition temperature: 430 °C

· Decomposition temperature: Not determined.

(Contd. on page 6)



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

	(Contd. of page
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	2.7 Vol %
Upper:	15.6 Vol %
· Vapour pressure at 20 °C:	1 hPa
· Density:	Not determined
· Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Partly miscible.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 1	LD/LC50 values relevant for classification:		
120-92-3 C	Cyclopenta	none	
Oral	LD50	1180 mg/kg (Rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>19.5 mg/l (Rat)	
96-48-0 ga	mma-Buty	rolactone	
Oral	LD50	1540 mg/kg (Rat)	

(Contd. on page 7)



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

		(Contd. of page 6)
Dermal	LD50	5000 mg/kg (gui)
Inhalative	LC50/4 h	>5.1 mg/l (Rat)
97-99-4 Te	etrahydrofi	urfuryl alcohol
Oral	LD50	1600 mg/kg (Rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Experience with humans: No further relevant information available.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

May damage fertility or the unborn child.

· STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic tox	cicity:	
120-92-3 C	yclopentanone	
EC50/48 h	100 mg/l (daphnia magna)	
EC50/72 h	>100 mg/l (scenedesmus subspicatus)	
LC50/96 h	>100 mg/l (fish)	
96-48-0 gai	mma-Butyrolactone	
EC50/17 h	>10000 mg/l (bacterium)	
EC50/48 h	>500 mg/l (daphnia magna)	
EC50/72 h	360 mg/l (green algae)	
LC50/96 h	>220 - <460 mg/l (golden orfe)	

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

(Contd. of page 7)

· 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1866
•	0.111.000
14.2 UN proper shipping name ADR, IMDG, IATA	RESIN SOLUTION
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E,S-D
14.7 Transport in bulk according to Annex II o	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

(Contd. of page 8)

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 30
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child.

· Classification according to Regulation (EC) No 1272/2008

*Art.* 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 1B: Reproductive toxicity - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3