

Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: LOR C Series Resists

- · Article number: G713708, G713711, G713713, G713714, G713716
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Product category PC30 Photo-chemicals
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer:

Kayaku Advanced Materials

200 Flanders Road

Westborough, MA 01581

Telephone: (617) 965-5511

Fax: (617) 965-5818

Importer:

A-Gas Electronic Materials

Unit 3, IO Centre

Swift Valley

Rugby, Warwickshire

CV21 1TW, UK

Tel: +44-0-1788-537535 Fax: +44-0-1788-535835 Website: www.agasem.com

Email: customerservice.em@agas.com

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuAM.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency : 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Repr. 1B H360 May damage fertility or the unborn child.

(Contd. on page 2)



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

(Contd. of page 1)



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms









GHS05

GHS07

GHS08

· Signal word Danger

· Hazard-determining components of labelling:

gamma-Butyrolactone

Tetrahydrofurfuryl alcohol

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF ON SKIN: Wash with plenty of soap and water. P302+P352

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position P304+P341

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon

Store in a well-ventilated place. Keep cool. P403+P235

P501 Dispose of contents/container in accordance with local/regional/national/international

· Additional information:

Restricted to professional users.

(Contd. on page 3)



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

(Contd. of page 2)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:	
CAS: 120-92-3	Cyclopentanone	40-60%
EINECS: 204-435-9	🚸 Flam. Liq. 3, H226; 🕔 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
	gamma-Butyrolactone	25-50%
EINECS: 202-509-5	� Eye Dam. 1, H318; ◊ Acute Tox. 4, H302; STOT SE 3, H336	
CAS: 102322-80-5	Polyaliphatic imide copolymer	5-20%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 97-99-4	Tetrahydrofurfuryl alcohol	1-5%
EINECS: 202-625-6	🕸 Repr. 1B, H360; 🕠 Eye Irrit. 2, H319	
	Proprietary Dye B	<1%
	♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

(Contd. on page 4)



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

(Contd. of page 3)

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Use only under yellow light

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers:

Store in a cool location.

Store in inert atmosphere or keep well sealed to prevent the formation of peroxides and other oxidation products.

· Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

CD.



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Colour: Yellow-brown
Odour: Sweetish
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** 130 °C

(Contd. on page 6)



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

	(Contd. of page
Flash point:	<i>30 ℃ (クローズドカップ</i>)
Flammability (solid, gas):	Not applicable.
Ignition temperature:	430 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	2.7 Vol %
Upper:	15.6 Vol %
Vapour pressure at 20 °C:	1 hPa
Density:	Not determined
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Partly miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight. Contact with incompatible materials.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values rele	evant for classification:
120-92-3	Cyclopenta	none
Oral	LD50	1180 mg/kg (Rat)

(Contd. on page 7)



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

		(Contd. of page 6)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>19.5 mg/l (Rat)
96-48-0 ga	mma-Buty	vrolactone
Oral	LD50	1540 mg/kg (Rat)
Dermal	LD50	5000 mg/kg (gui)
		>5.1 mg/l (Rat)
97-99-4 Te	etrahydrofi	urfuryl alcohol
Oral	LD50	1600 mg/kg (Rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Experience with humans: No further relevant information available.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

May damage fertility or the unborn child.

- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic tox	cicity:
120-92-3 C	yclopentanone
EC50/48 h	100 mg/l (daphnia magna)
EC50/72 h	>100 mg/l (scenedesmus subspicatus)
LC50/96 h	>100 mg/l (fish)
96-48-0 gar	mma-Butyrolactone
EC50/17 h	>10000 mg/l (bacterium)
EC50/48 h	>500 mg/l (daphnia magna)
EC50/72 h	360 mg/l (green algae)
LC50/96 h	>220 - <460 mg/l (golden orfe)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 8)



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

(Contd. of page 7)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
14.1 UN-Number ADR, IMDG, IATA	UN1866	
14.2 UN proper shipping name ADR, IMDG, IATA	RESIN SOLUTION	
14.3 Transport hazard class(es)		
ADR, IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	
14.4 Packing group ADR, IMDG, IATA	III	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (Kemler code):	30	
EMS Number:	F-E,S-D	
14.7 Transport in bulk according to Annex II o	f	
Marpol and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	5L	
Transport category	3	
Tunnel restriction code	D/E	



Printing date 09.09.2022 Version number 5 Revision: 09.09.2022

Trade name: LOR C Series Resists

(Contd. of page 8)

· UN "Model Regulation":

UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuAM.com)
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 1B: Reproductive toxicity - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3