Revision: 03.05.2023



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.05.2023

Version number 5 (replaces version 4)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PermiNex® 2000 Series Resists
- · Article number: Y614022, Y614045, Y614058, Y614064
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU16 Manufacture of computer, electronic and optical products, electrical equipment
- · Product category PC30 Photo-chemicals
- · Application of the substance / the mixture Photoresist
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kayaku Advanced Materials, Inc.

200 Flanders Road Westborough, MA 01581

Tel: (617) 965-5511 Fax: (617) 965-5818

· Further information obtainable from:

Product Safety

Email: productsafety@kayakuam.com

· 1.4 Emergency telephone number:

Kayaku Advanced Materials : 617-965-5511 Chemtrec USA Emergency : 800-424-9300 (24 hr)

Chemtrec International Emergency: 703-527-3887 (24 hr)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 03.05.2023 *Version number 5 (replaces version 4)* Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 1)

· Hazard pictograms







GHS07

· Signal word Warning

Hazard-determining components of labelling:

Epoxy Resin M2

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF SWALLOWED: Immediately call a POISON CENTER/doctor. P301+P310

IF ON SKIN: Wash with plenty of soap and water. P302+P352

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 *If eye irritation persists: Get medical advice/attention.*

In case of fire: Use to extinguish: Alcohol resistant foam, Fire-extinguishing powder, Carbon P370+P378

dioxide.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

41.8 % of the mixture consists of component(s) of unknown toxicity.

Contains 59.2 % of components with unknown hazards to the aquatic environment.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- · **PBT**: Not applicable.
- · **vPvB**: Not applicable.

· Determination of endocrine-disrupting properties

None of the ingredients are included in the list established in accordance with Article 59(1) for having endocrine disrupting properties.

None of the ingredients are substances identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (or Commission Regulation (EU) 2018/605.



Printing date 03.05.2023 Version number 5 (replaces version 4) Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

- . 3 2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 120-92-3 EINECS: 204-435-9 Index number: 606-025-00-9 Reg.nr.: 01-2119495595-21-0000	Cyclopentanone Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2, H319	15-75%
	Epoxy Resin M2 Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	5-25%
	Epoxy Resin M3 Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	1-10%
CAS: 2530-83-8 EINECS: 219-784-2	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318	<1.5%
· Additional Components:		
Proprietary modified epoxy resin		15-50%
Proprietary Photoacid Generator		<1.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Wash eyes immediately with a large amount of water or normal saline, occasionally lifting upper and lower eye lids until no evidence of chemical remains (about 20 minutes). Remove contact lenses if present and easy to remove. Seek immediate medical attention.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam Fire-extinguishing powder

ABC powder

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

(Contd. on page 4)



Printing date 03.05.2023 Version number 5 (replaces version 4) Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 3)

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers:

Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.

Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)



Printing date 03.05.2023 Version number 5 (replaces version 4) Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 4)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of low exposure use cartridge respirator. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Long-sleeved work clothes

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- General Information

· Physical state Liquid

· Colour: Clear to light yellow

· Odour: Mild

· Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point

and boiling range 130 °C

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: 1.3 Vol %
 Upper: 0.0 Vol %
 Flash point: 30 °C
 Auto-ignition temperature: 430 °C

• **Decomposition temperature:** Not determined.

• **pH** Not determined.

Not determined.

(Contd. on page 6)



Printing date 03.05.2023 Version number 5 (replaces version 4) Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

					(Contd. of pag
Viscosity:					
Kinematic viscosity	Not determ				
Dynamic:	Not determ	nined.			
Solubility					
water:	Not miscil	ble or diffic	rult to mix.		
Partition coefficient n-octanol/water					
(log value)	Not determ	nined.			
Vapour pressure at 20 °C:	11 hPa				
Density and/or relative density					
Density:	Not determ				
Relative density	See Other information				
Vapour density	Not determined.				
9.2 Other information	Name	Number	Sp. Grav.	VOC(%by wt.)	VOC(g/L)
	PN 2001	Y614022	1.0018	70-75	710
	PN 2005	Y614045	1.0619	40-45	445
	PN 2010	Y614058	1.1020	25-30	290
	PN 2015	Y614064	1.1220	15-20	190
Appearance:					
Form:	Liquid				
Important information on protection of					
health and environment, and on safety.					
Ignition temperature:	Product is	not selfign	iiting.		
Explosive properties:	Product is	s not explo	sive. How	ever, formation	of explosive air/vapo
	mixtures a	ire possible	2.		
Change in condition					
Evaporation rate	Not determ	nined.			
Information with regard to physical					
hazard classes					
Evnlosivas	Void				
Lapiosives					
Explosives Flammable gases	Void				
Explosives Flammable gases Aerosols	Void Void				
Flammable gases					
Flammable gases Aerosols	Void				
Flammable gases Aerosols Oxidising gases	Void Void				
Flammable gases Aerosols Oxidising gases Gases under pressure	Void Void				
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	Void Void				
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable liquid and vapour.	Void Void Void				
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable liquid and vapour. Flammable solids	Void Void Void Void				
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable liquid and vapour. Flammable solids Self-reactive substances and mixtures	Void Void Void Void Void				
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable liquid and vapour. Flammable solids Self-reactive substances and mixtures Pyrophoric liquids	Void Void Void Void Void Void				
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable liquid and vapour. Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids	Void Void Void Void Void Void Void				
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable liquid and vapour. Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures	Void Void Void Void Void Void Void				
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable liquid and vapour. Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water	Void Void Void Void Void Void Void				
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable liquid and vapour. Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids	Void Void Void Void Void Void Void				
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable liquid and vapour. Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Oxidising solids	Void Void Void Void Void Void Void Void				
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable liquid and vapour. Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids	Void Void Void Void Void Void Void Void				



Printing date 03.05.2023 Version number 5 (replaces version 4) Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 6)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- · 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Contact with incompatible materials.

- · 10.5 Incompatible materials: Strong Oxidizing Agents, Strong Acids, Strong Bases
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Corrosive gases/vapours

Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
Epoxy Res	Epoxy Resin M2		
Oral	LD50	>2000 mg/kg (Rat)	
2530-83-8	2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane		
Oral	LD50	8030 mg/kg (Rat)	
Dermal	LD50	4248 mg/kg (Rat)	
Inhalative	plative $ LC50/4 > 5.3 \text{ mg/l (Rat)}$		
120-92-3 (120-92-3 Cyclopentanone		
Oral	LD50	1820 mg/kg (Rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	tive LC50/4 h 19.5 mg/l (Rat)		

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.



Printing date 03.05.2023 Version number 5 (replaces version 4) Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 7)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic tox	· Aquatic toxicity:		
2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane			
LC50/96 h	55 mg/l (Cyprinus carpio (common carp))		
EC50/48 h	30 mg/l (daphnia magna)		
EC50/72 h	255 mg/l (Desmodesmus subscipatus (green algae))		
120-92-3 Cy	120-92-3 Cyclopentanone		
LC50/48 hr	2950 mg/L (golden orfe)		
LC50/96 h	>100 mg/l (fish)		
EC50/48 h	3600 mg/l (Ceriodaphnia dubia (water flea))		
	100 mg/l (daphnia magna)		
EC50/72 h	>100 mg/l (scenedesmus subspicatus)		

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made in accordance with International, National, and regional regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number	•
· ADR, IMDG, IATA	UN1866

· 14.2 UN proper shipping name

· ADR, IATA RESIN SOLUTION

· IMDG RESIN SOLUTION, MARINE POLLUTANT

(Contd. on page 9)



Printing date 03.05.2023 Version number 5 (replaces version 4) Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

	(Contd. of page
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
·Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substance Formaldehyde, polymer with 1-chloro-2,3-epoxypropane an phenol
· 14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
· 14.7 Maritime transport in bulk according to IM instruments	IO Not applicable.
Transport/Additional information:	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
Transport estacom	Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	D/E
	2/2
· IMDG · Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
2	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 10)



Printing date 03.05.2023 Version number 5 (replaces version 4) Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 9)

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Art. 9(1) of Regulation (EC) No. 1272/2008 was used for classification purposes.

- · Department issuing SDS: Product safety department
- · Contact: Tom Cole, EHS Manager (tcole@kayakuam.com)
- · Revision History:

The manufacturer's information in Section 1, the product hazard information in Section 2 and the component hazard information in Section 3 have been updated.

- · Version number of previous version: 4
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2



Printing date 03.05.2023 Version number 5 (replaces version 4) Revision: 03.05.2023

Trade name: PermiNex® 2000 Series Resists

(Contd. of page 10)

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

EII.